C326

Manual Trans Harness

Back-up light switch

1661778C1

Pin	Circuit	Circuit Function
A	295 (LB/PK)	Fused run to back up switch
B	140 (BK/PK)	Back up lamp feed

C333

Allison LCT Trans Harness

Turbine speed sensor

2036583C1

Pin	Circuit	Circuit Function
A	213 (DB/YE)	Turbine speed sensor to ECU
B	214 (PK/LB)	Turbine speed sensor to ECU

C329

IP Harness

Shift selector



3518285C1

Pin	Circuit	Circuit Function
A	170 (RD/LB)	Primarey shift selector data 1
B	171 (BK/WH)	Primarey shift selector data 2
C	172 (LB/RD)	Primarey shift selector data 4
D	173 (DG/VT)	Primarey shift selector data 8
E	174 (GY/BK)	Primarey shift selector parity
L	—	Not used
M	175 (BK/YE)	Selector mode switch
N	124 (BN)	Sensor power selector
P	143 (LB/YE)	Shift selector batt -
R	136 (DB/YE)	Shift selector batt +
S	180 (RD)	Selector mode switch
T	186 (BN/LB)	Ground circuit
U	187 (DB/OG)	Illumination
V	188 (WH/BK)	Ground circuit

C341

Allison LCT Harness

NSBU switch vehicle
(neutral safety back-up)



3534635C1

Pin	Circuit	Circuit Function
A	—	Not used
B	—	Not used
C	295 (LB/PK)	Fused run feed to switch
D	220 (VT/OG)	NSBU switch to ECU
E	325 (DB/OG)	Module, ignition - crank enable
F	140 (BK/PK)	Back up lamp feed
G	32 (RD/LB)	Starter control