C2168

14401

D54
Program remote keyless entry module connector



F02090

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	25 (DB/OG)	Anti–theft

C2169

14401

P29
Non–Daytime running lamps jumper



F08050

Pin	Circuit	Circuit function
1	–	not used
2	15 (RD/YE)	Power, Hot with Headlamps on
3	57 (BK)	Ground
4	13 (RD/BK)	Power, Hot with Low Beams on
5	471 (OG/LG)	Daytime running lamps resistor, to, Headlamp relay
6	295 (LB/PK)	Voltage in Run (overload protected)
7	1033 (RD/YE)	Daytime Running Lamps (DRL) relay, Relay, switched power
8	–	not used

C2171

14401

B8
Throttle Position Sensor (TPS) (9B989)



F04269

Pin	Circuit	Circuit function
1	21 (DK/LG)	Powertrain Control Module (PCM) (12A650) – Flexible fuel sensor
2	216 (TN/RD)	Throttle Position Sensor (TPS) (9B989), input
3	–	not used
4	359 (GY/RD)	signal, return

C2172

14401

N616
Idle validation switch



F02072

Pin	Circuit	Circuit function
1	1285 (RD/LG)	Idle validation switch, control
2	1140 (VT)	PCM power relay, Switched, Power (Start or Run)