PIN	CIRCUIT	CIRCUIT FUNCTION
96	390 (TN/YE)	Heated Oxygen Sensor (HO2S) #22 Heater
97	361 (RD)	Power (VPWR)
98	562 (LB)	Fuel Injector #8 Control
99	560 (LG/OG)	Fuel Injector #6 Control
100	558 (BN/LB)	Fuel Injector #4 Control
101	556 (WH)	Fuel Injector #2 Control
102	–	NOT USED
103	570 (BK/WH)	Power Ground
104	529 (RD/YE)	Ignition Coil #4

CONNECTOR REFERENCE LIST

CONNECTOR	SECTION-PAGE
C286	62-7
C287	62-7
C291	14-2
C2001	41-4
C2008	69-3



C311

FUEL TANK ASSEMBLY (HARNESS SIDE)

PIN	CIRCUIT	CIRCUIT FUNCTION
1	–	NOT USED
2	359 (GY/RD)	Signal Return
3	791 (RD/PK)	Fuel Tank Pressure Sensor Output
4	351 (BN/WH)	Reference Voltage
5	29 (YE/WH)	Instrument Cluster Output
6	57 (BK)	Ground
7	787 (PK/BK)	Inertia Fuel Shutoff Output
8	651 (BK/YE)	Ground