C1030

14290

A253
Daytime Running Lamps (DRL) module



F06110

Pin	Circuit	Circuit function
1	13 (RD/BK)	Power, Hot with Low Beams on
2	477 (LB/BK)	Voltage supplied at all times (overload protected)
3	298 (VT/OG)	Voltage in Run (overload protected)
4	1205 (BK)	Ground
5	12 (LG/BK)	Power, Hot with High Beams on
6	22 (LB/BK)	Brake feed

C1033

14B060



F02085

12B637



F02072

(1) 31 (WH/RD)
(2) –

C1035a

12B637
14305
14B060

P93
Battery Junction Box (BJB) (14A003)

F01025

Pin	Circuit	Circuit function
1	290 (GY)	Voltage supplied at all times (fusible link)
	290 (GY)	Voltage supplied at all times (fusible link)

C1035b

14B060

P93
Battery Junction Box (BJB) (14A003)



F01129

Pin	Circuit	Circuit function
1	2037 (RD)	Battery cable +

C1041

14290

E7
Headlamp, right (13008)



F03169

Pin	Circuit	Circuit function
1	12 (LG/BK)	Power, Hot with High Beams on
2	1205 (BK)	Ground
3	1056 (DB/LG)	Headlamp, right (13008) – fused feed