C2145c

14401

A200
Lighting control
module



F13013

Pin	Circuit	Circuit function
1	932 (GY/WH)	High beam lamp, feed
2	905 (PK)	Power, Battery Power, Hot at all times
3	484 (OG/BK)	Cigar lighter, front (15055)
4	705 (LG/OG)	Battery saver relay, switched power
5	1056(DB/LG)	fused feed, Hot at all times
6	161 (DG/OG)	Low beam lamp, right front, feed
7	910 (PK)	Voltage supplied at all times (overload protected)
8	–	not used
9	54 (LG/YE)	Voltage supplied at all times (overload protected)
10	53 (BK/LB)	Interior lamp relay, switched power, output
11	–	not used
12	–	not used
13	676 (PK/OG)	Ground

C2145d

14401

A200
Lighting control
module



F13015

Pin	Circuit	Circuit function
14	1055 (WH/LG)	Headlamp, left (13008) – fused feed
15	160 (DB/WH)	Headlamp, left (13008), (Low beam lamp feed)
16	195 (TN/WH)	Voltage supplied at all times (overload protected)
17	44 (LB)	Turn signal flasher, to turn signal switch
18	44 (LB)	Turn signal flasher, to turn signal switch
19	12 (LG/BK)	Power, Hot with High Beams on
20	–	not used
21	–	not used
22	14 (BN)	Power, Exterior lamps
23	385 (WH/RD)	Voltage supplied at all times (overload protected)
24	385 (WH/RD)	Voltage supplied at all times (overload protected)
25	–	not used
26	28 (BK/PK)	Wiper run/park relay, switched power