C4209 (GY)

14A005

Navigation module



F24021

Pin	Circuit	Circuit function
1	828 (VT/LB)	Voltage supplied at all times (overload protected)
2	1523 (DG)	Fused accessory relay, switched power, output
3	–	not used
4	914 (TN/OG)	Standard Corporate Protocol (SCP) data +
5	1532 (DB/WH)	CAN Bus +
6	–	not used
7	1196 (DG/WH)	Microphone +
8	1534 (BK)	video R
9	1536 (BK)	video B
10	1538 (BK)	video, return
11	1530 (LB)	audio +
12	1531 (LG)	audio –
13	694 (BK/LG)	Ground
14	679 (GY/BK)	Vehicle Speed Sensor (VSS) +
15	–	not used
16	915 (PK/LB)	Standard Corporate Protocol (SCP) data –
17	1533 (DB/OG)	CAN Bus –
18	–	not used
19	1197 (LB/BK)	Microphone –
20	–	not used
21	1535 (BK)	video G
22	1537 (RD)	video, signal
23	48	Shield
24	48	Shield

C4211a (GY)

14A005

Navigation system amplifier



F24021

Pin	Circuit	Circuit function
1	720 (RD/YE)	Voltage supplied at all times (overload protected)
2	280 (LG)	audio, left front +
3	857 (WH/OG)	audio, left front –
4	168 (RD/BK)	audio, Subwoofer +
5	167 (BN/OG)	audio, Subwoofer –
6	277 (LB/BK)	audio, left rear +
7	859 (YE)	audio, left rear –
8	–	not used
9	–	not used
10	–	not used
11	–	not used
12	694 (BK/LG)	Ground
13	720 (RD/YE)	Voltage supplied at all times (overload protected)
14	279 (WH/RD)	audio, right front +
15	858 (BN)	audio, right front –
16	–	not used
17	–	not used
18	278 (VT/WT)	audio, right rear +
19	855 (LB)	audio, right rear –
20	–	not used
21	–	not used
22	173 (DG/VT)	audio, Subwoofer, High, mute
23	–	not used
24	694 (BK/LG)	Ground