C341g (GY)

14C719

Driver seat module (14C708)



F10135

Pin	Circuit	Circuit function
1	1003 (GY/YE)	Voltage supplied at all times (overload protected)
2	693 (OG)	UBP Diagnostics
3	268 (BK/OG)	Memory seat switch, position 2
4	267 (BN/LG)	Memory seat switch, position 1
5	270 (BN/OG)	Memory set switch (14776)
6	1203 (BK/LB)	Ground
7	1491 (LB/YE)	Adjustable pedal memory potentiometer, monitor
8	1493 (PK/BK)	Adjustable pedal switch, Forward Circuit
9	1492 (LB/RD)	Adjustable pedal switch, Rearward Circuit
10	272 (WH/OG)	Memory set switch (14776), Illumination control

C350 (BK)

* with IVD

7A786

Transfer case assembly



F16020

Pin	Circuit	Circuit function
1	770 (WH)	Motor position 3
2	*772 (LB)	Four–wheel drive control module, to, Transfer case speed sensor, rear
3	*774 (LG)	Sensor, voltage
4	*236 (BK/LG)	Four–wheel drive control module, to, Transfer case speed sensor, front
5	771 (VT/YE)	Motor position 4
6	*359 (GY/RD)	signal, return
7	*774 (LG)	Sensor, voltage
8	*359 (GY/RD)	signal, return
9	764 (BN/WH)	Motor position 2
10	762 (YE/WH)	Motor position 6, Ground
11	976 (OG)	clutch, Coil, return
12	–	not used
13	763 (OG/WH)	Motor position 1
14	778 (OG)	motor, control, clockwise rotation
15	777 (YE)	motor, control, clockwise rotation
16	779 (BN)	Four–wheel drive control module to Differential lock solenoid