C278 (NA)

14401

Brake pedal position switch (13480)



F05111

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	810 (RD/LG)	Brake pedal position switch (13480), input
3	276 (BN)	Voltage supplied at all times (overload protected)
4	511 (LG)	Brake pedal position switch (13480), to stoplamps
5	10 (LG/RD)	Voltage supplied at all times (overload protected)

C279 (BK)

14401

Transmission control switch



F02259

Pin	Circuit	Circuit function
1	298 (VT/OG)	Voltage in Run (overload protected)
2	224 (TN/WH)	PCM, to transmission overdrive cancel switch

C281a (BK)

14401

Four–wheel drive control module



F17005

Pin	Circuit	Circuit function
1	931 (OG)	Voltage supplied at all times (overload protected)
2	704 (DG/LG)	Voltage supplied at all times (overload protected)
3	–	not used
4	70 (LB/WH)	ISO Bus
5	465 (WH/LB)	Four–wheel drive control module to Four–wheel drive switch
6	–	not used
7	57 (BK)	Ground
8	778 (OG)	Four–wheel drive control module, to Transfer case assembly
9	1003 (GY/YE)	Voltage in Run (overload protected)
10	–	not used
11	771 (VT/YE)	Motor position 5
12	810 (RD/LG)	Brake pedal position switch (13480), input
13	–	not used
14	–	not used
15	770 (WH)	Motor position 4
16	463 (RD/WH)	Neutral, switch sense, input
17	777 (YE)	Four–wheel drive control module, to Transfer case assembly