C287

14401

B241
Photocell and amplifier



F06163

Pin	Circuit	Circuit Function
1	468 (BN)	Sunload sensor, input
2	218 (WH/VT)	Autolamp relay, control
3	–	not used
4	–	not used
5	398 (BK/YE)	Ground
6	–	not used

C289

19D570/19D887

M256
Temperature blend door actuator



F08015

Pin	Circuit	Circuit Function
1	437 (YE/LG)	with EATC, Air temperature door variable resistor, wiper
	351 (BN/WH)	manual A/C, Reference, voltage
2	–	with EATC, not used
	–	manual A/C, not used
3	–	with EATC, not used
	437 (YE/LG)	manual A/C, Air temperature door variable resistor, wiper
4	–	with EATC, not used
	438 (RD/WH)	manual A/C, Air temperature door variable resistor -
5	438 (RD/WH)	with EATC, Air temperature door variable resistor -
	–	manual A/C, not used
6	436 (RD/LG)	with EATC, Air temperature door variable resistor +
	436 (RD/LG)	manual A/C, Air temperature door variable resistor +
7	249 (DB/LG)	with EATC, Power, Blend door actuator
	1087 (OG)	manual A/C, Voltage in Run (overload protected)
8	250 (OG)	with EATC, Power, Blend door actuator
	57 (BK)	manual A/C, Ground

C291

14401



F02034

14A411



F02056