C4014 (BK)

13A409

Parking Aid Module
(PAM) (15K866)



F26025

Pin	Circuit	Circuit function
1	1040 (RD/BK)	Voltage supplied in Start and Run (overload protected)
2	–	not used
3	1205 (BK)	Ground
4	–	not used
5	70 (LB/WH)	ISO Bus
6	–	not used
7	400 (LB/BK)	On/Off signal
8	–	not used
9	140 (BK/PK)	Voltage supplied in reverse
10	1443 (WH/LB)	Parking Aid Module (PAM) (15K866) to Parking aid sensor, inner left (15K859), input
11	1444 (DB/YE)	Parking Aid Module (PAM) (15K866) to Parking aid sensor, outer left (15K859), input
12	–	not used
13	–	not used

Pin	Circuit	Circuit function
14	1437 (BK/PK)	Parking aid speaker +
15	1439 (BN/PK)	Parking Aid Module (PAM) (15K866), Sensor, Power
16	1440 (DG/YE)	Parking Aid Module (PAM) (15K866), Sensor, return
17	1438 (DG)	Parking aid speaker –
18	–	not used
19	401 (PK)	On/Off signal, Light emitting diode (LED), control
20	–	not used
21	–	not used
22	–	not used
23	1441 (WH/LG)	Parking Aid Module (PAM) (15K866) to Parking aid sensor, inner right (15K859), input
24	1442 (DG/WH)	Parking Aid Module (PAM) (15K866) to Parking aid sensor, outer right (15K859), input
25	–	not used
26	–	not used