C930 (BK)

14A504

Overhead console



F12056

Pin	Circuit	Circuit function
1	294 (WH/LB)	Voltage in Run (overload protected)
2	875 (BK/LB)	Ground
3	679 (GY/BK)	Vehicle Speed Sensor (VSS) +
4	19 (LB/RD)	Instrument illumination, feed
5	767 (LB/OG)	Ambient air temperature sensor (19E702), feed
6	470 (PK/BK)	Sensor signal return (reference/ground)
7	53 (BK/LB)	Interior lamp relay, switched power, output
8	705 (LG/OG)	Battery saver relay, switched power
9	57 (BK)	Ground
10	1173 (BN/OG)	Roof opening panel switch (15B691), common
11	1174 (WH/RD)	Roof opening panel switch (15B691), Open, signal
12	1175 (TN/RD)	Roof opening panel switch (15B691), closed, signal

C934 (GY)

14A504



F06138

(1) 400 (LB/BK)
(2) 1173 (BN/OG)
(3) –
(4) 1175 (TN/RD)
(5) 1174 (WH/RD)
(6) 57 (BK)

PIA



F06339

(1) (PK)
(2) (BN/OG)
(3) –
(4) (TN/RD)
(5) (WH/PK)
(6) (BK)