C1030 (GY)

14398

Daytime Running Lamps (DRL) module



F06347

Pin	Circuit	Circuit function
1	13 (RD/BK)	Power, Hot with Low Beams on
2	434 (LB/BK)	Voltage supplied at all times (overload protected)
3	932 (GY/WH)	Voltage supplied in Start and Run (overload protected)
4	1203 (BK/LB)	Ground
5	12 (LG/BK)	Power, Hot with High Beams on
6	162 (LG/RD)	Parking brake switch (15A851)

C1035a

14A280

Battery Junction Box (BJB) (14A003)



F01019

Pin	Circuit	Circuit function
1	36 (BK/OG)	Voltage supplied at all times (overload protected)

C1035b

14A280

Battery Junction Box (BJB) (14A003)



F01019

Pin	Circuit	Circuit function
1	2037 (RD)	Battery cable +

C1040 (BK)

14398

High beam lamp, right front



F02629

Pin	Circuit	Circuit function
1	12 (LG/BK)	Power, Hot with High Beams on
2	1205 (BK)	Ground

C1041 (BK)

14A408

Headlamp, right (13008)



F03169

Pin	Circuit	Circuit function
1	12 (LG/BK)	Power, Hot with High Beams on
2	1205 (BK)	Ground
3	161 (DG/OG)	Headlamp, right (13008), (Low beam lamp feed)