C3019

19D887

Auxiliary temperature actuator



E8OB-14489-RA (F)

Pin	Circuit	Circuit Function
1	—	not used
2	—	not used
3	1125 (BN)	Aux climate control - blend door pot. Return
4	—	not used
5	—	not used
6	—	not used
7	1003 (GY/YE)	Fused ignition "run" to module, GEM-input
8	1205 (BK)	General ground (type 4 ground)

C3020

19D887

Auxiliary mode actuator



E8OB-14489-RA (F)

Pin	Circuit	Circuit Function
1	—	not used
2	—	not used
3	—	not used
4	—	not used
5	—	not used
6	—	not used
7	1129 (BN/WH)	Aux climate control - mode door pot. Return
8	1128 (GY/LB)	Aux climate control - mode door pot. Positive

C3021

19D887

Auxiliary blower motor



E6DB-14489-ALA (F)

Pin	Circuit	Circuit Function
1	371 (PK/WH)	Blower motor relay to motor
2	515 (OG/RD)	Resistor to blower motor (hi)

C3022

19D887

Auxiliary blower motor resistor assembly



1L2T-14A464-DA (F)

Pin	Circuit	Circuit Function
1	261 (OG/BK)	Blower motor to switch (hi)
2	515 (OG/RD)	Resistor to blower motor (hi)
3	269 (LB/OG)	Heater blower motor to switch (medium)
4	260 (RD/OG)	Blower motor to switch (lo)

C3023

19D887

Auxiliary A/C relay



F3DB-14489-BA (F)

Pin	Circuit	Circuit Function
85	1205 (BK)	General ground (type 4 ground)
86	575 (YE/BK)	Relay to ATC control
87	371 (PK/WH)	Blower motor relay to motor
87A	—	not used
30	181 (BN/OG)	Blower motor feed