C270f

14A005

P91
Central Junction
Box (CJB) (14A068)



F07083

Pin	Circuit	Circuit function
1	–	not used
2	1389 (WH)	Rear Electronic Module (REM), to, Heated backlight relay, control
3	1332 (LB)	Accessory delay relay, control
4	956 (OG/LG)	Voltage supplied at all times (overload protected)
5	400 (LB/BK)	Accessory relay, switched power, output
6	186 (BN/LB)	Rear window defrost relay, switched power
7	536 (BK/LG)	Blower motor relay, Blower motor

C270g

14A005

P91
Central Junction
Box (CJB) (14A068)



F08167

Pin	Circuit	Circuit function
1	1455 (GY/RD)	Fused battery feed, SSP 3 relay, output
2	1330 (YE/LB)	Front Electronic Module (FEM) (13C788), to, SSP 3 relay, SSP 4 relay
3	1458 (VT/WH)	Fused battery feed, SSP 3 relay, output, to, courtesy lamps
4	1456 (RD/LB)	Fused battery feed, SSP 3 relay, to, High mounted stop lamp
5	400 (LB/BK)	Accessory relay, switched power, output
6	1457 (RD/YE)	Fused battery feed, SSP 4 relay, output
7	194 (PK)	Voltage in Run or Accessory (overload protected)
8	1454 (TN/RD)	Fused battery feed, SSP 3 relay, to, Rear Electronic Module (REM)

C271

14401

M200
Front blower motor
speed controller
(19E624)



F04247

Pin	Circuit	Circuit function
1	1205 (BK)	Ground
2	261 (OG/BK)	Blower motor, to switch – High
3	269 (LB/OG)	Heater blower motor (19805), to, Heater blower switch
4	260 (RD/OG)	Blower motor relay, control