C357 (BN)

14C719

Power seat motor assembly, left



F06339

Pin	Circuit	Circuit function
1	980 (YE/WH)	Fwd/Rwd motor, +/–
2	983 (RD/LG)	Rear height motor, +/–
3	982 (YE/LG)	Rear height motor, +/–
4	981 (RD/WH)	Fwd/Rwd motor, +/–
5	978 (YE/LB)	Front height motor, +/–
6	979 (RD/LB)	Front height motor, +/–

C359 (GY)

14C719

Heated seat module, driver side front



F12205

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	–	not used
3	1061 (BN/LB)	Seat cushion heater, driver side, Sensor, return
4	1060 (BK/LB)	Seat cushion heater, driver side, Sensor, feed
5	1003 (GY/YE)	Voltage in Run (overload protected)
6	1064 (YE/LB)	Seat cushion heater, driver side, heater, feed
7	1067 (VT/LB)	Lumbar adjust switch, driver side, heater, return
8	1020 (DG/VT)	Seat heater switch, passenger side, to, Heated seat module, passenger side front, Enable
9	–	not used
10	1255 (WH/RD)	Heated seat switch, driver side, Heated seat module, driver side front, to, Enable
11	–	not used
12	1048 (LB/WH)	Voltage supplied at all times (overload protected)

C361 (GY)

14C719

Lumbar adjust switch, left front (14B691)



F02073

Pin	Circuit	Circuit function
1	490 (RD)	Front seat lumbar compressor motor, feed
2	566 (DG)	Voltage supplied at all times (overload protected)