C1183

9H589

Y110
Injector 3 (9F593)



F02351

Pin	Circuit	Circuit function
1	361 (RD)	Voltage supplied in Start and Run (overload protected)
2	557 (BN/YE)	Injector 3, control

C1184

9H589

Y111
Injector 4 (9F593)



F02351

Pin	Circuit	Circuit function
1	361 (RD)	Voltage supplied in Start and Run (overload protected)
2	558 (BN/LB)	Injector 4, control

C1189

9H589

B8
Throttle Position
Sensor (TPS)
(9B989)



F03215

Pin	Circuit	Circuit function
1	89 (OG)	signal, return
2	355 (GY/WH)	Throttle Position Sensor (TPS) (9B989), input
3	351 (BN/WH)	Reference, voltage

C1195

14290

P133
Vapor management
valve



F02103

Pin	Circuit	Circuit function
1	34 (LB/OG)	Voltage supplied in Start and Run (overload protected)
2	191 (LG/BK)	Powertrain Control Module (PCM) (12A650), EVAP canister purge valve

C1197

14290

K359
Medium speed fan
control relay



F05107

Pin	Circuit	Circuit function
30	3829 (LB/BK)	Medium speed fan control relay, output
85	3886 (DB/GY)	Medium speed fan control relay, control
86	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
87	60 (BK/LG)	Voltage supplied at all times (overload protected)
87A	–	not used

C2007

14401

A271
Passive anti–theft
transceiver



F04245

Pin	Circuit	Circuit function
1	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
2	57 (BK)	Ground
3	167 (BN/OG)	TX, signal
4	168 (RD/BK)	RX, signal