C1432 (BK)

12A581

Brake pressure switch (2B264)



F02203

Pin	Circuit	Circuit function
1	307 (BK/YE)	Brake pressure switch (2B264), output
2	10 (LG/RD)	Voltage supplied at all times (overload protected)

C2003 (GY)

14401

Adjustable pedal motor (2C429)



F06249

Pin	Circuit	Circuit function
1	–	not used
2	–	not used
3	–	not used
4	–	not used
5	1495 (WH)	Adjustable pedal motor (2C429) – Rearward
6	1494 (RD)	Adjustable pedal motor (2C429) – Forward

C2008 (BK)

14401

Brake shift interlock



F03080

Pin	Circuit	Circuit function
1	1003 (GY/YE)	Voltage in Run (overload protected)
2	57 (BK)	Ground
3	810 (RD/LG)	Brake pedal position switch (13480), output

C2013a (GY)

14401

Belt minder module



F04143

Pin	Circuit	Circuit function
1	450 (DG/LG)	Safety belt indicator, control
2	85 (BN/LB)	Safety belt buckle switch (10B924), input
3	–	not used
4	257 (WH/RD)	Hot in Park or Head

C2013b (GY)

14401

Belt minder module



F04143

Pin	Circuit	Circuit function
1	640 (RD/YE)	Voltage supplied in Start and Run (overload protected)
2	–	not used
3	–	not used
4	875 (BK/LB)	Ground