C1048a

14290

Engine cooling fan motor

F02499

Pin	Circuit	Circuit function
1	29-PA6 (OG/YE)	Voltage supplied at all times (overload protected)
2	31-PA6 (BK/YE)	Ground

C1048b

14290

Engine cooling fan motor



F02066

Pin	Circuit	Circuit function
1	32-PA45 (WH/BU)	Switched between: Battery voltage, Ground or Open
2	–	not used

C1166

15A434

Driving lamp, left (13411)



F02095

Pin	Circuit	Circuit function
1	31-LD11 (BK/WH)	Ground
2	30S-LD11 (RD/WH)	Voltage supplied at all times (not overload protected), switch

C1167

15A434

Driving lamp, right (13411)



F02095

Pin	Circuit	Circuit function
1	31-LD17 (BK/WH)	Ground
2	30S-LD17 (RD/WH)	Voltage supplied at all times (not overload protected), switch

C1168 (GY)

18C463



F06142

(1) 30S-FB1 (RD/YE)
(2) 31-FB1 (BK/YE)
(3) 91S-FB3 (BN/BU)
(4) 30-FB3 (RD/OG)
(5) –
(6) 91S-FB4 (BN/GN)

14290



F06177

(1) 30S-FB1 (RD/YE)
(2) 31-FB1 (BK/YE)
(3) 91S-FB3 (BK/OG)
(4) 30-FB3 (RD/OG)
(5) –
(6) 91S-FB4 (BK/GN)