C1370

12B637

Variable valve timing solenoid 2



F02607

Pin	Circuit	Circuit function
1	15S-RL26 (GN/WH)	Voltage supplied in Start and Run (overload protected)
2	8-RL26 (WH/VT)	Variable valve timing solenoid 2, control

C1371

12B637

Inlet Manifold Runner Control (IMRC) solenoid 1



F02105

Pin	Circuit	Circuit function
1	15S-RL20 (GN/OG)	Voltage supplied in Start and Run (overload protected)
2	91S-RL20 (BK/RD)	Inlet Manifold Runner Control (IMRC) solenoid 1, control

C1372

12B637

Inlet Manifold Runner Control (IMRC) solenoid 2



F02105

Pin	Circuit	Circuit function
1	15S-RL40 (GN/BK)	Voltage supplied in Start and Run (overload protected)
2	91S-RL40 (BK/GN)	Inlet Manifold Runner Control (IMRC) solenoid 2, control

C1379

14290

High intensity discharge headlamp relay, left



F05110

Pin	Circuit	Circuit function
1	29S-LE16 (OG/GN)	fused feed, Switched System Power (SSP) 2
2	91S-LE16 (BN/YE)	High intensity discharge headlamp relay, left, control
3	29S-LE31 (OG/YE)	fused feed, Switched System Power (SSP) 2
4	–	not used
5	30S-LE16 (RD/BK)	High intensity discharge headlamp relay, left, switched power, output