C2089

14401

N449
Adjustable pedal switch



F07055

Pin	Circuit	Circuit function
1	1495 (WH)	Adjustable pedal switch, Rearward
2	566 (DG)	Voltage supplied at all times (overload protected)
3	57 (BK)	Ground
4	57 (BK)	Ground
5	19 (LB/RD)	Instrument illumination, feed
6	57 (BK)	Ground
7	1494 (RD)	Adjustable pedal switch, Forward

C2099

14401

N475
Passenger Air bag Deactivation (PAD) switch



F06052

Pin	Circuit	Circuit function
1	298 (VT/OG)	Voltage in Run (overload protected)
2	629 (BN)	Passenger Air bag Deactivation (PAD) switch, indicator, control
3	1112 (WH/LB)	Passenger Air bag Deactivation (PAD) switch, position, signal
4	649 (BK/OG)	Air bag, dedicated ground
5	–	not used
6	–	not used

C2107

14401

K377
Mechanical Shift On the Fly (MSOF) relay



F05110

Pin	Circuit	Circuit function
1	294 (WH/LB)	Voltage in Run (overload protected)
2	976 (OG)	Mechanical Shift On the Fly (MSOF) relay, control
3	704 (DG/LG)	Voltage supplied at all times (overload protected)
4	–	not used
5	779 (BN)	Mechanical Shift On the Fly (MSOF) relay, switched output