C1018

14290

V34
PCM Module power diode



F02009

Pin	Circuit	Circuit Function
1	546 (DG/YE)	Voltage supplied in Start and Run (overload protected)
2	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)
	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)

C1021

14290

E1
Headlamp, left



F03169

Pin	Circuit	Circuit Function
1	12 (LG/BK)	Power, Hot with High Beams on
2	57 (BK)	Ground
3	1055 (WH/LG)	Headlamp, left - fused feed

C1023

14290

E164
Park/turn lamp, left front



F03099

Pin	Circuit	Circuit Function
1	57 (BK)	Ground
2	14 (BN)	Power, Exterior lamps
3	3 (LG/WH)	Turn lamps, feed, left front

C1025

14290

N423
Deactivator switch



F02203

Pin	Circuit	Circuit Function
1	276 (BN)	Voltage in Run (overload protected)
2	307 (BK/YE)	Brake pressure switch, input

C1029

14290

Y134
EVAP canister purge valve



F02105

Pin	Circuit	Circuit Function
1	361 (RD)	Voltage supplied in Start and Run (overload protected)
2	191 (LG/BK)	Powertrain Control Module (PCM), EVAP canister purge valve

C1030

14290

A253
Daytime Running Lamps (DRL) module



F06110

Pin	Circuit	Circuit Function
1	13 (RD/BK)	Power, Hot with Low Beams on
2	54 (LG/YE)	Voltage supplied at all times (overload protected)
3	298 (VT/OG)	Voltage in Run (overload protected)
4	57 (BK)	Ground
5	12 (LG/BK)	Power, Hot with High Beams on
6	–	not used