C1107 (BK)

15525

Output Shaft Speed (OSS) sensor (7M101)



F02031

Pin	Circuit	Circuit function
1	1202 (BN/LG)	Output Shaft Speed (OSS) sensor (7M101), signal, return
2	136 (DB/YE)	Output Shaft Speed (OSS) sensor (7M101), signal

C1130 (GY)

12B637/9D930

Differential Pressure Feedback EGR (DPFE) sensor (9J460)



F03114

Pin	Circuit	Circuit function
1	352 (BN/LG)	Differential Pressure Feedback EGR (DPFE) sensor, signal
2	359 (GY/RD)	signal, return
3	351 (BN/WH)	Reference, voltage

C1134 (BK)

9D930

Ignition coil (12029)



F04162

Pin	Circuit	Circuit function
1	526 (DB/LG)	coil driver (CD) – A control
2	528 (PK/WH)	coil driver (CD) – C control
3	527 (RD/LB)	coil driver (CD) – B control
4	16 (RD/LG)	Voltage supplied in Start and Run (overload protected)

C1159 (GY)

12A581

Engine compartment lamp



F02071

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	705 (LG/OG)	Battery saver relay, switched power

C1171

13K027

Daytime Running Lamps (DRL) relay 1



F05110

Pin	Circuit	Circuit function
1	15 (RD)	Power, Hot with Headlamps on
2	57 (BK)	Ground
3	295 (LB/PK)	Voltage in Run (overload protected)
4	1032 (WH/BK)	Hot in Run, Headlamps Off
5	–	not used

C1172

13K027

Daytime Running Lamps (DRL) relay 2



F05110

Pin	Circuit	Circuit function
1	57 (BK)	Ground
	57 (BK)	Ground
2	1032 (WH/BK)	Hot in Run, Headlamps Off
3	13 (RD/BK)	Power, Hot with Low Beams on, output
4	1033 (RD/YE)	Power, Hot with Low Beams on
5	471 (OG/LG)	Voltage supplied at all times (overload protected)