C1008

14290

K107
A/C clutch relay



F05109

Pin	Circuit	Circuit Function
1	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
2	331 (PK/YE)	A/C clutch relay, control
3	883 (PK/LB)	Voltage supplied at all times (overload protected)
4	-	not used
5	321 (GY/WH)	A/C clutch relay, switched output
	321 (GY/WH)	A/C clutch relay, switched output

C1016

14290

K163
PCM power relay



F05107

Pin	Circuit	Circuit Function
30	175 (BK/YE)	Voltage supplied at all times (overload protected)
	175 (BK/YE)	Voltage supplied at all times (overload protected)
85	57 (BK)	Ground
86	296 (WH/VT)	Voltage supplied in Start and Run (overload protected)
87	100 (WH/RD)	PCM power relay, output
	361 (RD)	Voltage supplied in Start and Run (overload protected)
87A	-	not used

C1017

14290

K22
Starter relay



F05107

Pin	Circuit	Circuit Function
30	37 (YE)	Voltage supplied at all times (overload protected)
85	32 (RD/LB)	Voltage supplied in Start (overload protected)
86	1093 (TN/RD)	Power, Hot in Start with Park or Neutral
	1093 (TN/RD)	Power, Hot in Start with Park or Neutral
87	33 (WH/PK)	switched power, to starter solenoid
87A	-	not used

C1021

14290

E1
Headlamp, left



F03203

Pin	Circuit	Circuit Function
1	12 (LG/BK)	Switched, Ground
2	13 (RD/BK)	High beam lamp, Switched, Ground
3	1055 (WH/LG)	Headlamp, left - fused feed

C1023

14290

E164
Park/turn lamp, left front



F03099

Pin	Circuit	Circuit Function
1	57 (BK)	Ground
2	14 (BN)	Power, Exterior lamps
3	3 (LG/WH)	Turn lamps, feed, left front