C2103

14401

P5
Clutch triple function switch jumper



F06084

Pin	Circuit	Circuit function
1	33 (WH/PK)	Voltage supplied in Start (overload protected)
2	329 (PK)	Voltage supplied in Start (overload protected)
3	810 (RD/LG)	Brake pedal position switch (13480), input
4	306 (TN/LB)	Brake pedal position switch (13480), input
5	359 (GY/RD)	Signal return
	359 (GY/RD)	Signal return
6	199 (LB/YE)	Clutch pedal position switch, to, Powertrain Control Module (PCM) (12A650)

C2104 (GY)

14401



F04183

19A041



F04153

(1) 811 (DG/OG)
(2) 805 (WH/LG)
(3) 57 (BK)
(4) 761 (GY/RD)

C3014 (GY)

14401

A225
Driver safety belt retractor pretensioner



F04269

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	1080 (LG/BK)	Driver safety belt retractor pretensioner, return
3	85 (BN/LB)	Safety belt buckle switch (10B924), input
4	1079 (LG/RD)	Driver safety belt retractor pretensioner, feed

C3020

19A170

Y208
Subwoofer



F02047

Pin	Circuit	Circuit function
1	176 (PK/LG)	Subwoofer +
2	179 (OG/RD)	Subwoofer –

C3041a

19A170

A14
Subwoofer amplifier (18C804)



F02251

Pin	Circuit	Circuit function
1	57 (BK)	Ground
2	828 (VT/LB)	Voltage supplied at all times (overload protected)