• BRAKES—FRONT DISC BRAKE PAD AND/OR CALIPER RATTLE OVER BUMPS—REVISED FRONT BRAKE PADS • NOISE—RATTLE FROM FRONT DISC BRAKE PAD AND/OR CALIPER—REVISED FRONT BRAKE PADS	**Article No. 01-4-9**

FORD: 2000-2001 EXCURSION, SUPER DUTY F SERIES

ISSUE

Some vehicles may exhibit a front brake pad or caliper rattle when going over bumps. This may be caused by the brake pads rattling in the calipers.

ACTION

Install new front disc brake pads that have a pressure sensitive adhesive on the outside of both the inboard and outboard pads of the front calipers. Refer to the following Service Procedure for details.

SERVICE PROCEDURE

1. Raise and support the vehicle.
2. Remove the front wheel and tire assemblies.
3. Remove front disc brake caliper pin bolts.
4. Lift the brake caliper from the brake caliper anchor plate.
5. Remove the V-springs.
6. Remove the disc brake pads.

NOTE

DO NOT REUSE THE STAINLESS STEEL SHIM WHEN USING THE RATTLE FIX BRAKE PAD KIT.

7. Remove the plastic liner from both new Pads (1C3Z-2001-BA) exposing the adhesive, and install pads.

NOTE

THE BRAKE PAD WITH THE "EARS" GOES ON THE PISTON SIDE OF THE CALIPER.

8. Install the V-springs into the brake pads.
9. Install the disc brake caliper.
10. Install the disc brake caliper pin bolts. Torque to 56 N•m (42 lb-ft).
11. Install the wheel and tire assemblies. Torque to 200 N•m (148 lb-ft).
12. Lower the vehicle.

NOTE

PUMP THE BRAKE PEDAL SEVERAL TIMES AFTER INSTALLING WHEELS BEFORE MOVING VEHICLE. THIS WILL ALLOW THE BRAKE PADS TO MAKE CONTACT WITH THE ROTOR.

13. Verify front brake pad/caliper rattle is corrected.

PART NUMBER	PART NAME
1C3Z-2001-BA	Disc Brake Pad Kit - Front

OTHER APPLICABLE ARTICLES: NONE
WARRANTY STATUS: INFORMATION ONLY
OASIS CODES: 301000, 306000, 702000, 702100

Copyright © 2001 Ford Motor Company