DRIVEABILITY—BI-FUEL OBD II DIAGNOSTIC MONITOR APPLICATION STRATEGIES—BI-FUEL VEHICLES ONLY	Article No. 01-8-8

FORD: 1998-2000 CONTOUR
1998 F-250 LD
1998-2001 E-250, E-350, F-150
1999-2001 SUPER DUTY F SERIES

ISSUE

This article will provide an overview of Bi-fuel Liquid Propane Gas (LPG) and Compressed Natural Gas (CNG) operating characteristics for Bi-Fuel vehicles and can be used as an aid for diagnosis for the Bi-Fuel vehicles listed.

SERVICE INFORMATION

- US = Upstream
- DS = Downstream
- TP = Throttle Position
- MAF = Mass Air Flow

ACTION

Refer to the following OBD II enabled/disabled chart for Bi-Fuel system application information.

BI-FUEL OBD II ENABLED/DISABLED APPLICATION CHART

OBD II Diagnostic Monitor	Base Gasoline Vehicle	Bi-Fuel Vehicle On Gasoline	Bi-Fuel Vehicle On Alt. Fuel
Misfire Monitor	Enabled	Enabled	Disabled
HEGO Monitor	Enabled	- - -	Disabled
Lack of Switching (US & DS)	Enabled	Enabled	Disabled
Amplitude Response Test (US)	Enabled	Enabled (relaxed criteria)*	Disabled
Heater Current Monitor (US & DS)	Enabled	Enabled	Disabled
Downstream Activity Test	Enabled	Enabled (relaxed criteria)*	Disabled
EGR Monitor	Enabled	Enabled (relaxed criteria)*	Disabled
Fuel System Monitor	Enabled	Enabled (relaxed criteria)*	Disabled
Secondary Air Monitor	Enabled	- - -	Disabled
Evaporative Monitor	Enabled	Enabled	Disabled
Component Monitor	Enabled	Enabled	Partially-Enabled
2-Volt Test (TP/MAF)	Enabled	Enabled	Disabled
Fuel Pump Test	Enabled	Enabled	Disabled
Idle Speed Control Test	Enabled	Enabled	Disabled
Purge Flow Checks	Enabled	Enabled	Disabled
All Others	Enabled	Enabled	Disabled

* Relaxed criteria has been deleted beginning 2001 MY.

OTHER APPLICABLE ARTICLES: NONE
WARRANTY STATUS: INFORMATION ONLY
OASIS CODES: 490000, 690000, 698298

Copyright © 2001 Ford Motor Company