


CAGE ROD LOCKING SCREW
2.0mm [5/64in] HEX
2 PLACES, BOTH SIDES

1/4in-80 LOCKABLE ADJUSTER
REMOVABLE KNOB
2.0mm [5/64in] HEX
3 PLACES
PROVIDES $\pm 5^\circ$ TOTAL ANGULAR
DISPLACEMENT (0.4° PER REVOLUTION)
AND ± 3.0 mm [0.12in] TOTAL TRANSLATION
DISPLACEMENT



CAGE ROD CLEARANCE BORE
4 PLACES

SM1 (1.035-40) SERIES INTERNAL THREAD THRU
ACCEPTS $\varnothing 25.4$ mm [$\varnothing 1.00$ in] OPTICS
(2) SM1RR RETAINING RINGS INCLUDED
2.0mm [0.08in] THICK
 $\varnothing 22.9$ mm [$\varnothing 0.90$ in] CLEAR APERTURE

M4x0.7 MOUNTING HOLE
3 PLACES

ADJUSTER PRE-LOAD SCREW
0.035in HEX
6 PLACES

4.8mm
[0.19in]

29.2mm
[1.15in]

14.2mm
[0.56in]

29.2mm
[1.15in]

30.0mm
[1.18in]

14.2mm
[0.56in]

30.0mm
[1.18in]

9.5mm
[0.38in]

38.2mm
[1.50in]

58.4mm
[2.30in]

9.5mm
[0.38in]

METRIC ID MARK

28.6mm
[1.13in]

11.4mm
[0.45in]

$\varnothing 14.7$ mm
[$\varnothing 0.58$ in]

58.4mm
[2.30in]

11.6mm
[0.46in]

ADJUSTER LOCKING SCREW
2.0mm [5/64in] HEX
3 PLACES

4.8mm
[0.19in]

