Learning conditional language in continuous image space

Imagized Language Model Project

Abstract

Written language includes forms outside standard character encodings. We investigate continuous interfaces that read and emit glyph images, with generated pixels supplying subsequent history. Externally pretrained foundations provide inherited language knowledge; tokenizers, lexical heads and font rendering are absent from the deployed answer path. A compact experiment freezes a 1.409B contextual body and fits image interfaces on 13,785 complete Chinese book and question–answer sequences, covering 2.576 million target glyph positions. Two 8,172-update fits use 3.930 and 4.889 GiB peak allocated GPU memory, yet score zero complete exact QA answers out of 32 at all five checkpoints. A wider writer removes a measured velocity-rank restriction without solving language. Frozen diagnostics expose conditional-writing failure before generated feedback and a separate reader-alignment restriction. On the same question cohort, an earlier actor retaining 7.522B visual and contextual parameters gives two exact answers. Proportional input raises this to six with unchanged weights, but loses the one fully correct pair and an earlier readable answer. External native decoding gives ten exact proportional answers from matched first states. All 32 first target forms have training coverage, and supplied-image reconstruction is pixel-exact for 31, without establishing correct conditional writing. Cold replays verify independent pixel-feedback execution for fixed cases. These controls distinguish inherited answer access, physical support and language generation. Usable open-ended writing, historical-form transfer and a matched-quality efficiency advantage remain unresolved.

Written language is encountered as marks on paper, screens and historical surfaces. Its visual form carries information about script, handwriting and material history. Modern character encodings provide a powerful interface to many such marks, but a finite inventory cannot express every damaged, transitional or unencoded form. An image-based language model could retain that evidence throughout reading and generation, with transcription offered as an optional output view.

Pixel-based language modelling already has substantial precedents. PIXAR demonstrates autoregressive language generation in pixel space and identifies the difficulty of generating readable text[1]. Continuous autoregression can use a diffusion loss in place of vector quantization[2], while Diffusion Forcing models continuous sequences under independently chosen noise levels[3]. These results motivate a visual language interface, but do not establish that a small glyph generator acquires linguistic knowledge or that image input automatically reduces training cost. Exact pixel factorization also has established precedents in PixelRNN and conditional PixelCNN[6,7]. Masked autoregressive networks provide normalized probabilities without a character dictionary[8]. Multilingual generation from pixels has also been studied[9].

Recent continuous multimodal flow models share a generative objective across embeddings

while retaining token-derived language encoders and text decoders[15]. OCG reports rendered-question and answer-image reasoning with teacher assistance on the restricted CLEVR task[16]. We focus on independent image-only inference and controlled tests linking conditional scores to autonomous writing.

We investigate the conditional generation problem directly. The model receives raster history, predicts a distribution of future writing, emits pixels and rereads those pixels. Chinese provides a demanding initial case: stroke configurations must remain coherent while context selects among many similar written forms. The present study uses one canonical font to isolate this coupling before introducing handwriting or historical scripts.

The experiments progress from initial raster readers and denoisers to inherited contextual bodies with separately learned glyph interfaces. The earlier architectures provide controls. Restricted short-answer experiments evaluate the complete-glyph loop shown in Fig. S37; a separate compact experiment then fits complete book and question–answer sequences and measures all five saved checkpoints. A controlled wider writer and frozen-weight interventions then test the sources of failure. A matched earlier-actor control and full-prompt presentation comparison subsequently test retained image-answer transfer on the same question cohort. Matched native decoding and a first-writing audit then distinguish retained answer access from physical form support. Their partial gains and lost question pair remain distinct from new language learning. The contributions are the explicit emitted-pixel interface, controlled language tests, reproducible single-GPU execution and measured writer/reader restrictions. None establishes a generally usable visual language model or a from-scratch language learner.

Results

An initial continuous visual interface preserves the written signal

In the initial control, each observed cell is a 32×32 ink image. An orthonormal transform maps its signed pixels into a 1,024-dimensional continuous field. The transform is invertible and contains no learned character dictionary. An ordered sequence of these fields enters a causal transformer. The deployed model receives no Unicode values, OCR transcripts, character IDs or vocabulary logits (Fig. 1). Host-side rendering uses encoded source text during data preparation. This distinction matters: the current benchmark studies learning from rendered Chinese, rather than discovering a script from raw archaeological photographs.

Ordered image history contains next-writing information

The strongest established reader result uses 2,048 deterministic development windows and an evaluator-only bank of 1,024 canonical glyph images. Full-history next-image top-1 is 19.97%, above the image unigram at 1.42%, the symbolic bigram at 12.26% and the prefix-shuffled condition at 18.36%. The ordered history improves target log probability by 0.174 nat over the shuffled control. This result supports bounded conditional prediction from image sequences.

These figures measure selection among completed images. The evaluator bank does not enter the model and cannot act as a deployed writer. Thresholding the predicted continuous field




Fig. 1 | Initial visual language interface and its conditional generation test. a, Rendered or native writing supplies ordered image cells to a causal visual reader. Text rendering is an optional host interface. **b**, A conditional denoiser uses the frozen reader state and a noisy four-cell strip to predict diffusion velocity. Future cells exchange information through convolutions and pooled-cell attention. **c**, Sampling starts from noise, emits four visible cells and appends their pixels to the next context. Optional transcription follows generation and is absent from the model. The schematic shows the initial denoising control. Its generated content remains incorrect; the later complete-glyph runtime is shown in Fig. S37.

can mix strokes from several plausible futures. For squared-error prediction, the population optimum is $f^*(H) = \mathbb{E}[X \mid H]$. A conditional mean need not be a valid glyph when several futures are possible. Sharp copying, target ranking and sampled language generation therefore require separate measurements.

A glyph prior does not automatically bind to language

To separate visual synthesis from contextual prediction, we train an unconditional glyph prior and a noisy visual compatibility critic while freezing the causal reader. The combined runtime contains 23.27 million parameters. The critic scores an arbitrary noisy image against the visible history. In the ideal density-ratio limit,

$$\nabla_x \log p_t(x \mid H) = \nabla_x \log p_t(x) + \nabla_x \log \frac{p_t(x \mid H)}{p_t(x)}. \tag{1}$$

The construction is related to classifier-guided diffusion[4].

On 512 development windows, the clean critic reaches 21.875% top-1, versus 20.898% with

shuffled history. Its first guided sample reaches zero target identities in 256 cases. Selecting the highest clean critic score among four samples reaches 1/256, with the same result after shuffling history. The generated glyph-like marks are diverse and nonblank, yet fail conditional identity (Fig. 2).

This experiment identifies a reader–writer gap without proving a unique cause. At the terminal corruption level, target signal power is 2.43×10^{-7}, and an exact conditional guidance term should vanish. That limit also occurs in successful conditional diffusion. It cannot alone explain the failure. Insufficient conditional-score accuracy, off-manifold gradients, limited prior quality and finite sampling remain compatible explanations. We consequently test a directly conditional writer rather than interpret clean-image ranking as evidence of a generative solution.

Direct conditional block generation tests the missing coupling

The new writer models a joint four-cell future conditioned on 60 visible cells. It reuses the 16.28M-parameter reader and fine-tunes a 5.90M-parameter strip denoiser. A projected reader state modulates each residual scale, and a four-cell attention layer exchanges future information at the bottleneck. There is no separate guidance critic or candidate selector.

For signed clean writing x_0, noise ε and cumulative signal $\bar{\alpha}_t$, the training target is velocity:

$$x_t = \sqrt{\bar{\alpha}_t} x_0 + \sqrt{1 - \bar{\alpha}_t}\,\varepsilon, \tag{2}$$

$$v^* = \sqrt{\bar{\alpha}_t}\,\varepsilon - \sqrt{1 - \bar{\alpha}_t} x_0. \tag{3}$$

The clean estimate is $\hat{x}_0 = \sqrt{\bar{\alpha}_t} x_t - \sqrt{1 - \bar{\alpha}_t}\,\hat{v}$. Training alternates independently stratified future noise levels with synchronous levels that cover the sampling distribution. Fixed visual-field and foreground losses retain the writing signal. Intermediate target-field alignment follows the motivation of representation alignment[5], using a fixed raster transform rather than a semantic teacher.

The run completes all 8,000 updates in 361.6 s, using 0.543 GiB peak allocated CUDA memory. Evaluation uses one primary sample from 256 prefixes under paired initial noise. Ordered first-position identity is 1.17%, compared with 1.17% after shuffling and 0.00% with a zero condition. Across all four future cells, identity is 0.586%, with an ordered-minus-shuffled difference of 0.098 percentage points and a record-bootstrap 95% interval of [0.000, 0.307]. Pixel F1 is 0.320. The registered complete-mechanism decision is `reject`. The raw image panel shows the first fixed examples without reranking or selection (Fig. 2).

A post-result motor diagnostic supplies the intended first-cell image to the same trained writer on 64 fixed prefixes. Exact plan and image-field supply raise pixel F1 from 0.378 to 0.459 and target identity from 1/64 to 5/64. The fixed inverse transform reproduces the supplied raster with F1 1.0. Because this test supplies the answer, it provides no autonomous-language evidence. It shows that the current learned writer still loses substantial shape information even with an exact visual condition.

Exact raster likelihood preserves copying but not conditional language

The diffusion writer's supplied-image failure motivates a distribution that retains the exact inverse visual field as aligned pixel logits. For binary image X, ordered history H and row-major pixel index p, we define

$$p_\theta(X \mid H) = \prod_{p=1}^{1024} \mathrm{Bern}[X_p; \sigma(6A_p + \delta_\theta(H, X_{<p}))]\,. \tag{4}$$

Here A is the inverse predicted field, scaled to signed pixels and clipped to $[-2,2]$. A causal row transformer and within-row MADE supply the residual. The density contains 2,434,592 learned parameters, combined with the frozen reader for 18,711,841 runtime parameters. This is a conditional raw-pixel factorization[6–8], not a new language vocabulary.

With a supplied binary image, A_p is exactly ± 1. A zero-initialized residual therefore copies its greedy mode exactly before training. This is an architectural property, not acquired linguistic knowledge. Pure image NLL training retains that property: greedy copying is exact for all 256 development targets, stochastic-copy F1 is 0.99949, and a deranged supplied image reduces F1 to 0.358 (Fig. 3). These exercises supply the answer and cannot qualify autonomous generation.

On 512 natural targets, ordered NLL is 15.219 nats per image (0.02144 bits per pixel), versus 15.254 with earlier history shuffled. The paired advantage is 0.0355 nat, with source-record bootstrap 95% interval [-0.1014, 0.1693]. This interval includes zero. An independent-pixel distribution using the same predicted plan has NLL 846.09 nats. That comparison supports learned dependencies within the image; it does not isolate learned linguistic dependencies between images.

Autonomous sampling recovers 4/256 nearest target identities, versus 3/256 after shuffling, with pixel F1 0.350. The paired identity advantage is 0.391 percentage points, with interval [0, 1.210]. Greedy generation reaches 14/256 exact images but only 0.215 F1 and 0.330 target-relative ink, consistent with frequent sparse forms in the visible gallery. Four-step feedback identity is 4.297% ordered and 3.125% shuffled; this small secondary difference does not reverse the failed primary language tests. The registered decision is `reject`.

Joint learning improves the conditional image distribution

A matched experiment tests whether the same raster law benefits from learning its reader under image NLL. Both arms start from the exact-density EMA and receive identical new training draws. One continues to freeze the reader; the other differentiates likelihood through its hidden state and predicted field. Reader dropout remains disabled in both, so gradient flow is the controlled change. The unused contrastive temperature stays fixed.

After 8,000 updates per arm, joint target NLL is 7.026 versus 7.579 for the frozen control. The paired gain is 0.553 nat, with interval [0.450, 0.665]. Joint ordered history improves NLL over earlier-shuffled history by 0.185 nat, with interval [0.128, 0.244]. The frozen continuation also gains an earlier-history effect (0.119 nat, interval [0.052, 0.186]); extra training alone therefore explains part of the progress. The matched comparison isolates the additional likelihood benefit

of updating the reader.

Joint first-sample identity is 9/256, versus 6/256 for the matched control and 8/256 after shuffling. The joint-minus-control identity difference is 1.172 percentage points, with interval [-0.397, 2.893]. Both arms retain exact greedy copying of all 256 supplied images. Joint sampling has F1 0.362 and isolated-ink fraction 0.00744. The joint arm passes six of eight gates, but fails sampled quality and ordered-generation criteria; its decision remains `reject` (Supplementary Note 13 and Fig. S2). This is evidence of improved conditional learning, not a qualified language generator.

Raw-pixel search improves choice but exposes repetitive rollouts

Known-form validity and target correctness separate two remaining problems. A post-result audit of the original saved images finds exact known-form membership in 43.750% of joint first samples, versus 33.594% for matched frozen training. The paired gain is 10.156 percentage points [4.219, 16.240]. Joint greedy images reach 98.438% known-form membership, but only 7.422% exact target match (Supplementary Note 14). Clear writing alone is insufficient.

We next search the same normalized pixel law with eight partial-raster beams, without a glyph inventory or weight change. On 2,048 new deterministic development windows, ordered exact next-image match is 11.621%, versus 8.252% for original pixel greediness and 9.863% after earlier-history shuffling. The beam-minus-greedy gain is 3.369 points [2.351, 4.412]; the earlier-history gain is 1.758 points [0.966, 2.552]. Every primary beam output matches a known canonical raster after generation.

Eight-step feedback on 128 prefixes reaches 6.641% exact target images, versus 4.883% greedy, but adjacent repeated images rise to 25.446%. The actual target rate is 0.112%. Thus the registered decoder decision is `reject_decoder`: five of six gates pass, but repetitive rollout fails (Supplementary Note 15 and Fig. S4). This outcome is compatible with known limits of probability-maximizing language decoding [10]. No repetition filter or output replacement is applied.

Natural questions expose the gap between selection and complete answers

To test use of language beyond continuation, we add a copy distribution over images in the current prompt, following the established pointer–generator idea [11]. Repeated identical images contribute summed attention mass. A learned gate combines copying with the exact raster law, and a separate stop hazard controls answer length. Only observed pixels and causal states enter this 19.01M-parameter model. No reference answer, symbolic identity or persistent writing inventory enters generation.

Training uses 3,211 natural Chinese questions with full paragraphs from CMRC 2018 [12]; article overlap is removed across training and development. Both copy and no-copy arms make 4,000 updates from the same V55 weights, retaining natural continuation and motor exercises. On 256 fixed development questions, the copy arm gives 10 exact stopped answers (3.906%), versus one (0.391%) with question pixels blanked and zero for the no-copy control. Raster F1 is 15.718%, 5.553% and 6.582%, respectively (Fig. 4). The paired question-dependent F1 gain is 10.165

points [7.043, 13.371].

Complete reading remains inaccurate. Only one of 393 question pairs sharing a paragraph has both answers correct. Output reaches the 17-cell safety cap in 22.656% of primary cases. All 2,677 emitted primary cells use the copy branch; the free writer is retained but not exercised in these answers. All 256 supplied motor images remain exact. Four of seven gates pass, failing answer accuracy, F1 and paired-question correctness; the decision is `reject_reading_model`. A post-result image-only diagnostic finds a correct first glyph in 43 cases, but only 10 become correct complete answers. Fourteen outputs contain a complete reference prefix followed by extra output. Both evidence selection and answer structure need improvement (Supplementary Note 16).

Image-block answers improve structure but retain selection errors

We next normalize a joint start–end law over contiguous observed image blocks of one to sixteen cells. Equal image sequences share probability mass, and the selected end position terminates the answer. Training marginalizes all matching source locations using target images alone. This 19.60M-parameter model retains the free raster writer and natural/motor exercises.

After 4,000 additional updates from the V57 copy checkpoint, exact answers reach 25/256 (9.766%), versus 3/256 with question pixels blanked and 21/256 for matched additional glyph-answer training (Fig. 5). Block F1 is 27.033%, versus 9.169% blanked and 22.140% for the matched control. The block-minus-control F1 gain is 4.893 points [0.469, 9.047], but the exact-answer difference is unresolved: 1.563 [-1.509, 4.652]. Extra training explains much of the improvement over V57; it cannot all be attributed to the block law.

Both answers are correct in only 4/393 paragraph pairs. Six of seven registered gates pass; paired-question correctness fails. Motor copying remains exact on 256/256 images. The block arm trains in 211.0 s at 0.967 GiB peak allocated memory on the same GPU, excluding previous training. Native prompt-PNG replay through the inference-only export exactly reproduces output pixels and boundary events. The result establishes limited extractive reading, not useful general free writing (Supplementary Note 17).

Frozen pretraining is not sufficient under a shifted visual interface

A separately registered probe compares frozen V58 and released MIXAR-477M[9] features using identical fresh 789,520-parameter block readouts. Both see the same prompt images, pair-aligned states, fixed continuous projections and fine image features. The student readout reaches 24/256 exact answers and 25.340% F1; MIXAR reaches 6/256 and 11.588%. Its F1 difference is -13.752 points [-18.247, -9.094]. No MIXAR pair has both answers correct, versus 12/393 student pairs. The frozen-foundation probe is rejected. This comparison includes different prior task training and a font/layout shift from MIXAR's native renderer; it does not disprove the released model's language competence. External pretraining is not local single-GPU work (Supplementary Note 18 and Fig. S5).

Moving the question before the passage is insufficient

For a causal reader, placing the question first allows each later passage state to depend on it. A registered input-order comparison starts both arms from identical V58 weights and retains the same images, parameters and 4,000-update budget. Question-first reading yields 21/256 exact answers and 23.765% F1, versus 27/256 and 26.908% for continued context-first training. The F1 difference is -3.143 points $[-6.544, 0.446]$, unresolved. Both questions are correct in 5/393 versus 16/393 paragraph pairs. Four of eight intervention gates pass, and the change is rejected. Motor copying remains exact in both arms. This result limits a simple ordering explanation of the selection failure; it does not establish that question-conditioned source representations are ineffective in general (Supplementary Note 19 and Fig. S6).

Native free writing fits pixels but fails reading

We next adapt every parameter of the released MIXAR-477M native pixel-language model[9], rather than selecting source-image spans. The actor receives prompt images and predicts unrestricted binary image blocks, with no output glyph inventory, OCR or external inference call. All 477,145,984 parameters receive answer-image likelihood gradients. The 1,000-update run takes 1,501.1 s on one RTX 4090 D at 9.912 GiB peak allocated memory, excluding loading and final serialization. External foundation pretraining is attributed separately.

Held-out answer-pixel NLL improves from 0.6842 to 0.1548 nats, yet generated answers remain inaccurate (Fig. 6). Exact answers are 0/256 and both-correct paragraph pairs 0/393. Exact-raster F1 is 0.149%, while aligned foreground F1 is 12.264%. Question blanking reduces foreground F1 to 8.473%, but the strict-raster F1 difference does not resolve zero. Five of ten registered gates pass, all concerning implementation, resources or termination rather than the required answer quality. The decision remains `reject_native_free_reading`.

Native PNG inference reproduces answer tensors, PNG bytes and stopping events from a self-contained learned bundle in a fresh offline process with empty model/code caches. This establishes an independent runtime, without certifying its language. The Noto CJK cell renderer differs from the released model's native font interface. A blinded answer-only OCR diagnostic is poorly calibrated even on reference images, recognizing only 40/256 exactly; it cannot replace a semantic evaluation (Supplementary Note 20).

Correlated pixels improve fit without establishing answers

We next replace the single product-Bernoulli head with eight conditional experts, each defined over a complete 32×64 bitmap. A shared latent expert permits pixel covariance without a character inventory. Both arms fully adapt the same native foundation for 1,000 updates on identical sampled examples; the eight-head actor has 490.00M parameters versus 477.15M for the single-head control. The comparison matches training budget, not capacity.

Held-out answer-pixel NLL is 0.1248 versus 0.1542 nats for eight and one experts, respectively (Fig. 7). Strict-raster F1 increases from 0.234% to 0.815%, a 0.580-point difference [0.089, 1.094]. Foreground F1 increases from 12.205% to 15.827%. Nevertheless, both arms produce zero exact

answers among 256 questions and zero both-correct pairs among 393 shared-paragraph pairs. The eight-head normal-minus-blank raster gain is only 0.295 points [−0.006, 0.623], leaving question dependence unresolved. Foreground F1 also has no resolved question-dependent gain. The registered density-intervention gate and both bounded reading gates fail.

Training takes 1,887.5 and 1,972.8 s, with 9.904 and 10.174 GiB peak allocated memory for one and eight experts. Both independent bundles reproduce native PNG tensors, image bytes and decoder events offline. The eight-head gate entropy averages 1.812 nats, with five experts selected across the primary continuations, including termination. These usage diagnostics describe the mixture; they do not demonstrate semantic specialization (Supplementary Note 21).

Direct assignment changes reference scores but weakens free writing

To test conditional binding, we continue the eight-expert generator from one shared learned checkpoint. Two questions about a paragraph provide distinct accepted answer images. Both matched 489,998,208-parameter actors score all four correct and swapped question–answer streams. The control uses positive image likelihood alone; the aligned arm adds a smooth penalty on the assignment margin. Both consume identical pair draws for 2,000 updates. The extra loss cancels additive question-only and answer-only offsets, but this property does not guarantee useful conditional generation.

The aligned actor reaches 2.417% strict-raster F1 versus 3.229% for control (Fig. 8). The difference is −0.812 percentage points, article-bootstrap 95% interval [−1.504, −0.202]. Exact answers are one and two of 256 respectively; both-correct pairs remain zero of 393 for both. Normal-minus-blank-question raster gains resolve positively in each arm: 1.677 points [0.492, 3.033] for aligned and 1.765 [0.504, 3.251] for control. Thus both use question pixels, while neither meets the absolute reading requirements. The assignment intervention and both reading gates fail.

When accepted answer images are supplied, control chooses the correct pair assignment in 324/393 cases and aligned in 330/393. These descriptive scores cannot establish a statistically resolved improvement, and supplied answers are unavailable to autonomous writing. All-development pixel NLL is 0.113901 for control and 0.114186 for aligned. Training takes 7,355.2 and 6,737.3 s, with 10.301 GiB peak allocated memory in both. Complete sample journals match; standalone offline tensors, PNG bytes and stopping events replay exactly (Supplementary Note 22). Timing variation in one sequential run does not establish comparative efficiency.

Separate output coordinates preserve forms

To isolate a writing failure from conditional language selection, we cross the inherited reader features and a lossless pixel control with flow and direct image reconstruction. All four writers receive the same 64 training blocks, initial weights and 2,000-update exposure. Direct reconstruction recovers 63/64 blocks exactly from inherited features and 64/64 from pixels; neither flow arm recovers an exact block (Fig. 9a,c). This fitting experiment identifies a failure of the tested flow route, but supplies the answer image and cannot demonstrate language.

A broader direct writer then samples 160,000 blocks from a 12,976-example Chinese/English pool, consuming 12,972 distinct examples. After 10,000 updates, the fixed 128-case reconstruction audit reaches 56.563% foreground F1 versus 18.520% with shuffled conditions, with three exact blocks. The conditioning gain passes its original requirement, but fidelity misses 90%. The run uses a fitting-stage warm start and is not a matched broad-corpus comparison with the earlier flow writer. Raw outputs and failed criteria are retained.

A separate continuous writing codec removes the requirement to invert the semantic reader. With its original frozen weights and no additional learning, two 768-dimensional image codes reconstruct the same 128 development blocks at 99.998% F1 and 126 exact blocks, versus 21.413% F1 and zero exact blocks with shuffled codes (Fig. 9b,d). The encoder receives target images; the decoder receives only continuous coordinates. Thus the result qualifies supplied-code fidelity, not prediction of an unknown answer.

The complete successor retains all 27 visual and 36 contextual layers while predicting this separate writing space. It has 7,539,239,282 total parameters and 9,351,937 trainable parameters, with 16.953 GiB peak allocated memory. All 24 actual execution checks pass, including early/late adapter gradients, future-image isolation and exact optimizer/RNG replay. Its two-update output remains fragmented. These preflight measurements establish execution, separately from the subsequent instruction-learning test (Supplementary Notes 24–26).

Conditional prediction remains inaccurate

The complete actor then finishes its registered 10,000-update instruction stage on all 12,976 admitted Chinese/English training examples. Fresh corpus permutations yield 20,000 recorded draws, including every admitted example once in the first epoch. The final adaptation and production checkpoint agree exactly; all recorded draws match the seeded order. This adapts 9,351,937 parameters within the inherited 7.539B-parameter actor, using 16.965 GiB peak allocated memory on one RTX 4090 D. External foundation and codec training remain part of its provenance (Supplementary Note 27).

The final actor generates answers to 128 Chinese questions from 64 shared-passage pairs and 64 English instructions, each with a fixed blank control. All 384 raw streams and input layouts are independently verified. Chinese foreground F1 is 32.671%, versus 19.508% with question pixels blanked (Fig. 10a). The paired difference is 13.163 percentage points, with 95% article-bootstrap interval [10.933, 15.730]. Nevertheless, no Chinese answer is exact and no pair has both answers correct. All 128 normal Chinese outputs stop through the learned decision. The three absolute answer-quality gates fail while question dependence and stopping pass (Fig. 10b,c). English recorded-reference agreement is also poor, at 9.763% F1 and zero exact matches; that metric does not credit every alternative valid answer.

A fixed 32-case diagnostic then separates supplied-code reconstruction, prediction with exact reference history, and autonomous writing. Each split/source group contains eight examples. Supplied-code F1 is 99.947–100%, but prediction with supplied history and answer length reaches only 21.805–35.554%, including training examples. No first predicted block is exact

(Supplementary Note 28 and Supplementary Fig. S9). The initial pixels and stop probabilities agree between paths starting from the same prompt. The failure therefore precedes generated-history drift. This assisted diagnostic does not identify a unique learning repair or qualify language; the original autonomous decision remains rejection.

Numeric controls retain bounded visual reading

We test the original imported body through numeric chat/task vectors with its vocabulary absent. A separate helper temporarily applies the source text projection. Among eight Chinese development questions, native-budget images give four exact answers versus zero with questions erased; original-scale images give one, and matched text gives three. All 742 retained helper decisions replay as exact argmax choices (Supplementary Note 29 and Fig. S10). This reused sample supports bounded reading, without qualifying image writing or isolating the scale effect.

The successor conditions a 38.652M-parameter causal writer on frozen prompt-only visual states. A joint flow predicts two-tile codes; the codec emits pixels, which are re-encoded for history. Real-example future-target exclusion, bit-exact optimizer/RNG resume and physical feedback checks pass. Full-corpus training completes 40,000 updates and 640,000 draws over 12,976 examples. The autonomous audit gives zero exact Chinese answers out of 128 and 29.386% foreground F1, versus 21.873% with questions erased. Four of six Chinese requirements fail (Supplementary Note 30 and Fig. S11).

A post-hoc diagnosis identifies an obstruction in the velocity head: its final affine span has rank 769 in 1,536 writing coordinates. In real arithmetic the remaining 767 components of initial noise are invariant before normalization. Actual-weight CPU trajectories support this prediction. A full-dimensional velocity control improves fidelity but fails its worst-image requirement on fresh noise. Predicting clean writing codes instead, with an FP32 final projection and analytic noise contraction, reproduces one learned Chinese image exactly on all 256 fresh draws (Supplementary Note 31). Clean-data prediction follows prior denoising work[20]; the known-image control establishes neither reading nor conditional language competence. The complete clean writer subsequently fits 32 seen training questions: 29 original answer images are exact, versus 31 frozen-codec reference images, with 99.997% original-image F1. This is a paired learning-capacity control, not unseen-question generalization (Supplementary Note 32).

Full-corpus clean writing still fails

A fresh 64.520M-parameter clean writer trains on all 12,976 examples for 40,000 updates, completing 49 corpus passes. Its autonomous audit produces 2/128 exact Chinese answer images and 37.631% foreground F1, versus 23.609% with question ink erased. Both questions are exact in 0/64 passage pairs; three original requirements fail. The question effect is resolved at 14.023 F1 points [10.861, 17.487], and all normal Chinese answers stop by their learned rule. Dependence on question pixels does not establish correct answers. A separate 12-request Chinese/English/numeric copy probe also gives no exact outputs (Supplementary Note 33).

The full writer fails even on the earlier 32 training questions: free generation reaches 45.771%

F1 with no exact answer. Correct prior image codes and supplied answer length raise F1 to 58.045%, still with no exact stream. Supplied-code rendering reaches 99.9953% F1. Thus error is already present under correct histories. The clean predictor also slightly corrupts constructed near-clean target codes. This identifies an additional writing defect, without showing that it causes the much larger free-answer failure. The earlier small fit received 2,000 passes over its selected examples; neither that memorization result nor theoretical time-coverage calculations demonstrate a useful general language model.

A matched head-only refinement broadens denoising-time supervision while holding the causal body fixed. It improves assisted near-clean block F1 from 99.0658% to 99.8602%, but free-stream F1 falls from 48.726% to 45.028%. Both arms remain at 0/32 exact training answers. This intervention fails all four prespecified repair criteria (Supplementary Note 34); better near-clean reconstruction is insufficient for prompt-conditioned generation.

An offline source-decoder diagnostic recovers 8/12 exact copy answers and 19/32 exact training answers from the same physical prompt images, compared with zero exact image outputs in both groups (Supplementary Note 35 and Fig. S12). All 44 normal prefill memories match the original 52-state BF16 suffixes exactly. The first source projection matches the correct answer prefix on 22/32 training questions, excluding the paired answer in each case. Thus some answer information is available before the new writer. Later source decoding uses the full layerwise visual/context KV history, which the image writer does not receive. These measurements motivate examining the compact-memory and conditional-readout boundary; they do not demonstrate sufficiency of the compact state or a usable image-language model.

A key-visibility intervention now tests that boundary directly. After identical prefill, permitting attention only to the final 52 task positions reduces exact source-helper copy answers from 8/12 to 0/12 and training answers from 19/32 to 2/32 (Supplementary Note 36 and Fig. S13). Original cache positions, rotary coordinates and first decisions are preserved. This rejects the tested frozen suffix interface without proving a lower bound on learned compression. The next continuous image actor retains all 36 native layers and full prompt KV. Initial forward, gradient, causal-mask and emitted-image feedback checks use 16.638 GiB on one GPU, with zero optimization updates. Its first writing block still depends on the initial reader state alone. The complete trained actor has 7.583B parameters including externally pretrained weights; 46.900M image interface parameters are trainable.

Subsequent training completes 40,000 updates over all 3,193 Chinese examples, using 18.298 GiB peak allocated memory, but gives 0/128 exact development images, 36.504% foreground F1 and 0/64 both-correct pairs (Supplementary Note 37 and Fig. S14). Erasing the question reduces F1 to 25.404%; the paired gain is 11.101 percentage points, with a 95% article-bootstrap interval of [8.578, 14.018]. All streams stop, but stopping and input sensitivity do not establish accurate answers. On the same 32 training questions, free generation gives 46.235% F1 and correct-history prediction gives 50.241%, with no exact images in either path. Supplied-code decoding gives 99.9953% F1 and 28/32 exact images. Thus conditional prediction

remains inaccurate under correct history; generated-history errors cannot be the sole explanation. These physical-image scores are not a separate measurement of semantic accuracy.

A matched readout repair adds an initial continuous query and trains rank-8 suffix adapters while retaining the full prompt cache. After 2,000 updates per arm on those same 32 training questions, free F1 is 71.177% for continued control and 72.748% for adaptation; neither produces an exact complete image (Supplementary Note 38 and Fig. S15). Correct preceding history gives 77.372% and 79.629%, again with no exact images. Supplied-code fidelity is unchanged at 99.9953%. The adapted model fails three of four declared training-fit criteria. The small increase in image agreement does not resolve conditional writing or qualify general language capability.

Decoder-sensitive reweighting also fails (Supplementary Note 39 and Fig. S16). From identical adapted weights, 2,000 matched updates lower autonomous F1 from 85.984% to 70.009%, with 0/32 exact in both arms. Correct-history F1 is 92.430/75.116%; supplied codes give 99.9953%. All four repair criteria fail; scaling is rejected.

A separate native image-generator adaptation learns partial copying (Supplementary Note 40 and Fig. S17). Two fresh rank-16 adapters train on the same 32 Chinese/English copies for 512 updates. Removing exactly white bottom padding preserves every source pixel but changes frozen-VAE features. Training invocation time falls from 795.624 to 287.182 s, with peaks of 9.501 and 8.437 GiB. On the matched eight-case screen, OCR exact match changes from 2/8 to 3/8. Complete strip observation yields 6/32 training and 10/32 validation strings, against clean-reference OCR scores of 27/32 and 28/32. Raw omissions, repetitions and unwanted marks independently reject the 30/32 reliability requirement. All 64 outputs are retained; eight are original observations and 56 are additional calls. This model has 3.900B deployed transformer parameters plus an 84.046M VAE, with 24.359M trained adapter parameters. No natural QA is optimized in these copying runs. Faster copying execution therefore does not establish language understanding or efficiency at useful language quality.

Frozen recognition supervision also fails reliable copying: a matched 512-update treatment gives 6/32 seen and 9/32 held-out OCR-exact strings (Supplementary Note 47 and Fig. S24). A subsequent 32-update continuation supervises actual final images generated from independent noise, combining reader CE with balanced pixel error and differentiating through all 50 native steps[24]. Seen copying rises from 6/32 to 15/32 and held-out copying from 9/32 to 13/32, meeting an exploratory progress rule but failing the 30/32 writing floor (Note 48 and Fig. S25). Training takes 1,135.452 s at 12.057 GiB peak allocation. At initial assessment, the continuation lacks an additional-training control and changes input-encoding precision as well as the loss; the later comparison below holds precision common. Raw omissions and repetitions remain. It establishes neither semantic answering nor a quality-matched efficiency advantage.

The subsequent old-objective continuation gives 5/32 seen and 10/32 held-out OCR-exact copies on matched example draws; both it and the final-image pilot retain only 3/16 held-out Chinese copies (Note 49 and Fig. S26). This retrospective comparison differs in objective and compute. Continuing the pilot for 128 balanced updates, four per training input, raises held-out copying

to 17/32, including 4/16 Chinese, but reduces seen copying to 13/32. The prospective Chinese and seen-retention conditions fail; only English retention passes. Training takes 4,500.117 s at 12.032 GiB. Omissions, repeated characters and copied instructions still reject reliable writing, and semantic QA remains untested. This result does not support further unchanged copying-budget scale-up.

A matched physical-loss replacement then increases held-out OCR-exact copying from 16/32 in control to 19/32, including 4/16 to 6/16 Chinese; seen copying is 16/32 versus 18/32 (Note 50 and Fig. S27). Both arms use identical starting weights, optimizer states, inputs and noise over 32 updates. The prospective exploratory rule passes, but raw omissions, repetitions and copied instructions still reject reliable writing. No semantic QA is optimized in these arms. A separate full-page preflight fits two real discarded updates at 12.203 GiB; four native source reconstructions retain 97.834–98.180% foreground F1, while the fixed earlier checkpoint answers none of four normal questions correctly (Note 51 and Fig. S28). Physical representation and actual gradients have not established language learning.

A native unified backbone provides a separate visual-access diagnostic (Show-o2[21]; Supplementary Note 41 and Fig. S18). Its frozen source gives no exact answers on twelve image prompts, while the same body recovers all eight requested copy contents from their original text. Gated visual-only adaptation then trains 8.490M parameters for 4,096 updates on 128 copies and 256 natural questions. The native language body and Unicode output head stay frozen. Complete held-out text readout gives 27/32 exact stopped copies (11/16 Chinese and 16/16 English), but 0/32 correct natural answers. All 32 question responses collapse to two unrelated years. With matched passage seeds, 15/16 question pairs receive the same answer and erasing the question leaves 29/32 normal outputs unchanged; no pair is both correct. Training takes 2,758.904 s at 6.894 GiB allocated peak on one RTX 4090 D, excluding source pretraining, cache preparation and separate evaluations. The adapted source contains 2.839B parameters plus a 126.893M codec. These are auxiliary text-head measurements, with no trained image-answer result. Improved short-string reading therefore coexists with failed question-dependent answer selection.

The subsequent full-page curriculum and geometry intervention refine this interpretation (Supplementary Note 42 and Fig. S19). Another 2,560 updates raise exact copying to 29/32, but Chinese and English natural QA remain 0/32 at the original geometry. Full transcription improves on four short copying pages and fails on all four complete Chinese QA pages. The source interface had extended the official 432-square reading configuration to 1024-square pages with interpolated spatial positions. Resizing the same whole English pages to 432 recovers 11/32 exact stopped answers from the frozen source, versus 0/32 at 1024, without optimization. Nine of these eleven correct answers disappear when the passage is erased; two remain correct without it. Both learned adapter checkpoints reach only 5/32 at 432. All eighty calls per condition retain the same questions, references, seeds and decoding. The pixel/position change is joint, so the particular geometric mechanism remains unresolved. This recovers inherited source reading capability, while rejecting the existing adaptation as a demonstrated repair. Direct image answers and useful

independent image-language learning remain unachieved.

A subsequent source-preserving visual-state correction improves English QA from 11/32 to 16/32 and English copying from 7/16 to 16/16, but Chinese QA remains 0/32 and copying 0/16 (Supplementary Note 43 and Fig. S20). Four of six reader requirements fail. A separate seen-prompt check corrupts all eight Chinese strings despite previous training exposure. The earlier dense checkpoint retains 13/16 Chinese copies on its original 1024-by-256 strips; adding only white bottom padding reduces copying from 29/32 to 7/32 overall, with every ink pixel and model weight fixed. Tight whole-request cropping also fails. All 480 layout-control calls are retained, including exact replay of the 160 original responses. A separate contextual-attention learner retains 29/32 copies but leaves QA at 0/32 in both languages. A further 128-call feature/context intervention does not restore Chinese copying by shortening the square context alone; strip features in the long context recover 16/16 English but only 2/16 Chinese copies (Note 43). These observations identify geometric brittleness and failed Chinese fit, without isolating a unique internal cause or qualifying image-answer generation.

A separate contextual source-pixel component copies all 32 new Chinese/English strings and fits all 32 tested training questions exactly, but gives only 9/64 exact held-out Chinese answers and 1/32 both-correct paragraph pairs (Supplementary Note 44 and Fig. S21). Question erasure gives 2/64 and passage erasure 0/64. Three of four registered component requirements fail. Four actual native-image calls reproduce its cached descriptors and answer pixels, including the wrong first question. This is learned source-region selection with exact pixel copying, rather than free glyph synthesis. Its 2.378M trained head retains a 7.531B externally pretrained runtime. The clean copying and seen-data fit therefore expose a remaining selection/boundary generalization gap without qualifying a lightweight general image-language model.

A matched continuation uses the same four-pass schedule over 3,193 admitted Chinese QA images and 64 copies, with 3,257 updates per arm. Head-only control gives 23/64 exact unseen answers; additionally adapting 6.193M contextual attention parameters gives 26/64. Both retain 32/32 new copies, but answer both questions correctly in only 3/32 paragraph pairs (Supplementary Note 45 and Fig. S22). Both fail two of four reader floors, and the three-answer gain with no additional complete pairs misses the prospective improvement rule. Independent scoring reconstructs all 512 native outputs, and eight standalone calls replay pixels and events exactly. These checks verify execution and the failed comparison rather than free image-language synthesis. A separate retained-history audit finds only 2/75 intermediate image boundaries with a matching saved text-prefix state (Note 46 and Fig. S23); the distances do not establish an alignment repair.

Full-page answer learning remains unsuccessful

A complete natural-QA adaptation of the image writer fails all six prospective exploratory conditions (Supplementary Note 52 and Fig. S29). Four permutations of 32 training questions give 128 updates. Initial and final models each produce 0/32 source-accepted OCR-exact seen answers, 0/32 held-out answers and 0/16 both-correct held-out passage pairs. Both erased-input controls also give 0/32. Held-out copying falls from 19/32 to 16/32, exceeding the allowed loss of

two exact strings. Training takes 12,782.358 s at 12.204 GiB peak allocation. All 384 original assessment pages are inspected, with malformed writing, extra fragments and omissions retained (Fig. S30). Imperfect reference OCR remains material. These observations reject scaling the unchanged recipe and do not establish an independent language model.

A separate native image-answer flow adaptation completes 1,536 updates on 384 image pairs using 37.381M low-rank adapter parameters within a retained 6.240B-parameter pretrained system (Supplementary Note 53; Fig. S31). The complete matched comparison yields 0/32 source-accepted OCR-exact seen answers, 0/32 held-out answers and 0/16 both-correct held-out passage pairs in both arms. Copying rises from zero to 2/32 seen and 3/32 held-out exact strings. All 384 output pages are authenticated and inspected. Training takes 3.18 h at 15.697 GiB peak allocation, including loading, saving and fixed monitoring. Reference OCR remains imperfect. A small conditional-field signal and failed guidance-one diagnostic do not qualify answer generation; eight saved target-codec reconstructions preserve four seen answers. These results do not establish useful language learning.

Precise image fitting does not establish language generalization

Additional controls separate optimization from useful answering (Supplementary Notes 54–56; Figs. S32 and S33). A 128-update reader-query fit still gives no exact answers on two seen and two excluded questions. Supplying correct text to the native writer yields 1/4 source pages at guidance four, falling to 0/4 when the VAE reference is removed; adapted writing remains 0/4. A separate 3.453M-parameter causal pixel head learns from frozen image-only contextual states. After 1,200 updates, even correct preceding pixels leave Chinese training-piece accuracy at 76.831%. Restoring the same untrained head and extending optimization to 16,000 updates gives 512/512 exact autonomous training first blocks, but 0/128 Chinese and 0/64 English development first blocks. Active head training takes 279.131 s at 0.825 GiB peak allocation, excluding the pretrained reader and cache. Thus precise emission for learned conditions is achievable in this component; conditional generalization and complete language answering remain unresolved. Physical fitting is not a semantic benchmark.

Complete image-answer fitting and failed transfer

The native actor learns complete answer images (Supplementary Note 57; Figs. S34 and S35). Full prompt context conditions a causal pixel density and learned stop; emitted images become history. The externally pretrained 7.544B actor adapts 13.856M parameters on 32 natural Chinese questions from 16 passages. Exact complete training answers increase from 0/32 to 17/32, 29/32 and 32/32 at updates 0, 1,000, 2,000 and 4,000. The registered exact-fit stop triggers at 4,000; fresh-PNG evaluation confirms all 32 answers and all 16 passage pairs. However, reused development gives 0/16 exact Chinese answers and 0/8 English transfer answers, with foreground F1 0.240 and 0.034. Development outputs contain broken glyphs and unrelated training fragments. All outputs stop below the safety cap. Active optimization takes 63.2 min and total execution 81.6 min, at 18.191 GiB peak allocated memory, excluding inherited pretraining. Five cold-loaded

PNG replays preserve complete pixels and stopping exactly. Complete image fitting succeeds; new-prompt answering fails. Changes in initialization, decoder, precision and schedules preclude attributing this gain to the likelihood alone.

The learned writing interface loses usable reading capability

Increasing the cohort from 32 to 512 questions gives 495/512 complete pixel-exact training answers after 16,000 updates, but no exact normal development answers (0/16 Chinese and 0/8 English; Supplementary Note 58, Fig. S36). All 512 training first images are exact; none of the 24 normal development first images matches a reference. The mismatch is therefore already present before feedback from an earlier complete generated image, although within-image autoregression remains a possible contributor.

Scoring fixed owning checkpoints separates an erroneous learned distribution from a decoding-only explanation. Every supplied correct development first image is less likely than the corresponding saved emission. At the final state, the mean best-reference minus emitted-image log probability is -751.24 nat for Chinese and -941.82 nat for English. A maximum-likelihood decoder cannot select any of these supplied references over the existing emission. This does not rule out other correct wordings or fonts. Relative question conditioning nevertheless transfers: 14/16 Chinese reference events favor their owning question and all eight paired assignment contrasts are positive. Relative preference alone does not establish useful output.

The original source reader, using the same normal and question-erased PNGs, reproduces all 32 ILM image-memory fingerprints. A temporary helper-only source text head then gives 12/16 literal normal answers, zero erased answers and 11/16 source-text answers. The two date questions receive the correct years; the learned pixel writer's corresponding forms remain damaged. Some literal mismatches are aliases or longer relevant wording. These are reused development cases without independent semantic grading, and the symbolic helper generates no ILM images. The comparison localizes substantial lost capability to the writing interface without uniquely separating its initial query, conditional density and image-history projection.

We consequently separate glyph formation from language continuation (Fig. S37). A continuous CNN encoder and decoder learn training-only semantic anchors for 4,087 distinct canonical forms. Direct decoding is exact for 4,048 forms (foreground F1 0.999940); actual-image roundtrip is exact for 3,697 (F1 0.999634). The 80.22-second primitive run peaks at 0.728 GiB, excluding the large contextual body and its pretraining. Semantic alignment is weaker than reconstruction, with mean cosine 0.77735 on the first 128 forms. Clear reconstruction neither validates unseen glyphs nor demonstrates language understanding. The proposed continuation loop preserves the native assistant state, predicts one complete glyph and re-encodes its actual pixels. Fitting only its readout/stopping on 508 supported questions yields readable new complete strings corresponding to 288 items and the year 1874 (Supplementary Note 59). Nevertheless, only 1/16 normal Chinese development images is canonical-exact, and eleven cap; the one exact full year string occurs in training. These are partial examples, not a semantic-accuracy estimate.

A frozen intervention replaces passage dates on two templates selected from those outputs

(Fig. S38). Eleven of fourteen prospectively fixed new dates have clear matching output-first transcriptions, two are canonical-exact and all fourteen stop naturally without a target length. Three damaged/wrong digit streams remain failures. Erased-question controls give no correct date. Six clear outputs compose full year strings absent from supported training answers. This supports restricted input-dependent composition through actual image feedback, while broader unseen-answer reliability remains unresolved.

Sharp known-form generation does not recover uncertain glyph identity

Additional controls distinguish a useful motor from correct conditional writing (Supplementary Note 60; Fig. S39). On sixteen normal Chinese initial states, an allowed reference first form is nearest in semantic cosine for nine, but only one first image is pixel-exact. A spectral calculation gives a 0.060109 lower bound on uniform anchor-code MSE for a rank-2048 affine output; distance to the trained output span and bias is 0.305180. These are regression limits, not pixel-error bounds. Synthetic-state readout transfer and an added contrastive loss both fail their physical glyph requirements. Noise-trained decoding and two joint motor flows also fail fixed mixed-code tests. A 3.89M-parameter spatial flow generates the 4,087 known clean-condition forms with mean foreground F1 0.998260, but mixed-condition F1 is 0.810537. None of these rejected motors undergoes autonomous language assessment. Confident known-form generation remains distinct from recovering the intended form and producing a correct complete answer.

Improved glyph copying does not restore complete-answer generation

Training on genuine copy-prompt states separates physical writing from language decisions (Supplementary Note 61; Fig. S40). Removing source-anchor regression from the writer objective improves held-wording glyph F1 from 0.951778 to 0.972856 and the number reaching F1 0.95 from 194/256 to 229/256. Complete development-answer transfer nevertheless fails: the resulting image-feedback model gives no canonical exact answer among sixteen reused questions. On a fresh C3 cohort, neither the original nor the improved writer produces a clearly correct complete answer phrase among 32 conditions. A separate source-policy diagnostic isolates a sequence-interface problem: with identical image prefills, native source-unit feedback gives twelve literal matches among sixteen questions, whereas both exact-character and image-encoded character feedback give three. These helper trajectories use a source lexical head and are not ILM answers. The comparison motivates adapting sequence dynamics, but does not establish that frozen contextual states cannot support an independently trained writer.

Contextual adaptation improves autonomous image answers

Adapting the final four contextual layers, together with the image writer and stopping head, improves complete answers relative to a broader-data readout-only control (Supplementary Note 62; Fig. S41). Both conditions use 3,176 training questions and 18,000 updates. On 32 prospectively reserved questions from 16 contexts, conservative clear complete literal matches are 16/32 versus 11/32; both different questions are correct in 5/16 versus 2/16 contexts. Canonical pixel-exact complete answers are 2/32 and 1/32. Neither condition meets the predefined pilot requirement

of 24/32 matches and 10/16 paired contexts, and both retain a failed training-pixel qualification. The result demonstrates partial image-conditioned answer transfer, not a reliable general language model. Training first-glyph fidelity is lower than later reference-conditioned fidelity, so generated-image feedback cannot explain every failure. A separate cold replay reproduces the full image-feedback execution on one fixed input without runtime lexical, font or answer-bank access.

An additional balanced writer refinement isolates a training-fit problem. With the learned reader fixed, batched first/later supervision raises training F1 from 0.963524 to 0.999811 and passes physical qualification. On a different reserved cohort, however, clear complete answers are 18/32 versus 19/32 for the unchanged parent, with two canonical exact answers each. The one-case reading difference is a damaged initial glyph, not an established semantic regression. Neither passes the answer pilot (Supplementary Note 62; Fig. S42). Stronger reference-conditioned fitting alone has not established a generalization gain.

Historical glyph fidelity and resolution

We encoded and decoded 27 catalogued oracle, bronze and seal glyph rasters from sealed source families. The rasters had no exact match in the original historical training partition for the fixed codec. Twenty round trips were pixel-exact, and mean foreground F_1 was 0.9981 (Fig. 11).

The bronze source B12643 retains only ten ink pixels at 32×32 even though its codec reconstruction is exact. Its 128×128 raster reveals thin strokes lost at the smaller size. Five tall bronze forms represented as four vertically stacked tiles averaged foreground $F_1 = 0.9389$ after decoding and reassembly. All five changed pixels. The historical reading and stage-selection tests remain unevaluated with a trained language checkpoint.

Complete-sequence adaptation exposes a compact writing failure

We next test a smaller contextual foundation on complete continuation and question–answer sequences. The deployed contextual layers contain 1,409,410,048 externally pretrained parameters from a Qwen3 1.7B archive[18], with vocabulary embeddings and the lexical output head absent. A frozen 7.42M-parameter codec maps each visible glyph to 768 continuous coordinates. A learned image interface groups up to sixteen glyphs, supplies one to three contextual updates per span, predicts the next span's length and writes its image. Subsequent context receives the emitted pixels. This experiment transfers inherited language knowledge to a visual interface; it does not establish language acquisition from images alone.

The corpus contains 13,785 training sequences: 4,762 public-domain book passages from fourteen works and 9,023 complete CMRC question–answer pairs[12]. The targets contain 2,576,239 glyph positions. Whole works and passage groups define the development partition; exact source, text and pixel overlap checks pass, while exposure during inherited pretraining is unknown. Offline teacher extraction supplies 2,380,620 causal state targets. One complete fit makes 8,172 updates over all 108 shards, adapting 12,872,213 image parameters and an 8,388,608-parameter training-only projection. The contextual body and codec remain frozen. Extraction and fitting take 1,783.41 and 1,759.83 seconds, including resource waits of 770.72 and 110.11 seconds.

Peak allocated GPU memory is 13.396 and 3.930 GiB, respectively. These are preparation and adaptation costs; they exclude the inherited foundation's original training.

The fixed evaluation uses 32 questions in sixteen held-out passage groups and twelve prefixes from two held-out books. All normal inputs run at steps 0, 1,956, 4,049, 6,152 and 8,172. Endpoint erased-input controls bring the total to 372 generated pages. Every checkpoint scores 0/32 complete exact QA answers and 0/16 both-correct pairs (Fig. 12). The source-matched Qwen3 1.7B native-text reference gives 8/32 exact answers and 2/16 both-correct pairs on the same normal prompts. Its run is on CPU; the comparison does not establish a matched-hardware efficiency advantage.

One model-based reviewer inspected opaque answer images before opening the mapping to cases and checkpoints or the scoring references. The reviewer had prior dataset familiarity; no independent human adjudication was performed. Thirty pages were blank and 342 had uncertain whole-response transcriptions. Individual characters or punctuation were sometimes recognizable, but no reliable complete reading was credited. Consequently, no readable complete book continuation was established. This limits the interpretation of its coherence score. All raw streams remain in the denominators. The same first QA pair and book prefix, fixed before fitting, are shown at every checkpoint in Figs. 13–15.

The final normal cohort has seventeen predicted stops and twenty-seven budget-limited streams, compared with forty-four predicted stops initially. Blank normal responses decrease from nine to two. Neither change establishes language learning. Endpoint question-erased and passage-erased QA counts also remain zero. The registered passage-group bootstrap returns [0, 0] intervals for the constant complete-answer observations and their paired differences. These degenerate sample intervals do not establish zero population success.

A separate traced final-checkpoint process reproduces the fixed 128-glyph book stream, its PNG, stopping/cap status and all 128 emitted-pixel feedback events. Required prompt and weight opens are verified, with no forbidden training/reference paths or IP connections observed. This checks the standalone boundary for that invocation, while its answer remains a language failure.

The writer has an identifiable capacity restriction. Its final linear velocity projection has rank 384 in a 768-dimensional codec space. For a complementary projector P, $PW = 0$ gives $Pv = Pb$, so the eight-step Euler endpoint satisfies $Pz_1 = Pz_0 + Pb$. At least 384 Gaussian directions cannot be contracted or conditioned by this continuous velocity model. Terminal normalization can restrict the varying output further. The result is an exact-arithmetic capacity statement, not a hardware-exact sampler identity or proof of the sole cause of failed answers. A separately registered 1,024-channel writer comparison removes this tested restriction, as evaluated below.

Removing the writer rank restriction is insufficient

The controlled comparison changes the writer width from 384 to 1,024 while preserving the corpus, exposure, six objectives, optimizer schedule and seed. The initial encoder, length head and teacher projection match the compact control. The wider writer's output projection, centered map and three tested local velocity Jacobians have rank 768 before and after fitting. Its image

parameters increase to 48,547,733, with the same 8,388,608-parameter training-only projection. One pass again completes 8,172 updates. Fitting takes 1,945.56 seconds, including 150.14 seconds of resource waiting, with 4.889 GiB peak allocated GPU memory.

All five wider-writer checkpoints still give 0/32 complete exact QA answers and 0/16 both-correct pairs (Fig. 16). Another opaque review retains all 372 outputs: twenty-four are blank and 348 have uncertain whole transcriptions. No readable complete book continuation is established. The final normal cohort contains thirteen predicted stops, thirty-one budget-limited streams and four blanks. All erased-input QA scores remain zero. The separate trained cold child reproduces its fixed pixel stream and feedback without observed forbidden accesses. Its wrapper terminated before writing verification, for an unknown reason; the completed original child traces permit CPU-only recovery without rerunning inference. Removing the rank restriction therefore does not solve language under this recipe.

Conditional writing fails before emitted feedback

We localize the failure with frozen weights in both final checkpoints. The fixed diagnostic contains eight QA and eight book records from each of the training and development partitions. At most eight following spans per record give 201 spans, containing 122 training and 131 development glyphs. Every writer arm receives the reference next-span length. Controlled history and count supplies separate physical writing from autonomous inference.

Correct image history with eight sampling steps gives foreground F1 of 0.3801/0.3477 on training/development targets for V1 and 0.3720/0.3518 for the wider writer (Fig. 17). Direct codec reconstruction exceeds 0.9998 F1 and exactly reconstructs 117/122 and 128/131 glyphs. Increasing the writer to 64 sampling steps does not repair writing. A native-embedding bypass, which changes the conditioning distribution, also remains poor. These supplied-target F1 values measure pixel reconstruction, not semantic answer quality.

The first target spans contain twenty training and twenty-six development glyphs. Both models have zero exact matches under correct history. Their first outputs are identical to the emitted-history arm, before feedback can diverge. Generated-history drift alone cannot explain these failures. Later emitted-history arms deteriorate further. All reference lengths remain supplied, so none of these arms is a new autonomous language result.

The reader has a separate restriction. Its 384-channel terminal-normalized feedback head has a 383-dimensional affine family for 2,048-dimensional native targets. Even after relaxing preceding image-network constraints, the best possible relative squared error on selected source positions is 0.5705/0.5768 for V1 and 0.5685/0.5754 for the wider fit, compared with achieved errors around 0.75 (Fig. 18). These are target-alignment bounds under the fixed trained heads, not language-quality bounds. No complete prompt grouping exactly matches the reference in either model, despite high local count accuracy and contextual cosines. Those representation diagnostics do not establish comprehension.

An initial prefix-consistency interruption led to a separate one-case precision probe. Full versus truncated BF16 evaluation gives relative RMS error 0.05029; FP32 arithmetic on the same

rounded weights reduces it to 2.59×10^{-6}. Same-shape future erasure is bit-equal. The completed diagnostic uses matching cached execution and retains the original consistency tolerance. It takes 260.16 seconds with 3.401 GiB peak allocation and no optimizer updates. The stopped attempt, probe and CPU preparations bring these registered stages to 467.24 seconds. The evidence rejects an unchanged compact fit or a sampler-only repair, without identifying a single cause of all failed answers.

Input presentation changes retained answers but fails retention

To test whether the compact failures discard previously demonstrated image answers, we evaluate the unchanged earlier contextual-tail actor on the same cohort. This actor retains 7,522,463,984 inherited visual/contextual parameters and uses a deterministic complete-glyph writer with actual emitted-pixel feedback. It gives 2/32 strict complete exact QA answers, both from one passage pair, and 3/32 readable QA outputs. Neither compact final checkpoint retains the two exact answers. The third readable output omits a canonical parenthetical alias and fails unchanged strict matching; this does not establish semantic falsity. All twelve book continuations reach the cap, with no credited readable coherent complete continuation. Different bodies, writers and adaptation histories prevent a causal model-size comparison.

The frozen full-prompt comparison changes input font, spacing and wrapping together while preserving every passage and question. There are no new optimizer updates or answer-centered crops, and the output cap remains 128 glyphs. Median page height changes from 704 to 512 pixels at 1,024-pixel width. Complete exact QA rises to 6/32, with a pointwise 95% passage-group bootstrap interval of 6.25–31.25%. Whole-response readability rises from 3/32 to 11/32, and QA caps decrease from 24/32 to 13/32 (Fig. 19). However, both-correct pairs fall from 1/16 to 0/16. The exact-answer gain is 12.5 percentage points, with interval 0–25; the paired difference is minus 6.25 points, with interval minus 18.75 to zero. Both difference intervals include zero. The previously exact area answer becomes unreadable, while the location answer and shorter instrument list remain readable. The registered retention rule therefore fails.

All 120 fixed-cell and 96 proportional-input outputs are retained. Separate opaque reviews freeze their complete readings before reference scoring, with prior cohort familiarity and no independent human adjudication. Both erased QA conditions give zero exact and zero readable answers in both layouts. Readable concise answers, omitted aliases and one digit/letter discrepancy are preserved without post-hoc transcription repair or a substituted semantic metric. This repeated development cohort supplies no untouched confirmation or independent training-seed replication. The comparison tests presentation transfer of inherited capability, not language acquisition from images alone.

The fixed-cell run takes 1,589.88 seconds for 120 inputs; the proportional run takes 1,179.29 seconds for 96. Both peak at 17.786 GiB allocated memory. Their different input counts prevent a matched speed comparison. Separate fixed-book and fixed-question cold invocations reproduce signed pixels, contextual states, stopping and actual feedback, with no observed forbidden input access or IP connection. Those replay checks establish execution for the tested cases, not reliable

language. Neither input presentation qualifies a usable visual language interface.

Native answer access exceeds glyph strict matching

The completed native-reader diagnosis authenticates 448 calls and reproduces all 192 adapted image-prefill states bit-for-bit from actual glyph generation. An external native lexical decoder receives those states; its tokenizer, output projection and previous-symbol embeddings never enter the ILM. Adapted native continuation gives 4/32 exact fixed-cell answers and 10/32 proportional answers, versus the glyph actor's 2/32 and 6/32 (Fig. 20a,b). Both-correct pairs are 1/16 in each adapted native image arm, versus 1/16 and 0/16 through glyph output. The proportional native-minus-glyph exact difference is 12.5 percentage points, with a pointwise 95% passage-group interval of 0–25 points. These are reused-development contrasts, not untouched confirmation.

Seven proportional cases are exact only through native continuation, three only through glyph output, three through both and nineteen through neither. Six native-only cases have uncertain whole glyph readings; the seventh omits a canonical alias. The three glyph-only cases instead have native wording or punctuation differences, without establishing native semantic error. The lost area answer remains exact through native continuation while its proportional glyph stream is unreadable. Retained native access therefore exposes a writing/continuation gap without identifying a unique mechanism.

Disabling contextual adapter outputs changes native exact scores to 2/32 fixed-cell and 13/32 proportional. Complete text controls give 11/32 adapted and 10/32 with adapter outputs disabled. Proportional-minus-fixed native gains are 18.75 points [6.25, 31.25] adapted and 34.375 points [21.875, 50] with adapter outputs disabled. Layout brittleness thus extends to native reading; mixed adapter effects do not justify globally replacing the deployed body. All eight question- or passage-erased image arms give zero exact answers. The helper produces no new ILM images or optimizer updates.

The subsequent CPU audit authenticates all 192 original QA glyph streams and their first-state bindings. Before scoring, the rasterizer reproduces every one of 4,096 primitive characters and all 745 canonical target tiles exactly. All 32 first forms have primitive coverage. Supplied-image reconstruction is 31/32 pixel-exact at those first positions, with mean foreground F1 0.999934. Original normal first images instead have mean canonical F1 0.492173 fixed-cell and 0.632918 proportional, with 0/32 and 3/32 exact bitmaps. These are physical comparisons, not character or semantic accuracy: both exact complete fixed-cell answers have nonidentical first pixels, and valid alternative wording can begin with another form.

Across full canonical answers, 743/745 positions have training-primitive coverage; two absent forms occur later, leaving thirty complete answers fully covered. Supplied reconstruction is exact at 726/745 positions, with mean F1 0.999220. The covered subset has mean F1 0.999933; the two absent forms give 0.734417. Coverage describes exposure rather than a hard decoder vocabulary. No stream stops before its first image. These controls reject missing first forms or poor direct reconstruction as a general explanation for initial damage, while retaining wording, later writing, stopping and feedback limitations. Complete glyph-language scores remain unchanged.

Discussion

The results separate a useful visual predictive state from a useful visual language generator. The established causal reader learns context-dependent next-writing information, while subsequent writers can erase that information or model the marginal appearance of glyphs. A complete visual language model must bind meaning and sequence to the exact marks it generates.

The compact complete-sequence fit adds a larger authentic target stream while keeping the contextual foundation fixed. It completes training within one 4090 but does not produce a credited readable complete answer on its fixed development cohort. Its independent cold replay verifies execution boundaries, not comprehension. The velocity projection has a provable noise subspace; terminal normalization also matters when repairing its width. The completed wider-writer comparison removes the tested restriction but retains zero complete exact QA answers at every checkpoint. Correct-history diagnostics show writing failure before generated feedback, while a separate reader restriction limits native-target alignment. These results reject the unchanged joint recipe and a sampler-only repair. The matched earlier-actor control retains two exact answers and one fully correct question pair on the same cohort. Full proportional prompts raise exact answers to six but lose that pair and an earlier readable answer, failing the registered retention rule. This establishes presentation sensitivity and limited inherited transfer, without establishing a consistently better interface or new learning. The matched native continuation gives ten exact proportional answers from the same adapted first states, while its lexical decoder remains outside the ILM. Native reading also depends strongly on layout. All first target forms have primitive coverage and supplied reconstruction is nearly exact, yet some original first forms are already damaged. Canonical pixel mismatch can also reflect readable strokes or different wording. Neither missing first forms nor later feedback alone explains every failed answer. Further model changes require controlled tests of conditional writing, stopping and generated-history feedback, followed by untouched source groups and independent review after any development improvement.

An image interface enlarges the representable output space, including the possibility of forms absent from a character encoding. It does not remove the need to learn syntax, knowledge or long-range dependencies. This study has not demonstrated general instruction following, etymology answers, handwriting transfer or arbitrary historical-script generation. It also lacks independent training-seed replication and a capability-matched text-model comparison. Small allocated memory in a bounded experiment establishes feasibility on one GPU, rather than a general efficiency advantage over language models.

Supplied-target reconstruction is preserved by an aligned inverse-image path; the free image writers still fail reliable new prompt-directed copying. The separate source-pixel component passes its new-copy test but fails natural-reading qualification. The remaining test is whether context selects and generates a coherent written future. Low teacher-forced image NLL can reflect dependencies among strokes already revealed within the target, while generated output still loses global identity. Joint training improves proper likelihood beyond matched extra density training; the raw generated continuations still fail the intended language test. Conditional continuation

and short answers require counterfactual prompts and the same context effect during autonomous sampling and visible feedback. Broader books and offline teacher-generated exercises can supply later training data while leaving the final inference path independent. A larger corpus or longer training requires improvement on the intended generation task, beyond the conditional-likelihood gain established here.

Broader pixel training reproduces 495 of 512 answers but still fails the supplied unseen reference images. The matched native reader retains useful answer capability, directing the intervention toward the learned writing interface. The complete-glyph loop supports restricted input-dependent date composition, with actual-image feedback independently replayed. It remains unreliable on broader questions: eleven of sixteen normal Chinese streams cap. Wider semantic readout coverage and robust generated histories remain necessary; clear familiar glyphs and low training loss are insufficient.

Recent visual generators study mixture assignment and the geometry of distribution matching [13,14]. These results motivate more expressive writing distributions, but marginal image fidelity cannot certify an answer. A generator that swaps the correct images for two equally frequent questions preserves the answer-image distribution while answering both incorrectly. Conditional supervision and prompt interventions therefore remain necessary; natural-image gains do not establish a shortcut to language learning.

An inherited visual/contextual successor provides a separately measured execution route. With its vocabulary module removed, the complete 7.548B actor trains 25.58M adapter/writer parameters within 17.181 GiB allocated memory. Causal, backward and resume checks pass after explicit precision repairs. Eight short source-engine sanity cases support the contextual initialization; no image-language ability follows from that check. Its continuous writer fails its reconstruction test (Supplementary Note 23). The separate qualified codec preserves supplied writing, while the completed predicted-code actor fails its autonomous language test (Supplementary Notes 25–28). Poor first-block and exact-history predictions, including on training cases, show that generated-history drift cannot be the sole explanation. Conditional feature information, readout capacity, the objective and optimization remain possible limitations. The current evidence does not select a successful density, optimizer or semantic-transfer method. External pretraining remains part of the model's provenance.

Methods

Compact continuous glyph feedback

The compact experiment receives ordered 32×32 binary ink tiles, with one fixed Noto Sans CJK face during data preparation. The fixed codec maps each tile I_j to $z_j \in \mathbb{R}^{768}$. A 384-channel image encoder uses learned boundaries to group at most sixteen glyphs. It predicts one to three continuous updates $u_{i,r} \in \mathbb{R}^{2048}$ per span. The frozen 28-layer contextual body consumes those vectors directly and supplies the state c_i after each span. During training, native source alignment supplies span ends and update counts; at inference both are derived from visible pixels.

The writer predicts length $K \in \{0,\dots,16\}$ from c_i. Length zero ends generation. For a nonempty span, a conditional rectified flow starts from $z_0 \sim \mathcal{N}(0,I)$ and applies eight Euler steps,

$$z_{k+1} = z_k + \tfrac{1}{8} v_\theta(z_k, k/8, c_i), \qquad k = 0,\dots,7. \tag{5}$$

The codec decodes the endpoint into binary ink. The same image encoder reads these actual emitted pixels to update contextual history. No font renderer, OCR service, lexical head or answer lookup supplies generated content. The 128-glyph budget can stop before a full predicted span would exceed the cap; that stream is recorded as budget-limited rather than naturally stopped. Raw page segmentation and arbitrary reading order are outside this tile-stream experiment.

Six complete-sequence objectives

The reference-image training history differs from generated-image history at inference. Each complete sequence supplies all continuation/answer spans and its terminal decision. For predicted feedback vector $\hat{u}$ and compact source embedding e, the relative regression objective is

$$\mathcal{L}_{\text{fb}} = \mathbb{E}\frac{\|\hat{u}-e\|^2}{\max(\|e\|^2, 10^{-8})}. \tag{6}$$

Training-only source embeddings and native span alignment come from the authenticated source archive; they do not enter deployed inference. The encoder also minimizes update-count cross entropy $\mathcal{L}_{\text{count}}$ and binary span-boundary cross entropy $\mathcal{L}_{\text{boundary}}$. The writer minimizes span-length cross entropy $\mathcal{L}_{\text{length}}$, including the zero-length terminal. For clean codec span y, fresh noise ε and $t \sim U(0,1)$, its velocity objective is

$$z_t = (1-t)\varepsilon + ty, \tag{7}$$

$$\mathcal{L}_{\text{flow}} = \mathbb{E}\|v_\theta(z_t,t,c) - (y-\varepsilon)\|^2/d, \qquad d = 768. \tag{8}$$

Only valid glyph positions contribute. An offline Qwen3-VL teacher[17] supplies causal context states $h^T \in \mathbb{R}^{4096}$. A training-only linear projection $A : \mathbb{R}^{2048} \to \mathbb{R}^{4096}$ gives

$$\mathcal{L}_{\text{teacher}} = \mathbb{E}[1 - \cos(Ac, h^T)]. \tag{9}$$

The implemented objective is the equal-weight sum

$$\begin{aligned}\mathcal{L} = {} & \mathcal{L}_{\text{fb}} + \mathcal{L}_{\text{count}} + \mathcal{L}_{\text{boundary}} + \mathcal{L}_{\text{length}} \\ & + \mathcal{L}_{\text{flow}} + \mathcal{L}_{\text{teacher}}.\end{aligned} \tag{10}$$

The corpus has 7,255,223 training glyph positions including repeated QA passages, and 2,576,239 continuation/answer target glyph positions. Its 13,785 sequences cover fourteen training works and 9,023 QA pairs. Two whole works and separate CMRC passage groups form the development partition. Exact source, text and input-pixel overlap checks pass. Pretraining exposure of either

inherited foundation remains unknown.

The offline teacher body supplies 2,380,620 state targets in 108 authenticated shards. The fit uses seed 202611152, AdamW at learning rate 2×10^{-4}, weight decay 0.01, gradient norm capped at 1.0 and a 1,024-position padded batch budget. Trainable parameters remain FP32. Frozen contextual matrices are dequantized from the authenticated GGUF archive into BF16, and neural computation uses BF16 autocast. All 8,172 updates complete one pass. Five snapshots preserve initial, quarter, half, three-quarter and final shard exposure, recording their actual optimizer steps. Training resumes only with the original source, corpus, teacher-cache and configuration identities.

Compact evaluation, review and provenance

The prospective development cohort contains 32 QA prompts from sixteen passage groups and twelve prefixes from two whole-held-out works. The five snapshots use seed 202611153, eight flow steps, the same normal prompts and a 128-glyph budget. The initial and final snapshots additionally run question-erased, passage-erased and book-prefix-erased controls, giving 372 pages. One model reviewer transcribes opaque original images before their mapping and scoring references are opened. Prior dataset familiarity is disclosed. Uncertain whole transcriptions, blank responses and caps stay in the original complete answer denominators. This is not independent human adjudication.

Exact QA success requires a reliable nonempty transcription matching the canonical answer and a learned stop. Both-correct pairs require both answers and distinct output images. Book coherence is judged against the visible prefix; an uncertain whole transcription cannot establish readable coherent continuation. Pointwise 95% intervals use 10,000 whole-passage-group bootstrap replicates, seed 202611154, retaining both questions per group. The same groups are resampled for final-minus-initial and normal-minus-erased differences. With constant zero observations the interval degenerates; it cannot establish zero population success. Two book works do not support a book-level interval. This small development cohort also requires fresh confirmation after any model-selection improvement.

The unchanged native-text reference uses the same 44 normal prompts with Qwen3 1.7B on CPU; its book coherence remains unrated. A traced fresh-process replay separately checks the final image actor's fixed book output, exact display pixels, termination and emitted-pixel feedback against its suite run. The child receives only the visible input, authenticated foundation/codec and deployable image heads. Access auditing distinguishes an unused vocabulary inside source-archive metadata from materialized lexical model modules or answer access. Preparation, fit and inference costs are recorded separately.

Wider writer and frozen failure localization

The controlled wider writer uses 1,024 hidden channels for a 768-dimensional velocity. All other registered training choices remain fixed, including seed, initial encoder, length head and teacher projection. CPU-only construction preserves the GPU random state. Initial and final output, centered-output and local Jacobian ranks are checked separately from language quality. The

same five-checkpoint protocol, 372 opaque images and complete-answer definitions apply. The cold child's original traces are retained, including its parent-wrapper interruption and CPU-only verification recovery. No inference rerun supplies that receipt.

For failure localization, source groups are ordered by a fixed hash, taking eight QA and eight book records per partition. The two development works contribute four records each. Both final checkpoints remain frozen. The six writer arms use correct image history at eight or 64 flow steps, native source-embedding history, an incorrect reference context, emitted history with supplied update counts, or learned prompt grouping with emitted history. All receive reference output lengths and identical per-span initial noise. The direct codec control reconstructs the targets without the writer. Native history is an explicit distribution-changing bypass. Gold history, span lengths and counts are diagnostic supplies, not available autonomous answer information. First-span measurements precede generated feedback.

Pixel metrics are independently recomputed from persisted binary targets and outputs, including blank-target and nonblank-target exact counts. Original PNGs, noise hashes and feedback hashes are authenticated. Latent errors are not independently recomputed because separate target latents were not saved. The first registered case of each split/kind supplies the raw displays; that deterministic display rule was introduced during analysis, not preregistered. These selected diagnostics have no semantic grading or generalization interval.

For the reader, write D for the fixed output scaling and μ for its mean. With the final LayerNorm parameters γ, β, projection W, b and $C = I - \mathbf{1}\mathbf{1}^\top/384$, every feedback vector lies in

$$a + \mathrm{col}(A), \qquad A = DW\,\mathrm{diag}(\gamma)C, \tag{11}$$

$$a = \mu + D(W\beta + b). \tag{12}$$

Both final heads have $\mathrm{rank}(A) = 383$. If Q is an orthonormal basis of its column space, relaxing all preceding network constraints gives the target error floor

$$\ell_{\min}(e) = \frac{\|(I - QQ^\top)(e-a)\|^2}{\max(\|e\|^2, 10^{-8})}. \tag{13}$$

The reported mean weights selected source positions uniformly. It is not the original objective's batch weighting or a lower bound on language error.

The first diagnostic stops at its original prefix-consistency tolerance. A separate one-prefix probe compares full and truncated sequence execution, same-shape future erasure, cache/mask controls and FP32 arithmetic using the same BF16-rounded weights. Its twelve contextual calls and twenty-four velocity calls are recorded separately. The completed diagnostic uses matching prefix prefill and cached updates for reference and generated history, retaining the original tolerance. The stopped attempt, probe, completed run and CPU preparation costs remain in the evidence. No optimizer update or new autonomous language result is attributed to this diagnostic.

Matched earlier actor and full-prompt presentation

The earlier actor uses a separate inherited 36-layer visual/contextual body, four adapted tail layers and a complete-glyph CNN encoder/decoder. Its previously fitted checkpoint remains fixed throughout these comparisons. All 32 compact-cohort QA questions, both erased-input controls and twelve book prefixes with their erased controls give 120 fixed-cell inputs. All 32 QA questions and their 64 erased controls give the 96 proportional inputs. No earlier successful pair, short reference or favorable font-coverage subset is selected. Recorded adaptation data contain 3,176 admitted questions, with no current question, normalized passage or exact training-PNG overlap. Inherited pretraining and all earlier ancestors remain uncertified.

CPU preparation authenticates each original complete source prompt. The proportional view reuses the exact earlier Pango renderer and Noto CJK face, 24-pixel font size and 32-pixel strip height. Each source newline becomes one ordinary space; all non-whitespace codepoints remain unchanged. Capacity is measured from the full prompt without shrinking or truncation. Blank-column wrapping preserves and exactly recovers the complete rendered strip. Passage, question and structural ink masks are isolated without changing shaping, must be disjoint and must reconstruct every normal ink pixel. Erased views whiten only the original field pixels in place, retaining the normal wrap ranges, canvas and all other ink. All 96 images pass exact strip/page roundtrips and the unchanged host preparation. Preparation takes 4.16 seconds.

The native visual observer, numeric task frame, deterministic contextual numerics, learned stop threshold and 128-glyph cap remain unchanged. The deterministic writer produces binary glyph images and rereads their actual pixels. Each complete output retains its original signed tensors, displayed PNG, states, feedback hashes and cap/stop decision. The deployed answer path has no lexical output module, tokenizer, font renderer, reference answer or external teacher. Zero new optimizer updates occur in either comparison.

One model reviewer inspects all opaque outputs and ambiguous enlargements before the corresponding mapping or references are opened. Proportional outputs use presentation-specific opaque identifiers, preventing reuse of the earlier display mapping. Frozen readings give three complete readable fixed-cell outputs and eleven proportional outputs; the remaining 117 and 85 whole responses are uncertain, with no blank outputs. Reviewers have prior dataset and earlier-output familiarity. No independent human adjudication is performed. The original complete canonical exact-match, learned-stop and distinct-pair requirements remain fixed. Noncanonical wording is not relabeled as factually false, and no favorable semantic score is added after inspecting answers.

Pointwise intervals use 10,000 whole-passage-group paired bootstrap draws, seed 202611154. Constant zero groups give degenerate sample intervals, without proving zero population success. The registered development rule requires gains in exact answers, correct pairs and readability while retaining the three original readable cases and not increasing QA caps. Its paired gain and exact-answer retention conditions fail. An additional conservative core-prefix retention check was implemented during generation before new output inspection; it is not described as preregistered

and is unnecessary to reject the original rule. Figure 19's three raw example pairs were chosen after scoring to show the lost area, retained location and first newly exact quantity answer. They do not substitute for all registered denominators.

The fixed-cell and proportional runs include 80.20 and 97.89 seconds loading, with 1,484.92 and 1,060.67 seconds of generation, respectively. Both record zero resource-pressure wait. Earlier adaptation, inherited pretraining and corpus preparation remain excluded costs. The fixed-book cold replay takes 84.89 seconds at 17.757 GiB, and the proportional fixed-question replay takes 79.08 seconds at 17.693 GiB. Each independent traced invocation checks actual signed pixels, states, stopping and feedback. The unchanged command-line viewer lays out a long row rather than the suite grid; exact tensors and display pixels, rather than PNG layout bytes, verify the proportional replay. No observed forbidden corpus, reference or font access or IP connection occurs. These are fixed-case boundary checks, separate from language accuracy.

Matched native continuation and first-writing audit

The native diagnostic keeps all 32 questions, both full image presentations, normal inputs and both erased controls. Each image case runs with the learned contextual adapters and with their output matrices set to zero, giving 384 image calls. Complete text prompts give 32 calls per adapter condition, for 448 calls total. One shared body executes the conditions serially. All 192 adapted image-prefill vectors match the actual glyph actor's saved first states exactly. The source-adapter control changes that contextual condition; it does not authorize replacing the deployed image-output actor.

The native tokenizer, vocabulary projection and previous-symbol embedding lookup remain helper-only variables. The BF16 source projection contracts with each FP32 contextual vector in ascending 4,096-row chunks using FP32 arithmetic, with lower source index breaking exact ties. Greedy continuation ends at a source terminal symbol or 128 source units. This cap differs from the glyph actor's 128 emitted images, so neither output lengths nor costs form a matched-unit efficiency comparison. Raw source IDs, selected logits, decoded texts, hidden states and ending decisions are retained. CPU scoring verifies every case and original glyph-score binding. A score-receipt schema lookup is corrected without regeneration or any change in references or matching. Whitespace-only normalization, natural ending and distinct paired answers retain the original strict scoring rules. No semantic regrading is added.

Native and glyph differences use 10,000 paired whole-passage bootstrap draws with seed 202611154 and pointwise 95% intervals. The same sixteen passage groups define all comparisons. Unknown inherited pretraining exposure, development reuse and prior output familiarity remain limitations. Native execution takes 2,838.924 seconds, including 158.819 seconds setup and 180.172 seconds pressure waiting, at 18.947 GiB peak allocated GPU memory. It makes no optimizer update or new ILM image; acquisition and earlier adaptation remain excluded costs.

The subsequent CPU preparation authenticates all 192 original QA streams, first states, stop decisions and signed-image/PNG/feedback bindings. Canonical target compatibility is checked against the original Noto CJK SC collection face 2, size 26, baseline 26 and 32-square binary

rasterization. All 4,096 selected primitive characters reproduce their 4,087 unique image arrays, and all 745 source target tiles reproduce exactly before neural scoring. Character and exact-bitmap membership are counted separately over all first and later targets, without removing absent forms. The evaluator-only inventory never enters inference.

For target ink image I, the answer-supplied physical control computes

$$\widetilde{I} = \mathbf{1}\left[\sigma(D(E(1-2I))) \geq \tfrac{1}{2}\right],$$

where E is the frozen image encoder and D includes the frozen motor projection and image decoder. Batches of 32 use FP32 CPU arithmetic and two threads. Original GPU emissions are never replaced by this reconstruction. Per-image foreground F1 is $2\mathrm{TP}/(2\mathrm{TP}+\mathrm{FP}+\mathrm{FN})$; means average images rather than pooling pixels. Two empty arrays receive one; an absent emission receives zero and is distinct from a blank tile. Pixel exactness requires identical arrays. First-pixel disagreement can reflect different wording or readable learned strokes and does not imply semantic error. All original whole-answer readings and strict scores remain fixed.

An independent CPU recount verifies every counter, coverage flag and outcome subgroup from saved arrays, plus all 128 tiles in the two labelled comparison boards. Those boards are inspected with prior cohort familiarity, without independent human review. Preparation takes 6.539 seconds without a neural call; supplied reconstruction takes 1.502 seconds at 1.078 GiB peak process RSS. CUDA remains uninitialized, and there is no contextual call or new optimizer update. Figure 20's first-tile examples are retrospective selections from these completed controls and are explicitly excerpts rather than full answers.

Initial raster control data

The public Chinese stream contains 7,017 provenance-tracked records. Records are assigned deterministically to training, development or a sealed partition before rendering. Original and simplified views inherit their source split. Both generation experiments use one fixed Noto Sans CJK font, 26-pixel writing inside 32-pixel cells, without image augmentation. A 65-cell training segment supplies the first 60 cells as context and cells 61–64 as future writing. The remaining cell is unused. No string, source identifier or symbolic target enters a model method. Sealed records remain unopened.

Initial raster control training

In the diffusion experiment, the reader is frozen. Copied glyph-prior weights initialize the denoiser, which is then optimized as a velocity predictor. AdamW uses a learning rate of 5×10^{-5} for transferred layers and 2×10^{-4} for new modules, 400 warmup updates, cosine decay to 10%, batch size eight, BF16 arithmetic and gradient clipping at one. EMA decay is 0.999. Checkpoints retain model, optimizer, RNG, dataset offset and provenance hashes. Interrupted and continuous smoke runs produce byte-identical model and EMA weights.

The field objective applies an orthonormal transform directly to floating signed predictions. Thresholding is confined to output and identity evaluation. This distinction is verified by an

isolated pixel-gradient test. The primary velocity MSE is supplemented by foreground, Dice, field and representation losses at weight 0.10 each, plus an ordered-history margin at weight 0.25. Supplementary Information gives the complete objective and gates.

The exact-density experiment uses 64-cell causal histories and 16 stratified positions in each of eight streams per update. A quarter of selected images receive supplied-image motor conditions; the remainder use predicted states. Binary observations are thresholded once before unweighted Bernoulli NLL. AdamW uses learning rate 2×10^{-4}, 400-update warmup, cosine decay, BF16, norm clip one and EMA 0.999. All 8,000 updates complete in 207.8 s with 0.400 GiB peak allocated CUDA memory. This timing excludes the frozen reader's earlier training. Exact resumed weights and EMA match uninterrupted smoke training. Strict-causality gradient tests and enumeration of a four-bit subproblem verify the probability masks.

The matched continuation reinitializes optimizer and EMA from identical exact-density weights. Both arms make 8,000 additional updates, using the same data and training generator. The joint arm uses reader learning rate 2×10^{-5} and density rate 2×10^{-4}, with the same schedule and motor mixture. It trains 18,711,840 participating parameters; the frozen arm trains 2,434,592. Joint and control times are 342.4 and 218.0 s, with peaks 0.648 and 0.400 GiB. Frozen-reader weights remain identical to initialization, while joint reader weights change. Both final training RNG states match. Development opens only after both arms finish.

The subsequent decoder retains eight partial images after each binary pixel expansion, ranked by accumulated Bernoulli log probability. Row conditions are gathered along beam-parent indices within each row. Stable ties prefer ink, matching the original width-one rule. Full FP32 matmuls are used for both new controls after a documented numerical preflight; model weights are unchanged. The maximum production incremental-score/parallel-NLL error is 2.10×10^{-5} nat, below the unchanged 0.001 tolerance. The complete inference audit takes 269.3 s at 0.154 GiB allocated CUDA memory.

The assignment experiment keeps the native eight-expert architecture and trains all parameters from the same V62 EMA. Both arms score the same four streams for every sampled pair. AdamW, sample order, update budget and final EMA selection match. The auxiliary penalty has temperature 0.01 and weight one for aligned, zero for control. Complete details, independent runtime replay and the unchanged conjunctive gates appear in Supplementary Note 22.

Separate continuous writing coordinates

The successor uses a visual reader E_r, contextual body F_θ, output projection A_θ and frozen writing codec (E_w, D_w). For observed prompt image X and completed answer blocks $Y_{<t}$,

$$h_t = F_\theta(E_r(X), E_r(Y_{<t})), \tag{14}$$

$$\widehat{z}_t = N(A_\theta h_t), \qquad z_t^* = \mathrm{sg}(E_w(Y_t)), \tag{15}$$

$$\widehat{Y}_t = D_w(\widehat{z}_t). \tag{16}$$

Here h_t contains two structural queries, N is nonaffine LayerNorm with $\varepsilon = 10^{-5}$, and sg stops label gradients. Each writing state comprises two continuous 768-vectors for two physical 32×32 tiles, without character segmentation. The encoder already normalizes its codes; the state loss explicitly normalizes both arguments again:

$$\begin{aligned}\mathscr{L} = \mathrm{MSE}(N(\widehat{z}_t), N(z_t^*)) \\ + \mathrm{MSE}(D_w(\widehat{z}_t), Y_t) + \mathscr{L}_{\mathrm{stop}}.\end{aligned} \tag{17}$$

Uniformly sampled block losses retain the complete teacher-forced history. A separate class-balanced stop loss supervises termination after the complete answer. Frozen decoder weights still transmit image-loss gradients into predicted codes and contextual adapters. Generation uses prompt pixels, learned stopping and only its own completed output images. This regression objective is not a normalized language likelihood or a guarantee against averaging distinct conditional writing modes. Execution and reconstruction are evaluated separately from language (Supplementary Notes 26–28). The complete instruction run fixes 10,000 updates and two examples per update under fresh full-corpus permutations, with final raw weights and no EMA. Its autonomous audit scores all 192 fixed normal prompts and their matched blank controls, preserving full widths and learned stops. Neither the actor nor its evaluator repairs generated pixels. The subsequent exact-history diagnostic uses the same final weights and no optimizer updates.

Sampling, controls and statistics

The diffusion experiment uses 32 registered DDIM schedule levels and classifier-free scale two. Four future cells start from Gaussian noise. The same noise is reused for ordered, suffix-preserving shuffled and zero-condition histories. Only one sample contributes to the primary block result. Generated cells are appended as visible rasters for a second four-cell block.

An evaluator-only canonical bank measures nearest-raster identity after generation. Targets outside the bank receive no identity credit, and bank coverage is reported per position. This measurement can assign a nearest identity to an illegible pseudo-glyph, so direct images and surface statistics accompany every result. Pixel F1 alone is also insufficient because many Chinese glyphs share strokes. No OCR is used by the model or the reported identity evaluator.

The exact-density audit uses 512 NLL targets, 256 single-image generations and 64 four-step feedback streams. Its sampler uses 32 row-transformer evaluations and 1,024 masked-head evaluations per image. Ordered and shuffled runs share the same Bernoulli uniforms. Its post-generation bank includes all distinct training forms plus every audit target, including punctuation: 9,932 unique binary rasters and 100% target coverage. This enlarged bank differs from the earlier Han-only bank. Zero condition is an out-of-distribution intervention, not a separately trained unconditional baseline. One standalone export embeds the complete reader and density; image-prompt inference reproduces the training-checkpoint continuation exactly under the same seed and greedy mode.

Confidence intervals use 2,000 bootstrap resamples of source records, retaining all windows from a record together. Paired differences use identical windows and initial noise. Intervals describe development-record variability for this trained checkpoint, not variability across training seeds. The current development partition has informed a sequence of experiments and is not a final independent generalization test.

The assignment comparison retains the same fixed 256 primary questions and 393 paragraph pairs. Its paired 95% intervals use 2,000 whole-article resamples, seed 20266329. Reference-energy ranking supplies accepted answers and remains a separate diagnostic. One seed, reused development data and external foundation training limit both this result and efficiency claims.

Data and code availability

Implementation, protocols, evidence summaries and scripts are available in `https://github.com/lachlanchen/ImagizedLanguageModel`. Manifest and checkpoint hashes identify the exact local research artifacts. Restricted reference books are not redistributed. The complete research record and Supplementary Information distinguish earlier foundation provenance from the present raster-only deployment experiment.

References

1. Tai, Y., Liao, X., Suglia, A. & Vergari, A. PIXAR: Auto-Regressive Language Modeling in Pixel Space. *arXiv* 2401.03321 (2024). `https://arxiv.org/abs/2401.03321`.
2. Li, T., Tian, Y., Li, H., Deng, M. & He, K. Autoregressive Image Generation without Vector Quantization. *Advances in Neural Information Processing Systems* (2024). `https://arxiv.org/abs/2406.11838`.
3. Chen, B. et al. Diffusion Forcing: Next-token Prediction Meets Full-Sequence Diffusion. *arXiv* 2407.01392 (2024). `https://arxiv.org/abs/2407.01392`.
4. Dhariwal, P. & Nichol, A. Diffusion Models Beat GANs on Image Synthesis. *Advances in Neural Information Processing Systems* (2021). `https://arxiv.org/abs/2105.05233`.
5. Yu, S. et al. Representation Alignment for Generation: Training Diffusion Transformers Is Easier Than You Think. *International Conference on Learning Representations* (2025). `https://arxiv.org/abs/2410.06940`.
6. van den Oord, A., Kalchbrenner, N. & Kavukcuoglu, K. Pixel Recurrent Neural Networks. *Proceedings of the 33rd International Conference on Machine Learning* **48**, 1747–1756 (2016). `https://proceedings.mlr.press/v48/oord16.html`.
7. van den Oord, A. et al. Conditional Image Generation with PixelCNN Decoders. *arXiv* 1606.05328 (2016). `https://arxiv.org/abs/1606.05328`.
8. Germain, M., Gregor, K., Murray, I. & Larochelle, H. MADE: Masked Autoencoder for Distribution Estimation. *Proceedings of the 32nd International Conference on Machine Learning* **37**, 881–889 (2015). `https://arxiv.org/abs/1502.03509`.
9. Hu, C., Tai, Y., Vergari, A., Keller, F. & Suglia, A. MIXAR: Scaling Autoregressive Pixel-based Language Models to Multiple Languages and Scripts. *arXiv* 2604.11575v2 (2026). `https://arxiv.org/abs/2604.11575v2`.
10. Holtzman, A., Buys, J., Du, L., Forbes, M. & Choi, Y. The Curious Case of Neural Text Degeneration. *International Conference on Learning Representations* (2020). `https://arxiv.org/abs/1904.09751`.
11. See, A., Liu, P. J. & Manning, C. D. Get To The Point: Summarization with Pointer-Generator Networks. *Proceedings of ACL*, 1073–1083 (2017). `https://aclanthology.org/P17-1099/`.

12. Cui, Y. et al. A Span-Extraction Dataset for Chinese Machine Reading Comprehension. *Proceedings of EMNLP-IJCNLP*, 5883–5889 (2019). https://aclanthology.org/D19-1600/.
13. Zhang, C. et al. Unifying Distributional Training for One-Step Visual Generation. *arXiv* 2609.35763v4 (2026). https://arxiv.org/abs/2609.35763v4.
14. Van Assel, H., De Brouwer, E., Saremi, S., Scalia, G. & Regev, A. Generate in Reconstruction Space, Match in Semantic Space: Transport Geometry for One-Step Generation. *arXiv* 2606.00514v2 (2026). https://arxiv.org/abs/2606.00514v2.
15. Tao, H. et al. Multimodal Flow: Unified Flow Modeling of Language and Vision in Embedding Spaces. *arXiv* 2609.40362v1 (2026). https://arxiv.org/abs/2609.40362v1.
16. Huang, L. & Wu, X. OCG: Optical Character Grounded Visual Reasoning with Flow Matching. Author manuscript (2026). Peer-review status unverified.
17. Bai, S. et al. Qwen3-VL Technical Report. *arXiv* 2511.21631v2 (2025). https://arxiv.org/abs/2511.21631v2.
18. Yang, A. et al. Qwen3 Technical Report. *arXiv* 2505.09388 (2025). https://arxiv.org/abs/2505.09388.
19. Databricks. Databricks Dolly 15k instruction dataset (2023). https://huggingface.co/datasets/databricks/databricks-dolly-15k.
20. Li, T. & He, K. Back to Basics: Let Denoising Generative Models Denoise. *arXiv* 2511.13720v1 (2025). https://arxiv.org/abs/2511.13720v1.
21. Xie, J., Yang, Z. & Shou, M. Z. Show-o2: Improved Native Unified Multimodal Models. *arXiv* 2506.15564v3 (2025). https://arxiv.org/abs/2506.15564v3.
22. Rajpurkar, P., Zhang, J., Lopyrev, K. & Liang, P. SQuAD: 100,000+ Questions for Machine Comprehension of Text. *Proceedings of EMNLP*, 2383–2392 (2016). https://aclanthology.org/D16-1264/.
23. Wei, H. et al. General OCR Theory: Towards OCR-2.0 via a Unified End-to-end Model. *arXiv* 2409.01704 (2024). https://arxiv.org/abs/2409.01704.
24. Clark, K., Vicol, P., Swersky, K. & Fleet, D. J. Directly Fine-Tuning Diffusion Models on Differentiable Rewards. *International Conference on Learning Representations* (2024). https://arxiv.org/abs/2309.17400.




Fig. 2 | Prediction and generated-image evidence. a, The established causal reader ranks completed next images above unigram, bigram and shuffled-history controls on 2,048 windows. These are ranking measurements, not generated text. **b**, Prior-plus-critic guidance retains completed-image ranking but almost never generates the target identity. **c**, Direct conditional block generation reports all four positions under ordered, shuffled and zero conditions. Bars use the same starting noise and single primary samples. **d**, Fixed, unselected examples show the target and all generated controls. Images are raw model outputs with nearest-neighbour enlargement. No OCR or image-bank replacement is applied.




Fig. 3 | Exact image likelihood separates motor success from language failure. a, A frozen image reader supplies an aligned plan and continuous history state. Strict row and pixel masks give a normalized raster law. **b**, Ordered-versus-shuffled NLL advantage on 512 development targets; the interval uses 2,000 source-record bootstrap draws and crosses zero. **c**, Supplied-image copying and autonomous next-image sampling on 256 targets. The copy controls reveal the answer. **d**, The first eight audit rows, shown without selection, compare target, exact supplied-image copying and autonomous controls. Every displayed output is the actual model raster. The 9,932-image evaluator bank is created after generation, covers all targets and never selects or replaces an output. Its identity rates are not directly comparable to earlier 1,024-image-bank results.




Fig. 4 | Question-dependent image answers remain inaccurate. a, Exact stopped answer and multiset raster F1 on 256 fixed questions from unseen articles, using full questions, blanked question pixels and the matched no-copy arm. F1 does not enforce order or correct termination. **b,c**, First two audit questions and raw answer images, with the first retained reference. The complete paragraph is also supplied to the model. No examples are selected or repaired; white output denotes a zero-cell answer. Question images are host renderings, and outputs are actual model rasters. All primary copy-arm answer cells are selected from the visible prompt.




Fig. 5 | Predicting whole observed image answers. a, The reader assigns probability to variable-length source image blocks, marginalizing identical sequences. **b**, Fixed development answers after matched additional training. F1 counts exact-raster multiset overlap; exact answers also require order and termination. **c**, First two audit questions, retained reference images and raw block answers, without example selection or repair. The full passage also enters the model. Block copying preserves forms but does not establish that the selected text answers the question.




Fig. 6 | Better pixel likelihood does not yield useful free writing. a, All-development answer/termination-pixel NLL, released base and final adapted EMA. **b**, Exact-raster multiset F1 and aligned foreground F1 on 256 fixed primary questions, with question-blanked and released-base controls. Foreground overlap does not establish a correct character or answer. **c**, First two fixed audit rows, with retained references and unmodified generated pixels. White padding aligns the display and never changes a nonblank output. All exact answers and both-correct pairs fail.




Fig. 7 | A whole-image mixture improves pixel fit but fails the question-dependent writing test. a, Conditional image law and inference boundary. One latent expert couples all pixels; experts are context-dependent neural functions. **b**, All-development answer/termination-pixel NLL after matched-budget adaptation. **c**, Strict-raster and aligned foreground F1 on normal and blank-question prompts. **d**, First two fixed primary references and raw outputs, with white display padding only. No nonblank pixel is repaired or removed. Parameter counts and output computation differ between arms; both use externally pretrained weights.




Fig. 8 | Question use and reference compatibility do not establish correct free writing. a, Strict-raster F1 on the fixed 256 primary questions and their blank-question controls. Bars show means. **b**, Paired differences with 95% intervals from 2,000 article resamples. The assignment arm scores lower than control despite positive question effects in both. **c**, First two fixed primary references and unmodified generated answers. White padding aligns the display; no nonblank output pixel is removed or repaired. Strict raster agreement does not credit every readable alternative form.




Fig. 9 | Faithful supplied-code writing does not establish answer selection. a, Foreground F1 for four matched fitting arms on 64 training blocks. The pixel condition is an answer-supplying control. **b**, Direct and fixed-codec reconstruction on the same 128 reused-development blocks, with their shuffled-condition controls. Training histories differ; this is not a matched efficiency comparison. **c,d**, The first two fixed fitting and development rows, with original source pixels and unmodified reconstructions. No row is chosen by quality, cropped or repaired.




Fig. 10 | **Question dependence persists when accurate answer writing fails. a**, Chinese foreground F1 on 128 fixed development questions with full and matched question-blank prompts. The paired difference uses 2,000 bootstrap draws of 64 source articles. **b**, Exact full answers, both-correct question pairs and learned stopping. The original answer-quality gates fail, although question dependence and stopping pass. **c**, Complete reference and unmodified generated streams for the first two fixed Chinese cases. Images retain their physical width and aspect ratio; no nonblank pixel is removed or repaired. These are reused development data.




Fig. 11 | Historical forms through the fixed glyph codec. a, Exact reconstruction fraction and mean foreground F_1 for the 27 single-tile images and five tall bronze crops. Group sizes are in parentheses. **b**, The same source SVG, B12643, rasterized at three resolutions. It is the sparsest input among the 27 single-tile images. **c**, B12642 before and after decoding four 32×32 tiles. It had the lowest foreground F_1 of the five tall crops. All panels use supplied historical images. The source identities and measurements are recorded in the archived evaluation receipt.




Fig. 12 | Complete-answer performance across the compact full-sequence fit. a, Complete exact QA answers among 32 questions at five fixed checkpoints. **b**, Both different questions correct within sixteen passage groups. The native-text reference ran on CPU and is shown for task quality. Its displayed intervals resample whole passage groups. Every visual complete-answer interval is [0, 0], which does not imply zero population success. **c**, Predicted stops and budget-limited streams for 44 normal inputs. Blank responses are included among stops. All 372 generated pages were retained. Readability judgments come from one model reviewer without independent human adjudication.


Fixed QA question A: raw outputs

Visible input: last three rows; the complete source PNG is retained in the evidence

。下图显示英格兰48个名誉郡的分布情况。东萨塞克斯东北与根德郡相邻，南临英伦海峡，西与西萨塞克斯郡相邻，北与舒梨郡相邻。　問題：东萨塞克斯管辖哪些区域？　回答：

Update 0　0 glyphs　predicted stop (blank output)


Update 1,956　60 glyphs　predicted stop



Update 4,049　11 glyphs　predicted stop



Update 6,152　70 glyphs　predicted stop



Update 8,172　126 glyphs　predicted stop



The first QA pair and first book prefix were fixed before fitting. All five outputs are shown.
Original answer PNGs are embedded without cropping, reconstruction, OCR replacement or repair.

Fig. 13 | Raw writing for the first fixed QA question. The input preview shows its last three rows; the complete input is retained in the evidence. All five original answer PNGs are shown, including the blank initial response. Labels give actual update, emitted glyph count and predicted stop or budget status. The case was selected before fitting. No answer pixels were cropped, reconstructed, replaced by OCR or repaired. Recognizable fragments do not establish a readable complete answer.

Fixed QA question B: raw outputs


Visible input: last three rows; the complete source PNG is retained in the evidence

。下图显示英格兰48个名誉郡的分布情况。东萨塞克斯东北与根德郡相邻，南临英伦海峡，西与西萨塞克斯郡相邻，北与舒梨郡相邻。 問題：东萨塞克斯在哪里？ 回答：

Update 0 21 glyphs predicted stop




Update 1,956 60 glyphs predicted stop



Update 4,049 11 glyphs predicted stop




Update 6,152 97 glyphs predicted stop



。

Update 8,172 128 glyphs generation budget reached



The first QA pair and first book prefix were fixed before fitting. All five outputs are shown.
Original answer PNGs are embedded without cropping, reconstruction, OCR replacement or repair.

Fig. 14 | Raw writing for a different question about the same passage. The second member of the first fixed QA pair changes the question while retaining the passage. All five original answer PNGs and termination labels are shown. The input preview contains its last three rows, with the complete input preserved separately. Similar output prefixes are visible across the two questions. This display supplies the registered examples, without selecting successes or repairing ambiguous marks.

Fixed book continuation: raw outputs

Visible input: last three rows; the complete source PNG is retained in the evidence


，奈何？」行者道：「莫成是丫頭的頭，和尚的身子？弄的這等不男不女，卻怎生是好？你可佈起罡來。」他就吹他一口仙氣，果然即時把身子變過，與那孩兒一般。

Update 0 **0 glyphs** **predicted stop (blank output)**

Update 1,956 **0 glyphs** **predicted stop (blank output)**

Update 4,049 **0 glyphs** **predicted stop (blank output)**

Update 6,152 **128 glyphs** **generation budget reached**



Update 8,172 **128 glyphs** **generation budget reached**



The first QA pair and first book prefix were fixed before fitting. All five outputs are shown.
Original answer PNGs are embedded without cropping, reconstruction, OCR replacement or repair.

Fig. 15 | Raw writing for the first fixed book continuation. The preview contains the last three rows of the visible prefix. All five original outputs are retained, including the three early blank responses. Later nonblank writing does not establish readable coherent continuation. The complete input, original pixel streams, source hashes and all endpoint controls remain in the evidence.




Fig. 16 | The wider writer preserves the complete-answer failure. a,b, Complete exact QA and both-correct passage pairs at all five fixed checkpoints. The two visual curves overlap at zero. The same native-text CPU reference is shown for task quality. Constant group-bootstrap observations give [0, 0] intervals, without establishing zero population success. **c**, Predicted stops and budget-limited streams in all 44 normal inputs per model/checkpoint. Blanks remain included. Both fits retain all 372 outputs; each review has one model reviewer with prior dataset familiarity and no independent human adjudication.




Fig. 17 | Frozen-weight writing with explicit reference supplies. a,b, Aggregate foreground F1 against the 122 training and 131 development target glyphs. Every writer arm receives reference output lengths. History and update counts vary as labeled. Native history is an explicit source-embedding diagnostic bypass, not deployed image inference. Both models fail the first target span before emitted feedback. Codec fidelity and the supplied-reference measurements are separate from autonomous language accuracy. These selected diagnostics have no generalization interval.




Fig. 18 | Reader alignment and unrepaired diagnostic outputs. a,b, Native-position-weighted achieved relative squared error and the best affine-family error floor for each trained head. The floor relaxes preceding image-network constraints and is not a language bound. **c**, The first registered development QA example, showing original reference, codec and writer pixels at exact nearest-neighbour enlargement. The deterministic display rule was added during analysis, not preregistered. Reference supplies and incorrect glyphs remain visible. No OCR replacement or output repair was applied.




Fig. 19 | **Proportional prompts increase exact answers but lose a correct pair. a–c**, Complete exact QA, both-correct question pairs and whole-response readability on the same 32 questions. Input presentation changes with weights, full passage content and actual-pixel output feedback fixed. Counts retain every registered case. The displayed pointwise difference intervals resample sixteen whole passage groups; both include zero. **d**, Predicted stops and caps for the 32 normal QA inputs. Neither layout has an empty normal answer. **e**, Complete original outputs for the lost area answer, retained location and a newly exact quantity answer. These three matched examples were chosen retrospectively after complete scoring. Each pair is fitted at a common physical scale with no image crop, stroke reconstruction or OCR replacement. Opaque readings come from one model reviewer with prior cohort familiarity and no independent human adjudication. The registered retention rule fails, and no new training is performed.




Fig. 20 | Retained answer access and physical support do not ensure glyph language. a,b, Complete strict QA and both-correct pairs for the external native decoder and original glyph actor. Native source disables contextual adapter outputs; it is not a separately evaluated image-output model. All original questions remain. Native source-unit and glyph budgets use different units. **c**, Mean foreground F1 of the first image against its canonical tile. The supplied-image encoder/decoder receives the answer. First-pixel agreement does not grade character identity, meaning or complete-answer quality. **d**, Strict native/glyph outcome groups for the 32 proportional cases. Native-only includes six uncertain glyph readings and one alias omission; glyph-only includes native wording/punctuation differences. **e**, Twelve original first-tile excerpts for three retrospectively selected cases: early damage, an exact first image with a later alias omission, and a different answer prefix. Tiles retain original pixels at a common scale, without stroke repair. All 32 labelled first-image comparisons and 192 complete original streams remain in the evidence. There is one model reviewer with prior cohort familiarity and no independent human adjudication. No new ILM generation or training is performed by these controls.