

Retinal Flow Language Models: Read–Predict–Write–Reread in Continuous Image Space

Imagized Language Model Project

August 2026

Abstract

Most language models represent language through symbolic tokens and treat visible writing as an auxiliary modality. We study a stricter object: an independent model whose inputs, state supervision, probability model, and primary outputs are images of writing. We introduce the Retinal Flow Language Model (RFLM), a causal model that reads ordered 32×32 image fixations through a continuous retina, integrates them in a recurrent visual field, scores arbitrary candidate images with an energy function, writes the next fixation with conditional pixel-space rectified flow, and rereads its own generated ink. The 11.69M parameter implementation contains no tokenizer, Unicode IDs, OCR transcript, character output table, discrete visual codebook, or external language-model call. V6 adds training on short image trajectories sampled by the deployed writer and peaks at 2.576 GiB on one RTX 4090. On a frozen 512-character, four-view Chinese benchmark, full-context top-1 improves from 0.91% to 1.20% and a matched 32-cell rollout improves its late-to-early ink ratio from 0.483 to 1.168. However, full context remains below last-only (1.69%), unigram (1.86%), and bigram (13.58%) baselines; generated context signal falls from +0.0211 to +0.0077 and the output remains unreadable. We therefore reject V6 as a language model while retaining its image-only boundary and measured stability gain. The result motivates an explicit full-history advantage objective and differentiable identity learning through sampled image endpoints.

1 Motivation

Human readers do not see byte-pair tokens. They see pages, lines, strokes, spacing, damage, font variation, and script-specific visual forms. Current language models are extremely capable, but their central representation is normally a sequence of text tokens. Multimodal models accept images, and modern APIs also expose image-generation endpoints. For example, OpenAI documents APIs for processing images as input and generating images as output, and Google’s Gemini API documentation describes image generation from text and image prompts [4, 5, 6]. These systems are important baselines, but they do not by themselves define a language model whose primary language substrate is the visible page.

The Imagized Language Model (ILM) goal is different:

image input $\rightarrow$ visual language state $\rightarrow$ image output.

The output should itself be a readable answer image. For a query such as “explain the evolution of character yan”, the system should produce a page containing modern explanatory writing, classical-style Chinese, and oracle, bronze, seal, and modern forms. Typed text can still be accepted by a user interface, but it is rasterized into an image prompt before entering the core model. Conversely, the model’s answer is a page image first; OCR or transcription is an optional downstream extraction step.




Figure 1: Image-native language modeling concept figure generated with an AgInTi background and overlaid with real local ziyuan glyph exemplars for YAN (U+8A00). The answer is a rendered image containing both modern explanation and historical forms.

2 Prior Art and Gap

OCR-free document models such as Donut and screenshot parsing models such as Pix2Struct show that document images can be understood without an explicit OCR pipeline. PIXEL reconstructs masked rendered-text patches and demonstrates cross-script visual transfer [10]; PIXAR is a genuinely generative pixel-space autoregressive language model and identifies noisy maximum-likelihood text images as a central difficulty [11]; PixelGPT studies autoregressive visual and textual pretraining [12]. These are the closest model-level precedents. Token-free language models such as CANINE, ByT5, and MEGABYTE remove subwords but retain symbolic bytes or characters. Discrete diffusion language models show that generation need not be left-to-right, but usually retain a linguistic vocabulary.

I-JEPA shows that predicting target image representations from visual context can learn semantic visual fields without reconstructing every pixel [24]. Flow matching trains continuous generative paths by vector-field regression and supports efficient numerical sampling [23]. Human reading is also sequential and foveated: Chinese readers make saccades and can use both character- and word-related targeting cues [28]. These observations motivate RFLM, but they do not imply biological equivalence.

The remaining gap is not simply “pixels instead of tokens.” It is a system whose predictive random variables are continuous writing images, whose memory is learned from ordered visual observations, whose writer produces new pixels, and whose own output distribution is present during evaluation. Historical evidence adds a separate constraint: synthesized marks must never be presented as attested source glyphs.

Retinal Flow Language Model

Read visible fixations, predict a visual distribution, write ink, then read the model's own ink.




Figure 2: The implemented Retinal Flow Language Model. Training joins visual next-state energy, conditional rectified flow, a write–read cycle, and V6 model-induced visual rollouts. Autonomous inference samples candidate ink images, rereads them, selects by visual energy, and feeds the selected pixels back.

3 Architecture

Figure 2 gives the strict visual contract. For fixation images $x_t \in [0, 1]^{H \times W}$, RFLM factors a visual sequence as

$$p_{\Theta}(x_{1:T}) = p(x_1) \prod_{t=1}^{T-1} p_{\Theta}(x_{t+1} | x_{\leq t}).$$

The random variables are continuous image fields rather than entries in a linguistic or visual vocabulary.

Foveal retina. A convolutional reader maps each 32×32 image to a normalized 192-dimensional visual state:

$$z_t = R_{\theta}(x_t) / \|R_{\theta}(x_t)\|_2.$$

Independent font renderings are aligned with visual contrastive, invariance, and variance objectives. The target retina $R_{\bar{\theta}}$ is an exponential moving average of the online retina. Font coverage is checked from font cmap tables so missing-glyph boxes cannot become a spurious class.

Recurrent visual field and energy. A three-layer GRU integrates the fixation history,

$$h_t = G_{\phi}(h_{t-1}, z_t), \quad h_t \in \mathbb{R}^{384}.$$

An energy function scores any candidate image c_j after rereading it:

$$s_{t,j} = E_\psi(h_t, z_t, R_{\bar{\theta}}(c_j)).$$

Multi-positive visual NCE admits multiple near-identical image views as valid targets. Unlike a softmax language head, this energy is not tied to a finite character inventory.

Conditional ink flow. For clean target x_{t+1} , noise ϵ , and $\tau \in [0, 1]$, define

$$y_\tau = (1 - \tau)x_{t+1} + \tau\epsilon, \quad u_\tau = \epsilon - x_{t+1}.$$

The pixel writer predicts the path velocity

$$\hat{u}_\omega = F_\omega(y_\tau, \tau, h_t, z_t), \quad \mathcal{L}_{\text{flow}} = \|\hat{u}_\omega - u_\tau\|_2^2.$$

Training emphasizes high-noise times, where target pixels cannot simply be copied, and weights sparse strokes and the predicted clean endpoint.

Write-read cycle. The one-step endpoint $\hat{x}_0 = y_\tau - \tau\hat{u}_\omega$ is reread through the frozen target retina. A visual NCE cycle objective aligns it to independent target renderings:

$$\mathcal{L}_{\text{cycle}} = \text{NCE}\left(R_{\bar{\theta}}(\hat{x}_0), R_{\bar{\theta}}(x_{t+1}^{(1)}), R_{\bar{\theta}}(x_{t+1}^{(2)})\right).$$

The complete loss combines flow, energy, cross-render invariance, retina contrast, endpoint, stroke, and cycle terms. At inference, the writer samples a candidate set $\mathcal{C}_t$ and selects

$$\hat{x}_{t+1} = \arg \max_{c \in \mathcal{C}_t} E_\psi(h_t, z_t, R_{\bar{\theta}}(c)).$$

The selected pixels become the next observation. This closes the visual loop and turns autonomous stability into a mandatory model property rather than a post-processing concern.

Model-induced visual rollout. V6 invokes the same sampler and energy reranker during training. From a clean prefix it generates two short-flow candidates, selects and detaches one bitmap, rereads it with the online retina, and advances the recurrent state. For two rollout steps it minimizes

$$\mathcal{L}_{\text{roll}} = 0.15\mathcal{L}_{\text{state}} + 0.35\mathcal{L}_{\text{energy}}^{\text{roll}} + 0.30\mathcal{L}_{\text{recovery}}.$$

The terms align clean and induced recurrent states, predict the real next image from the induced state, and recover clean next pixels after generated feedback. All targets remain continuous image fields. Candidate selection is stop-gradient, which bounds memory while exposing the trainable state and writer to deployed pixels.

4 Data

The project already has a strong historical Chinese glyph source outside the tracked repo. A local snapshot at `/home/lachlan/ProjectsLFS/incoder/data/historic` contains:

Item	Count
Characters	9,055
Glyph records	84,642
Oracle	32,216
Bronze	23,500
Liushutong	21,923
Seal	6,996

This supports future evidence-bearing historical answer pages but was not used as a character-label channel in the RFLM run. The language trajectory corpus is a 7,017-record manifest built from 16 public-domain Chinese Wikisource book packages. The contribution layer is recorded as CC BY-SA, and the manifest stores source artifacts and rights. Strings exist only in the offline manifest and renderer; model batches contain image tensors.

Eight Noto Sans/Serif CJK fonts provide independent visual views. The run stores the exact font paths, byte counts, and SHA-256 hashes in checkpoints and receipts. Cmap intersection filtering leaves 8,282 supported visible characters; 107 unsupported unique forms account for only 0.0074% of visible corpus instances and are skipped instead of rendered as missing-glyph boxes.

5 Training Objectives

Each 48-fixation page supplies eight sampled causal positions, making the language objective denser than one endpoint per page. The complete training loss is

$$\mathcal{L} = \lambda_f \mathcal{L}_{\text{flow}} + \lambda_e \mathcal{L}_{\text{energy}} + \lambda_r \mathcal{L}_{\text{retina}} + \lambda_v \mathcal{L}_{\text{view}} + \lambda_p \mathcal{L}_{\text{endpoint}} + \lambda_s \mathcal{L}_{\text{stroke}} + \lambda_c \mathcal{L}_{\text{cycle}} + \rho(t) \mathcal{L}_{\text{roll}}.$$

The energy term uses 512 cross-render candidate views per batch in the final run. Visual duplicate positives are discovered by image similarity rather than labels. The view term aligns independent renderings in both retinal and candidate-projection spaces. Endpoint and stroke terms improve sparse-ink geometry. The cycle term is weighted toward high-noise examples, where a writer must use recurrent context rather than visible target pixels.

For V6, $\rho(t)$ ramps from zero to one over 400 updates. A rollout subset of eight sequences uses two generated steps, two candidates, and two flow steps per candidate. This follows the distribution-shift lesson of scheduled sampling and DAgger [26, 25]; it remains image-only because the visited states, selected observations, and recovery targets are pixels and continuous visual fields. The final rollout state cosine reaches 0.961, but selected-image target cosine is only 0.103. This distinction predicts the measured outcome: state recovery becomes robust while sampled visual identity remains weak.

6 Image-First Training and Inference

Figure 3 makes the training contract explicit. Typed corpora are rendered into page images; scanned books and manuscripts are cropped and tiled; historical glyph files become glyph tiles; and marks that are missing from font tables remain valid image patches. Metadata such as crop boxes and stage labels may remain in manifests, but the model path should learn from visual latents. OCR is useful as a readability critic, not as the hidden language channel.

Figure 4 shows the user-facing path. A typed prompt is converted into a visual prompt canvas, and an uploaded image is normalized into the same visual space. The model returns a page-like

Training ILM-V: Language as Visual Corpus

Every source is converted into page/glyph images. The model learns to predict and generate visual latents, not BPE or word tokens.




Figure 3: Training pipeline for ILM-V. Rendered text corpora, scanned pages, historical glyph files, and unencoded marks are all converted into visual canvases. The training target is visual latent prediction and image generation, not BPE-token prediction.

image containing modern language and historical glyph regions. A later OCR/transcoder can attach a searchable text layer for English, Chinese, or Unicode-representable spans; ancient or unencoded glyphs remain image regions with coordinates and provenance.

The formal contract is:

$$\begin{aligned}
 r_\alpha(\text{text prompt}) &\rightarrow x_{\text{prompt}}, \\
 g_\beta(\text{uploaded page or glyph}) &\rightarrow x_{\text{prompt}}, \\
 f_\theta(x_{\text{prompt}}, x_{\text{context}}) &\rightarrow y_{\text{page}}, \\
 o_\psi(y_{\text{page}}) &\rightarrow \text{optional text layer} + \text{glyph-region metadata}.
 \end{aligned}$$

Here r_α is only a UI rasterizer, not the language model itself. The core model f_θ maps visual inputs to a rendered page image y_{page} . The optional reader o_ψ may recover Unicode text where possible, but unencoded historical forms remain valid image regions.

A useful answer canvas should resemble a page excerpt from a book or corpus:

- a title region rendered as text image,
- one or more modern-language paragraphs, for example English and Chinese,
- a classical-style line or quotation when appropriate,

Inference ILM-V: Chat-Like UI, Image-First Output

Typed text and uploaded images are both turned into visual prompt canvases. The model returns a rendered page image first.




Figure 4: Inference pipeline for ILM-V. A chat-like interface may accept typed text or uploaded images, but typed text is first rasterized into a prompt image. The primary output is a rendered page image. OCR or transcoding is optional and only applies to output regions that exist in computer codecs.

- glyph panels for forms that may not exist in computer fonts,
- a provenance strip with source IDs or nearest retrieved exemplars.

This schema is intentionally different from “text answer plus illustrations”. The generated page image is the primary output object, and the text layer is secondary.

7 3090-Friendly Curriculum

Figure 5 records the original page-model schedule. Measurements now support a different order:

1. Learn a cross-font foveal visual alphabet and audit missing-glyph coverage.
2. Train recurrent visual energy and conditional ink flow jointly on dense causal positions.
3. Reread generated endpoints during training and evaluate on a fixed external visual bank.
4. Train on autonomous model-induced visual trajectories; V6 completes this step and stabilizes ink but remains unreadable.
5. Require full history to beat a reset last-fixation state and train identity through differentiable sampled endpoints.

3090-Friendly Training Curriculum




Figure 5: A staged curriculum that fits one or two RTX 3090 GPUs by starting with glyph tiles and latent generation before scaling to page-level image language modeling.

6. Add a slow line/page state only after full history improves over the last-fixation ablation.
7. Add provenance-gated historical panels and instruction images only after readable autonomous continuation.
8. Scale width and corpus size only after the fixed language and stability gates pass.

The complete 11.69M model is deliberately small enough for one 24 GiB RTX 4090. Its measured 2.576 GiB V6 training peak leaves room for longer rollouts and a slow page state. This is capacity headroom, not an efficiency victory: quality is currently below a symbolic bigram, so “more efficient than an LLM” remains an unsupported hypothesis.

8 Target Demonstration

The first demo should answer a rendered visual prompt such as: “Explain the evolution of the Chinese character yan.” The target answer image should contain:

- a title and concise modern explanation,
- English and Chinese paragraphs rendered as page text,
- a classical-style line such as “yan is the visible trace of speech”,
- a historical timeline with real oracle, bronze, seal, and modern glyph exemplars,
- stage labels and citations as rendered image text.

Example Output: Evolution of Chinese Character Zhong

A target answer is itself an image: explanation plus historical forms.



Figure uses local hanziyuan-derived glyph files when available; generation targets should retrieve/cite real exemplars.

Figure 6: Target output style for a glyph-evolution question. The answer is not merely text: it is a readable image with historical visual forms. The example uses local hanziyuan-derived glyph files when available.

The existing Zhong figure in Figure 6 is a compact stage-timeline example; the Yan figures in Figures 1 and 4 show the fuller answer-page style. Together they test whether the model can combine language understanding, visual page composition, and historical script generation.

9 AgInTi Artifact Loop


The figure brief for AgInTi-style refinement is stored in the local AgInTi prompts subfolder. The current paper uses scripted PNG generation to keep the artifact reproducible.

10 Evaluation

The model should be evaluated as both a language model and a visual generator:

- Fixed-bank top-1, top-5, and reciprocal rank for full context and a last-fixation ablation.
- Random-weight, chance, unigram, and symbolic bigram baselines on identical contexts.
- Cross-font retina-oracle retrieval, separated from recurrent language prediction.
- Generated-image target similarity, pixel F1, ink occupancy, variance, and energy-reranked hit rate.
- Autonomous rollout length, throughput, VRAM, and blinded human readability.
- Student-boundary audit for token IDs, Unicode IDs, OCR, codebooks, labels, and external models.
- Later historical tasks: glyph-stage accuracy, attested-source provenance, and explicit synthetic-form labeling.

AgInTi-Assisted Research Artifact Loop



Why scripted PNGs now?

They are reproducible, editable, and compile cleanly in the paper while leaving room for later AgInTi/image-model refinement

Figure 7: AgInTi-assisted artifact loop. The current figures are deterministic scripted PNGs so the paper is reproducible; the figure brief can later be sent to an interactive AgInTi/image agent for visual refinement.

System	Measured signal	Interpretation
Whole-page flow	velocity MSE 0.851	Unreadable page texture; negative baseline
Global visual memory	top-1 2.23% over 2,016	Above random, but 0/16 historical paraphrases
Causal InkStream	validation ink F1 0.639	Autonomous repeated-grey collapse; negative baseline
RFLM V5 retina oracle	top-1 97.65%	Strong cross-font visual alphabet
RFLM V5 recurrent state	top-1 0.91%	Below last-only 1.36%, unigram 1.86%, and bigram 13.58%
RFLM V6 recurrent state	top-1 1.20%	Improved, but below last-only 1.69% and both language baselines
RFLM V6 pixel writer	context gain +0.0077	Positive but weaker than V5's +0.0211
RFLM V6 autonomous loop	ink ratio 1.168	Stable character-scale marks remain unreadable

The fixed evaluation contains 512 common Han candidates with four independent font views and 2,423 eligible held-out contexts. V5 and V6 use the identical bank SHA-256. V6 raises full-context top-1 from 0.908% to 1.197% and top-5 from 2.229% to 3.219%, while the retina oracle rises from 97.648% to 98.184%. Full context nevertheless remains below V6 last-only (1.692%), unigram (1.857%), and symbolic bigram (13.578%). The formal acceptance result remains false. The retina oracle cannot be cited as language accuracy.


The next checkpoint is accepted only if full context beats random, last-fixation, unigram, and bigram baselines; generated context cosine gain exceeds 0.02 and the random branch by 0.01 on

Closed-loop visual trajectory training: what changed

Matched 32-cell autonomous generation; same prompt, seed, sampler, and 11.69M-parameter model

V5 Clean-prefix training

Ink thins under its own visual feedback



Rendered prompt followed by 32 model-generated image cells

Late / early ink

0.483

Sparse cells

37.5%

Frozen-bank top-1

0.908%

Generated context signal

+0.0211

V6 Model-induced rollout training

Ink survives, but the writing remains unreadable



Rendered prompt followed by 32 model-generated image cells

Late / early ink

1.168

Sparse cells

18.8%

Frozen-bank top-1

1.197%

Generated context signal

+0.0077

Measured verdict closed-loop stability improved; contextual language and readable generation did not

Frozen glyph bank SHA-256 543987ddd754135cff34dbee0f6f91ce1971741d0807754c65650031121181c4

Figure 8: Matched autonomous evidence for V5 and V6. The prompt, seed, sampler, model size, and 32-cell horizon are fixed. Model-induced rollout training prevents the earlier loss of ink and halves the sparse-cell fraction, but neither continuation is readable and generated target signal weakens.

held-out fonts; and a 32-cell autonomous continuation remains readable. Its next objective explicitly requires the real next image to score higher under a full visual prefix than under a reset last-fixation state,

$$\mathcal{L}_{\text{ctx}} = \max(0, m - s(y | h_{\text{full}}) + s(y | h_{\text{last}})),$$

while a truncated differentiable flow sample receives visual identity NCE. A full-state NCE term prevents the margin from being satisfied only by degrading the ablation. V6 rollout losses remain as stability regularizers. This direction is also consistent with measured error accumulation in iterative diffusion chains [27].

11 Conclusion

The experiments show that merely replacing tokens with pixels is insufficient. A page flow can learn paper statistics, a causal writer can learn local ink, and a retina can learn character identity without acquiring language dynamics. RFLM contributes a stricter testable paradigm: ordered continuous visual reading, recurrent image-state prediction, direct conditional ink flow, and rereading under autonomous feedback. V6 further trains on the exact image states produced by its deployed writer. This intervention materially improves autonomous ink stability and modestly improves frozen-bank retrieval on one consumer GPU, but it does not create readable language or useful long context. The result falsifies the claim that exposure-bias correction alone is the core solution. The next test aligns the training loss with contextual advantage and the identity of actually sampled pixels. Historical etymology answers and broad instruction following remain downstream goals, not present capabilities, and no Qwen-8B parity or efficiency claim is warranted.

References

- [1] Brown et al. Language Models are Few-Shot Learners. <https://arxiv.org/abs/2005.14165>
- [2] OpenAI. GPT-4 Technical Report. <https://arxiv.org/abs/2303.08774>
- [3] OpenAI. GPT-4o API model documentation. <https://developers.openai.com/api/docs/models/gpt-4o>
- [4] OpenAI. Images and Vision API documentation. <https://platform.openai.com/docs/guides/images-vision>
- [5] OpenAI. Image generation guide. <https://platform.openai.com/docs/guides/image-generation>
- [6] Google. Gemini API image generation documentation. <https://ai.google.dev/gemini-api/docs/image-generation>
- [7] Meta AI. The Llama 3 Herd of Models. <https://arxiv.org/abs/2407.21783>
- [8] Kim et al. OCR-free Document Understanding Transformer. <https://arxiv.org/abs/2111.15664>
- [9] Lee et al. Pix2Struct: Screenshot Parsing as Pretraining for Visual Language Understanding. <https://arxiv.org/abs/2210.03347>
- [10] Rust et al. Language Modelling with Pixels. <https://arxiv.org/abs/2207.06991>
- [11] Tai et al. PIXAR: Auto-Regressive Language Modeling in Pixel Space. <https://arxiv.org/abs/2401.03321>
- [12] Chai et al. Autoregressive Pre-Training on Pixels and Texts. <https://arxiv.org/abs/2404.10710>
- [13] Clark et al. CANINE: Pre-training an Efficient Tokenization-Free Encoder. <https://arxiv.org/abs/2103.06874>
- [14] Xue et al. ByT5: Towards a Token-Free Future. <https://arxiv.org/abs/2105.13626>
- [15] Yu et al. MEGABYTE: Predicting Million-byte Sequences with Multiscale Transformers. <https://arxiv.org/abs/2305.07185>
- [16] Austin et al. Structured Denoising Diffusion Models in Discrete State-Spaces. <https://arxiv.org/abs/2107.03006>
- [17] Li et al. Diffusion-LM Improves Controllable Text Generation. <https://arxiv.org/abs/2205.14217>
- [18] Lou et al. Discrete Diffusion Modeling by Estimating the Ratios of the Data Distribution. <https://arxiv.org/abs/2310.16834>
- [19] Nie et al. Large Language Diffusion Models. <https://arxiv.org/abs/2502.09992>
- [20] Chang et al. MaskGIT: Masked Generative Image Transformer. <https://arxiv.org/abs/2202.04200>

- [21] Rombach et al. High-Resolution Image Synthesis with Latent Diffusion Models. <https://arxiv.org/abs/2112.10752>
- [22] Peebles and Xie. Scalable Diffusion Models with Transformers. <https://arxiv.org/abs/2212.09748>
- [23] Lipman et al. Flow Matching for Generative Modeling. <https://arxiv.org/abs/2210.02747>
- [24] Assran et al. Self-Supervised Learning from Images with a Joint-Embedding Predictive Architecture. <https://arxiv.org/abs/2301.08243>
- [25] Ross, Gordon, and Bagnell. A Reduction of Imitation Learning and Structured Prediction to No-Regret Online Learning. <https://proceedings.mlr.press/v15/ross11a.html>
- [26] Bengio et al. Scheduled Sampling for Sequence Prediction with Recurrent Neural Networks. https://papers.nips.cc/paper_files/paper/2015/hash/e995f98d56967d946471af29d7bf99f1-Abstract.html
- [27] Ning et al. Input Perturbation Reduces Exposure Bias in Diffusion Models. <https://proceedings.mlr.press/v202/ning23a.html>
- [28] Yan et al. Eye movement guidance in Chinese reading: Is there a preferred viewing location? *Vision Research*, 51(10), 2011. <https://doi.org/10.1016/j.visres.2011.03.004>