Conditional generation of visible language

a Training

60 visible glyph images
Frozen causal reader

→

Continuous visual history
384 state + 1024 image field

History conditions every residual scale

Four noisy future cells
Independent or shared noise levels

→

Conditional strip denoiser
FiLM and cell attention

→

Velocity and visual losses
5.90M trainable parameters

b Inference

Noise and visible history

→


32-level reverse process

→

Four output images
Append pixels to next context

Source: V53 frozen protocol, implementation and locked audit. Schematic objects are editable.

Direct block generation under paired visual histories



256 prefixes, one primary sample each, four output cells
Ordered block identity 0.586%, shuffled 0.488%, zero condition 0.195%

Source: locked V53 development report. Native chart includes its editable evidence workbook.

Unselected output images expose the language error



Fixed first eight audit rows. Pixels are model output, with nearest-neighbour enlargement. No glyph replacement.

Exact raster likelihood preserves a visible copy path

64 writing images
Frozen 16.28M reader

→

Continuous visual state
Hidden384 + image field1024

→

Fixed inverse field
Aligned signed pixel plan

Training: exact Bernoulli image NLL

Earlier target rows
Four-layer row transformer

→

Earlier pixels within row
Strictly masked MADE

→


Aligned logit + residual
Normalized next-image law

25% supplied-image motor exercises; 75% natural predicted conditions. No glyph inventory.

Inference: sample 1,024 causal pixels; append the visible raster to history

2.43M new density parameters; 18.71M total. Supplied-image copying is architectural, not language evidence.

Copying succeeds; autonomous language remains unresolved




Exact-image copying: 256/256 greedy. Autonomous target identity: 4/256 ordered, 3/256 shuffled.

Target NLL: 15.219 ordered; 15.254 shuffled nats/image
Paired advantage 0.0355 nat; source-record bootstrap 95% CI [-0.1014, 0.1693]


V54 locked development audit. Native chart and embedded workbook. Supplied-image controls reveal the answer.

Actual rasters: exact motor copying and failed continuation

Target	Supplied / greedy	Ordered / sample	Shuffled / sample	Ordered / greedy
				

First eight fixed audit rows; nearest-neighbour enlargement. No OCR, image replacement or selected examples.

Matched joint learning: better likelihood, incomplete generation



Exact target NLL: joint 7.026; matched frozen 7.579 nats/image
Paired gain 0.553; 95% source-record interval [0.450, 0.665]

Both arms retain exact supplied-image copying. Joint model passes 6/8 gates; generation remains unqualified.


V55 locked matched audit; 512 NLL targets, 256 single-sample prefixes. Native chart includes its editable workbook.

Raw matched output: exact copying and remaining language errors

Target	Frozen sample	Joint sample	Joint shuffled	Joint greedy	Supplied copy
江	疫	江	江	江	江
歲	亟	亟	亟	，	歲
般	鴿	一	一	一	般
精	追	些	些	，	精
六	四	四	四	三	六
他	路	路	路	不	他
王	用	苯	抂	王	王
物	蒴	恭	恭	人	物

First eight fixed audit rows, no selection. Pixels are actual output; no OCR, evaluator-bank replacement or external inference.

Clear glyphs and correct language are separate tests




Exact known-form gain, joint minus frozen: 10.156 percentage points
95% source-record interval [4.219, 16.240]; 256 saved first samples

The fixed 9,932-image bank is used only for evaluation. No image is repaired or replaced.

Post-result diagnostic; all original qualification decisions remain unchanged. Native chart includes its editable workbook.

Raw-pixel beam search: better immediate choice, repetitive output




2,048 prefixes: beam gain over greedy 3.369 points [2.351, 4.412]; over shuffled 1.758 [0.966, 2.552]
Observed-stream repetition: 0.112%; beam: 25.446%. Rollout gate fails; decoder rejected.

Observed future	Ordered beam	Shuffled beam	Original greedy
不尬的就跑回来了	一个，不是一个，	一个，不不不不不	，不不一，不不不
的女婿。丈人教我	，不是一人，不是	，不不不不不不不	，不不不不不不不

Unselected first two eight-step audit streams. Unchanged V55 weights; no vocabulary or repair. Both controls use highest FP32 precision.

Natural Chinese questions: some binding, inaccurate complete answers



Question-dependent F1 gain: 10.165 points [7.043, 13.371]
Exact answers: 10/256; both questions correct: 1/393 pairs. Four of seven gates pass; model rejected.


Q1 １９４０年８月世宗大学更名成什么？

Q2 邵伯温是在什么时候去世？

Reference 1	Copy	Blank question	No-copy
首尔女子师范学院 高宗绍兴四年（１１３４年）	１９４０年５月，Ｙ月世宗大学” 邵溥、邵博、邵传后》	节居绍圣、利州路转运作）	１９３０年 １３３０年

First two fixed audit rows; actual output images. White means zero emitted cells. All primary copy-arm answer cells use observed prompt images.

Whole observed image answers: better F1, unresolved exact-match gain




25/256 exact answers; matched glyph control 21/256. F1 gain 4.893 points [0.469, 9.047].
Only 4/393 paragraph pairs have both answers correct. Six of seven gates pass; reading rejected.

Prompt pixels → Causal reader → Start / end law → Source image answer

	Retained reference	Actual block answer
Audit row 1	首尔女子师范学院	“世宗学院”
Audit row 2	高宗绍兴四年（1134年）	卒于高宗绍兴四年（1134年）

First two fixed audit rows. Copying preserves selected pixels; it does not certify the meaning of the selected text.

Frozen visual foundation probe: larger pretrained features do not help here




Identical 789,520-parameter heads; 4,000 matched updates each.
Student 24/256 exact; MIXAR 6/256. MIXAR-minus-student F1 −13.752 points [−18.247, −9.094].

MIXAR has different pretraining and native rendering; this probe uses our Noto CJK grid.
External four-H200 pretraining is not one-4090 work. Frozen readout comparison rejected; not a general encoder ranking.

Continuous prompt-image features only. Shared cached release weights; no external inference call or answer annotation enters feature preparation.

Does reading the question first improve evidence selection?



Context first

Passage images X → Question images Q → Answer

Question first

Question images Q → Passage images X → Answer

Question-first minus context-first F1: -3.143 points [-6.544, 0.446].
4/8 registered gates pass; decision: reject_question_first_intervention.

Same checkpoint, data, parameters and training budget. Source pixels only; reused development, not a sealed final test or general language qualification.