

Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7 Wavelets and Multiresolution Processing





FIGURE 7.1
An image and its
local histogram
variations.



Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7

Wavelets and Multiresolution Processing






FIGURE 7.2
(a) An image pyramid. (b) A simple system for creating approximation and prediction residual pyramids.






Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com


Chapter 7 Wavelets and Multiresolution Processing



a
b

FIGURE 7.3

Two image pyramids and their histograms:
(a) an approximation pyramid;
(b) a prediction residual pyramid.




Digital Image Processing, 3rd ed.

Gonzalez & Woods


www.ImageProcessingPlace.com

Chapter 7 Wavelets and Multiresolution Processing



a b
c d
e f

FIGURE 7.11
Some Haar
scaling functions.



Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7 Wavelets and Multiresolution Processing





FIGURE 7.12
The nested
function spaces
spanned by a
scaling function.



Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7 Wavelets and Multiresolution Processing





FIGURE 7.13
The relationship
between scaling
and wavelet
function spaces.




Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com


Chapter 7

Wavelets and Multiresolution Processing



a b
c d
e f

FIGURE 7.14
Haar wavelet
functions in W_0
and W_1 .




Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com


Chapter 7

Wavelets and Multiresolution Processing



a b
c d
e f

FIGURE 7.15
A wavelet series expansion of $y = x^2$ using Haar wavelets.




Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com


Chapter 7

Wavelets and Multiresolution Processing



a b
c d

FIGURE 7.16
The continuous wavelet transform (c and d) and Fourier spectrum (b) of a continuous 1-D function (a).



Chapter 7

Wavelets and Multiresolution Processing







FIGURE 7.17
An FWT analysis bank.

Analysis




Chapter 7 Wavelets and Multiresolution Processing



a
b

FIGURE 7.18

(a) A two-stage or two-scale FWT analysis bank and (b) its frequency splitting characteristics.



Digital Image Processing, 3rd ed.


Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7 Wavelets and Multiresolution Processing

n	$h_{\psi}(n)$
0	$1/\sqrt{2}$
1	$1/\sqrt{2}$

TABLE 7.2
Orthonormal
Haar filter
coefficients for
 $h_{\psi}(n)$.



Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.19 Computing a two-scale fast wavelet transform of sequence $\{1, 4, -3, 0\}$ using Haar scaling and wavelet vectors.



Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.19 Computing a two-scale fast wavelet transform of sequence $\{1, 4, -3, 0\}$ using Haar scaling and wavelet vectors.

These coefficients correspond to neg. n



Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.19 Computing a two-scale fast wavelet transform of sequence $\{1, 4, -3, 0\}$ using Haar scaling and wavelet vectors.

★ Downsample by taking every second element

These coefficients correspond to neg. n



Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.20
The FWT⁻¹
synthesis filter
bank.

Synthesis



Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.21
A two-stage or
two-scale FWT⁻¹
synthesis bank.



Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.22 Computing a two-scale inverse fast wavelet transform of sequence $\{1, 4, -1.5\sqrt{2}, -1.5\sqrt{2}\}$ with Haar scaling and wavelet functions.



Chapter 7

Wavelets and Multiresolution Processing





FIGURE 7.22 Computing a two-scale inverse fast wavelet transform of sequence $\{1, 4, -1.5\sqrt{2}, -1.5\sqrt{2}\}$ with Haar scaling and wavelet functions.

Upsampling by adding a 0 every 2nd element



Digital Image Processing, 3rd ed.

Gonzalez & Woods

www.ImageProcessingPlace.com

Chapter 7 Wavelets and Multiresolution Processing









FIGURE 7.23 Time-frequency tilings for the basis functions associated with (a) sampled data, (b) the FFT, and (c) the FWT. Note that the horizontal strips of equal height rectangles in (c) represent FWT scales.




2D scheme






Chapter 7

Wavelets and Multiresolution Processing



Note that the wavelet components have typically 0 mean value (encode the small variations in the details of the image)



Chapter 7


Wavelets and Multiresolution Processing

Wavelets - so what now?

As we have done image manipulation (filtering, smoothing, in spatial domain, frequency domain, etc.) it is possible to apply the same tools in the wavelets formalism.

1. Apply DWT
2. Perform filtering/operation
3. Apply IDWT

The advantage of wavelets wrt to FFT is the cost ($O(N)$ wavelets, $O(N \log N)$ for FFT)




Chapter 7

Wavelets and Multiresolution Processing

Example:


Picking up edge
information by modifying
the approximation part

Modifying also the
horizontal detail
information



a b
c d

FIGURE 7.27
Modifying a DWT
for edge
detection: (a) and
(c) two-scale
decompositions
with selected
coefficients
deleted; (b) and
(d) the
corresponding
reconstructions.




Chapter 7

Wavelets and Multiresolution Processing

Haar wavelets
converge slowly.

Other families of
wavelets have better
convergence properties




a b
c d
e f
g

FIGURE 7.26
Fourth-order symlets: (a)–(b) decomposition filters; (c)–(d) reconstruction filters; (e) the one-dimensional wavelet; (f) the one-dimensional scaling function; and (g) one of three two-dimensional wavelets, $\psi^V(x, y)$. See Table 7.3 for the values of $h_\psi(n)$ for $0 \leq n \leq 7$.

n	$h_\psi(n)$
0	0.0322
1	-0.0126
2	-0.0992
3	0.2979
4	0.8037
5	0.4976
6	-0.0296
7	-0.0758


TABLE 7.3
Orthonormal fourth-order symlet filter coefficients for $h_\psi(n)$. (Daubechies [1992].)



Chapter 7

Wavelets and Multiresolution Processing

Example of noise removal:
here it is set to zero
the coefficients of
the wavelets
(detail coefficients),
while keeping
the approximation
coefficients



a b
c d
e f

FIGURE 7.28

Modifying a DWT for noise removal: (a) a noisy CT of a human head; (b), (c) and (e) various reconstructions after thresholding the detail coefficients; (d) and (f) the information removed during the reconstruction of (c) and (e). (Original image courtesy Vanderbilt University Medical Center.)