

Assignment 12


Query Optimization

ILARIA BATTISTON - 03723403

MAREVA ZENELAJ - 03736071

1 First exercise

Probability of $0 \leq j \leq 90$ pages being skipped:



Expected distance between two pages $B = 100$, $b = 10$, (10 bits set to 1): computing the distribution of zeros, and the expected number of zeros between two 1s.

$$\bar{B}_b^B = \frac{B - b}{b + 1} = \frac{100 - 10}{10_1} = \frac{90}{11} = 8.18$$

Expected distance between the beginning and the last page to be read:

$$\bar{B}_{tot} = \frac{Bb + b}{b + 1} = \frac{100 \cdot 10 + 10}{11} = \frac{1010}{11} = 91.8$$

Expected distance between the first and the last page

$$\bar{B}_{1-span} = \frac{Bb - B + 2b}{b + 1} = \frac{100 \cdot 10 - 100 + 20}{11} = \frac{920}{11} = 83.6$$

2 Second Exercise

The number of elements for which $R.a \geq 55$ holds true:

$$R.a \geq 55 = R.a > 55 + R.a = 55$$

$$\frac{60-40}{4} = 5$$

5 elements $\implies [55, 60) = 1/4$ of total

0 in the first bucket, 0 in the second, 1 in the third, 2 in the fourth and 0 in the last one. Therefore there are 3 elements.

3 Third exercise

$$R.a = S.b$$

When estimating joins on histograms with non-aligned bucket boundaries, buckets are split, such that boundaries are aligned.

Since it is impossible to evenly split buckets with odd numbers, when in doubt the element is placed in the bucket on the left.

$R.a$	$[0, 10)$	$[10, 20)$	$[20, 40)$	$[40, 50)$	$[50, 60)$	$(60, 80]$	$[80, 100)$
count	1	0	3	2	2	2	0
$S.b$	$[0, 10)$	$[10, 20)$	$[20, 40)$	$[40, 50)$	$[50, 60)$	$(60, 80]$	$[80, 100)$
count	2	4	1	6	1	2	1

$$(R.a = R.b) = \frac{1 \cdot 2 + 4 \cdot 0 + 3 \cdot 1 + 2 \cdot 6 + 2 \cdot 1 + 2 \cdot 2 + 1 \cdot 0}{(1 + 0 + 3 + 2 + 2 + 0) \cdot (2 + 4 + 1 + 6 + 1 + 2 + 1)} = \frac{22}{170} = 0.3$$

Selectivity of $(R \bowtie S) \approx 0.3$, so there are 23 elements satisfying the join criterion.