

Image Features

NGUYEN Hong Thinh

FET-UET-VNU

Ngày 28 tháng 3 năm 2020

Today:

- What is features?
- Global features vs Local Features
- Global features: Color features
- Local features: Image Matching
- HOG feature
- SIFT-BOW method for image classification
- Conclusion


Large volume of image database

Computer
Vision

NGUYEN
Hong Thinh

Content-based Image Retrieval

Given a query image, try to find visually similar images from an image database



Comparing 2 images: challenging problems?


Computer
Vision
NGUYEN
Hong Thinh

- Different size/resolution
- Different viewpoint/pose
- Different light condition
- Occlusion (Che khuất)
- Intra class variation
- Inter class variation

**Không thể so sánh trực tiếp 2 ảnh ⇒ So sánh dựa trên
đặc điểm /đặc trưng trong ảnh
-tiêu chuẩn**

Image features?

- Features (đặc trưng): là tất cả các đặc điểm, đặc trưng có thể sử dụng để phân biệt các đối tượng với nhau (vd color, shape)
 - Features vector: vector chứa thông tin của tất cả đặc trưng của ảnh.




Phân loại đặc trưng ảnh

Computer
Vision
NGUYEN
Hong Thinh


- Global features: One image \Rightarrow 1 feature
- Local features: Block based features: Images = set of blocks \Rightarrow features



Global feature representation



Local feature representation




1 vector

Phân loại đặc trưng ảnh

Computer Vision

NGUYEN
Hong Thinh



Popular features


Computer
Vision
NGUYEN
Hong Thinh

- Global features:
 - Color based features: CH, CM, Corr, CN
 - Shape features
 - GIST features
- Local features:
 - Interesting point detectors
 - Dense sampling
 - Descriptors: SIFT, SUFT, HOG, BRIEF, ORB...
open-cv

Global features: Colors features

Computer Vision
NGUYEN
Hong Thinh

Color histogram



Cam Đen Vàng Đỏ


50. 30. 20 0

35 65 15 0


0 60. 15 25

0 55 10 35

Earth mover's distance



χ^2 distance



Colors based features


- An image maybe a gray (intensity image) or colored image
- Normally, using RGB (8bit = 256 values for R,G,B color) to encode color of image
- R,G,B color channels have high correlations
- ⇒ using other color space
 - YCrCb
 - Lab (Light, Red/Green Value, Blue/Yellow Value)
 - HSV (Hue, Saturation, Values)

Colors based features

Computer
Vision

NGUYEN
Hong Thinh

HSV color space



R=red

G=green


B=blue

HSV is perceptual
system

Hue=H

Saturation=S

Value=V



Colors based features

Computer
Vision

NGUYEN
Hong Thinh

LAB color space



Colors based features

Compute color features?

- Step 1: \Rightarrow Convert RGB to other color space (HSV, LAB...)
- Step 2: Calculate mean, standard deviation, Skewness for each color of images \Rightarrow Color Moment (**CM**) features:
 - Mean: $E_c = \frac{1}{N} \sum_{allpixels} I_{i,j}$, where N is number pixels
 - Std: $\sigma_c = \sqrt{\frac{1}{N} \sum_{allpixels} (I_{i,j} - E)^2}$
 - Skewness: $s_c = \sqrt[3]{\frac{1}{N} \sum_{allpixels} (I_{i,j} - E)^3}$
- RGB image \Rightarrow CM features as:
 $[E_R, E_G, E_B, \sigma_R, \sigma_G, \sigma_B, s_R, s_G, s_B]$

Colors based features

Computer
Vision

NGUYEN
Hong Thinh

Calculate Normalized Color Histogram (**CH**):

- Compute histogram for each color channel (3 bins for R,G, 2 bin for B)
- Or compute histogram: 8 bins for R+G+B, 16 bin for R-G and 2B-R-G
- Concatenate histograms above
- Normalized
- Using histogram intersection distance to compare histogram


Colors based features

Computer
Vision

NGUYEN
Hong Thinh

COLOR MODULE


COLOR SPACE



HISTOGRAM INTERSECTION

[Swain & Ballard 1991]

$$\phi_c(s) = \frac{\sum_{i=1}^N \min(I_s(i), M(i))}{\sum_{i=1}^N I_s(i)}$$



NORMALIZATION

$$\bar{\phi}_c(s) = \frac{\phi_c(s) - \min_{s_i \in S} \phi_c(s_i)}{\max_{s_i \in S} \phi_c(s_i) - \min_{s_i \in S} \phi_c(s_i)}$$


Colors based features

Computer
Vision

NGUYEN
Hong Thinh

Compute color features?

- Too much colors: for example $256R * 256G * 256 B = 16.777.216$ colors
- ⇒ Color Quantizations (Kmean, Meanshift, ColorName)



- ⇒ Histogram on Quantized Image

Examples: Color-based Retrieval

2005




Shape based features

Image=> colors, shape, freq

w1 color +w2 shape + w3 freq

Shape context descriptor [Belongie et al '02]



Count the number of points inside each bin, e.g.:


⋮

Count = 10

Compact representation
of distribution of points
relative to each point

$$h_i(k) = \#\{q \neq p_i : (q - p_i) \in \text{bin}(k)\}.$$


Global features-GIST



Source - http://cybertron.cs.tu-berlin.de/pdcl10/art2real/Art2Real/Image_Descriptor.html

Global features

Computer Vision
NGUYEN Hong Thinh



Limitations?

Computer
Vision

NGUYEN
Hong Thinh

Different images content may have same color histogram



Motivation for using local features



Computer
Vision

NGUYEN
Hong Thinh

- Global representations have major limitations
- Instead, describe and match only local regions
- Increased robustness to
 - Occlusions



- Articulation




- Intra-category variations



Motivation for using local features

Computer
Vision


NGUYEN
Hong Thinh



Slide credit: Bastian Leibe

Local features


(Invariant) Local Features: Image content is transformed into local feature coordinates that are invariant to translation, rotation, scale, and other imaging parameters



Invariance: Geometric Transformations

Computer
Vision

NGUYEN
Hong Thinh




Slide credit: Steve Seitz

- Advantages of invariant local features:

- Locality: features are local, so robust to occlusion and clutter
- Distinctiveness: individual features can be matched to a large database of objects
- Quantity: many features can be generated for even small objects
- Efficiency: close to realtimeme performance
- Extensibility: can easily be extended to wide range of differing feature types, with each adding robustness

Local features


- Feature Detector: Detect interesting point/location in images
 - Dense sampling:** A special detector, sample image by a fix sliding window with fix overlap
- Feature Descriptor: an encoder method, to convert an image block into a vector, with some properties.



Local features

Computer
Vision

NGUYEN
Hong Thinh



Intersting point detector or dense sampling?

Computer
Vision
NGUYEN
Hong Thinh

- To detect intersting regions in image:



- Requirement:

- Region extraction needs to be **repeatable** and **accurate**
 - Invariant to translation, rotation, scale changes
 - Robust or covariant to out-of-plane (\approx affine) transformations
 - Robust to lighting variations, noise, blur, quantization
- Locality**: Features are local, therefore robust to occlusion and clutter.
- Quantity**: We need a sufficient number of regions to cover the object.
- Distinctiveness** : The regions should contain “interesting” structure.
- Efficiency**: Close to real-time performance.

Many Existing Detectors Available

Computer
Vision

NGUYEN
Hong Thinh

- Hessian & Harris [Beaudet '78], [Harris '88]
- Laplacian, DoG [Lindeberg '98], [Lowe '99]
- Harris-/Hessian-Laplace [Mikolajczyk & Schmid '01]
- Harris-/Hessian-Affine [Mikolajczyk & Schmid '04]
- EBR and IBR [Tuytelaars & Van Gool '04]
- MSER [Matas '02]
- Salient Regions [Kadir & Brady '01]
- Others...
- *Those detectors have become a basic building block for many recent applications in Computer Vision.*

Summary: Harris Detector [Harris88]

- Compute second moment matrix (autocorrelation matrix)

$$M(\sigma_I, \sigma_D) = g(\sigma_I) * \begin{bmatrix} I_x^2(\sigma_D) & I_x I_y(\sigma_D) \\ I_x I_y(\sigma_D) & I_y^2(\sigma_D) \end{bmatrix}$$



- Image derivatives
- Square of derivatives

- Gaussian filter $g(\sigma_I)$

4. Cornerness function - two strong eigenvalues

$$\begin{aligned}\theta &= \det[M(\sigma_I, \sigma_D)] - \alpha[\text{trace}(M(\sigma_I, \sigma_D))]^2 \\ &= g(I_x^2)g(I_y^2) - [g(I_x I_y)]^2 - \alpha[g(I_x^2) + g(I_y^2)]^2\end{aligned}$$

5. Perform non-maximum suppression




Slide credit: Krystian Mikolajczyk

Descriptor

Computer
Vision
NGUYEN
Hong Thinh

- We know how to detect points
- Next question:

How to *describe* them for matching?




Point descriptor should be:
1. Invariant
2. Distinctive


SIFT-Description:

SIFT (Scale Invariance Features Transform): Bất biến với scale, rotation and translation

1 block ảnh A \Rightarrow scale, rotate, translate nó, tạo ra block B;
thì SIFT(A) = SIFT(B).




SIFT descriptor formation




- Use the blurred image associated with the keypoint's scale
- Take image gradients over a 16x16 array of locations.
- To become rotation invariant, rotate the gradient directions AND locations by (-keypoint orientation)
 - Now we've cancelled out rotation and have gradients expressed at locations **relative** to keypoint orientation θ
 - We could also have just rotated the whole image by $-\theta$, but that would be slower.

SIFT descriptor formation



- Using precise gradient locations is fragile. We'd like to allow some “slop” in the image, and still produce a very similar descriptor
- Create array of orientation histograms (a 4x4 array is shown)
- Put the rotated gradients into their local orientation histograms
 - A gradients's contribution is divided among the nearby histograms based on distance. If it's halfway between two histogram locations, it gives a half contribution to both.
 - Also, scale down gradient contributions for gradients far from the center
- The SIFT authors found that best results were with 8 orientation bins per histogram, and a 4x4 histogram array.

SIFT descriptor formation




- 8 orientation bins per histogram, and a 4×4 histogram array, yields $8 \times 4 \times 4 = 128$ numbers.
- So a SIFT descriptor is a length 128 vector, which is invariant to rotation (because we rotated the descriptor) and scale (because we worked with the scaled image from DoG)
- We can compare each vector from image A to each vector from image B to find matching keypoints!
 - Euclidean “distance” between descriptor vectors gives a good measure of keypoint similarity

SIFT-Description: Image matching

Computer Vision

NGUYEN
Hong Thinh



SIFT-Description


Computer
Vision

NGUYEN
Hong Thinh

Stitching to create panorama picture




Automatic mosaicing



LAB

Computer
Vision
NGUYEN
Hong Thinh

Create your panorama: (Brown and Lowe: Automatic Panoramic Image Stitching with Invariant Features.)



OpenCV's image stitching algorithm