

Problem Set 3, Answers

Kevin Lacker

May 29, 2020

Problem 1. This is a four-part problem.

1. Let L be the set of leaves of the minimum-height protocol tree for f that give output 1. For each $l \in L$, let M_l be the matrix which is 1 on the input pairs whose path through the protocol tree ends at the leaf l . By the definition of a protocol tree, M_l can also be defined by a set X and Y with:

$$M_l[i, j] = 1 \iff i \in X, j \in Y \quad (1)$$

Thus, there are two possible rows in M_l , either all zeros or 1 precisely on indices in Y . Thus, the rank of M_l is 1, regardless of what field the rank is taken over.

Note that:

$$M_f = \sum_{l \in L} M_l \quad (2)$$

Since rank is subadditive, we can conclude:

$$\text{rank}(M_f) \leq \sum_{l \in L} \text{rank}(M_l) = |L| \leq 2^{D(f)} \quad (3)$$

The last inequality holds since L is a subset of leaves of a tree of height $D(f)$. We can then conclude

$$\log_2(\text{rank}(M_f)) \leq D(f) \quad (4)$$

2. There are 2^n rows of M_f . Consider them as vectors over the field \mathbb{F}_2 , and say the rows span a subspace of dimension d , so $\text{rank}(M_f) = d$. Since the field has size 2, this subspace has exactly 2^d elements in it. Since the rows of M_f are 2^n distinct vectors in this subspace of size 2^d , we have $2^n \leq 2^d$. So $\log_2(n) \leq \log_2(d)$ and by the conclusion of the previous problem, $\log_2(n) \leq D(f)$.
3. TODO
4. TODO