

```
# repeat the first 100 rows of the original dataframe
prediction_data_farc <- df[rep(1, 100), ]

# fill all department columns with 0
dept_cols <- grep("^departamento_", names(prediction_data_farc), value = TRUE)
prediction_data_farc[, dept_cols] <- 0

# fill every other variable, make all values equal to the mean
prediction_data_farc$ln_atparabacrim_cede = mean(df$ln_atparabacrim_cede, na.rm = TRUE)
prediction_data_farc$ref_partic = mean(df$ref_partic, na.rm = TRUE)
prediction_data_farc$share_santos_2_100 = mean(df$share_santos_2_100, na.rm = TRUE)
prediction_data_farc$incidence_multidim_pov_2005_100 = mean(df$incidence_multidim_pov_2005_100, na.rm = TRUE)
prediction_data_farc$lpop = mean(df$lpop, na.rm = TRUE)
prediction_data_farc$indrural2005 = mean(df$indrural2005, na.rm = TRUE)
prediction_data_farc$cultivated100 = mean(df$cultivated100, na.rm = TRUE)
prediction_data_farc$oil = mean(df$oil, na.rm = TRUE)
prediction_data_farc$ln_altitud = mean(df$ln_altitud, na.rm = TRUE)
prediction_data_farc$coberturabrutaeduc = mean(df$coberturabrutaeduc, na.rm = TRUE)

# have FARC attacks variable vary amongst ranges between the min and max values
prediction_data_farc$ln_atfarc_cede <- as.numeric(seq(min(df$ln_atfarc_cede, na.rm = TRUE),
max(df$ln_atfarc_cede, na.rm = TRUE),
length.out = 100))
```