




# OSS-LED SERIES



**OSS-LED-11**  
A & B = 11-1/2"  
C = 3-1/2"  
**OSS-LED-14**  
A & B = 14-1/2"  
C = 4"

**CALCULATED**  
**L70**  
LIFETIME  
**60,000 HRS**

**90+**  
C R I

**11"**

**1200**  
LUMENS

**15**  
WATTS

**14"**

**2200**  
LUMENS

**28**  
WATTS

## APPLICATION:

Hallways/corridors, office buildings, library stacks, schools, and hospitals.

## PRODUCT FEATURES:

- Heavy-gauge metal housing
- Housing suitable for mounting to standard junction box
- Lens is UV stable white acrylic
- Suitable for damp location
- Life tested to ensure light output up to 60,000 hours of operation to L70
- Tested to LM-79 and LM-80 standards

**OPTICS** - The OSS-LED uses a frosted acrylic lens to scatter the light emitted from the LED chips into functional light. The LED offered in the OSS-LED has the highest return on initial investment compared to other standard lighting solutions.

**PERFORMANCE** - The light engines found in the OSS are rated at 90+ CRI and are available in multiple CCTs: 3000K, 4000K and 5000K. Rated and tested to LM-79 and LM-80 standards. The LEDs are also binned to a 3-step MacAdam ellipses to achieve consistent color from fixture to fixture.

**ELECTRICAL** - Powered by high-quality constant-current power LED drivers which are rated for 50 to 60Hz at 120 or 120-277V input, produce less than 20% THD, and have a power factor of .90 to 1.00.

**QUALITY CONTROL** - Every fixture is turned on and rigorously tested by our QC Department before shipping.

**INSTALLATION** - Fixture easily mounts directly over a 4" recessed outlet box, and most standard size junction boxes.

**WARRANTY** - Limited 5 Year Warranty

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications are subject to change without notice.



## Ordering Information: Example: OSS-LED-14-1000L-DIM10-MVOLT-30K

| SERIES                                    | TYPE | FIXTURE SIZE           | LUMENS   | DIMMING                                      | VOLTAGE              | CCT   | CRI | OPTION                              |
|---|------|------------------------|--|--|----------------------|---|-----|-------------------------------------|
| OSS-Oracle<br>LED Surface<br>Mount Square | LED  | 11" - 11"<br>14" - 14" | 11" FIXTURE<br>1200L - (1200 lumens)<br>14" FIXTURE<br>2200L - (2200 lumens) | DIMTR<br>DIM10<br>(Not Available<br>for 11") | MVOLT<br>120<br>347* | 30K - (3000K)<br>40K - (4000K)<br>50K - (5000K) | 90  | USA - Made in America<br>Compliance |

\* Consult  
factory for  
details