

Round Instant Flexilight




The Round Instant Flexilight, 1/2" in diameter and rated at 35,000 hours, is a basic, long-lasting product. Since we only use the highest-quality PVC material along with UV additives, the Round Instant Flexilight can be used in indoor or outdoor applications and can withstand both freezing and scorching weather. Flashing light effects can be created if a controller is used.

The Round Instant Flexilight is very easy to use for a wide variety of design purposes, such as creating meaningful patterns in lighting projects; illuminating the edges of buildings, stairs, and other objects; or simply making a promotional sign.

Number of wire	2
Number of bulb/foot	12
Diameter	1/2"
Shape	Round
Colors available (PVC)	Clear:
	Clear, Green
	Fluorescent Colors:
	Green and Pink
	Pearl Colors:
	White, Red, Yellow, Blue & Green

FLEXIBLE ROPELIGHT

Specifications of Round Instant Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	12V	30'	4'	3.0V 0.07A 0.21W	12	2.52W/foot
	24V	60'	8'	3.0V 0.07A 0.21W	12	2.52W/foot
	110-120V	240'	24'	6.5V 0.07A 0.46W	12	3W/foot

Packages Available

Item Number	Length	Package
ERIF-120-150	150'	/Roll
ERIF-24-150*	150'	/Roll
ERIF-12-150**	150'	/Roll

ERIF

-

120

-

150

-

COLOR

Item No. Voltage Length Specify color

(Available in 150' Rolls only, no custom cut)

NOTE: EACH ROLL INCLUDES; 3pcs ERIFXXX Power Cords, 3pcs F3 Splice Connectors, 3pcs F4 End Caps

Round Instant Flexilight Accessories:

ERIF1-120V	Round Instant Flexilight 6ft. Power Cord w/ Power Connector
ERIF1-24V*	Round Instant Flexilight 6ft. Power Cord w/ Power Connector
ERIF1-12V**	Round Instant Flexilight 6ft. Power Cord w/ Power Connector
F3	Round Instant Flexilight Splice Connector
F4	Round Instant Flexilight End Caps
F5	Round Instant Flexilight Tie Strap
F6	Round Instant Flexilight Mounting Clips
F7	Round Instant Flexilight Suction Cup
F8	Round Instant Flexilight 6ft. Channel
F9	Round Instant Flexilight Easy Splice Connector
F10	Round Instant Flexilight Y-cord
F11	Round Instant Flexilight T-connector
F14	Round Instant Flexilight Splice Connector
F103	Round Instant Flexilight PVC Connector
F22	Round Instant Flexilight PVC T-Connector
F23	Round Instant Flexilight PVC X-Connector

ERIF1



F3



F4



F5



F6



F7



F8



F9



F10



F11



F14



F22



F23



F103



Standard Controller

MODEL	VOLTAGE AVAILABLE	MAX. LENGTH	FUNCTIONS
ERWL-2C-110	120V	150 FT.	Static/Flashing
ERWL-2C-24A*	24V	60 FT.	Static/Flashing
ERWL-2C-12A**	12V	30 FT.	Static/Flashing

(*Requires 24V AC power source)

(**Requires 12V AC power source)

