

Mini Round Instant Flexilight




The Mini Round Instant Flexilight, 3/8" in diameter and rated at 35,000 hours, is becoming the most popular rope light because of its smaller diameter. This design has become possible through a restructuring of wires and light bulbs inside the rope light. Therefore, the quality and life of the product has remained as high as the standard 1/2" rope light.

The exclusive use of the highest-quality PVC material along with UV additives makes this product suitable for both indoor and outdoor applications, and can withstand both freezing and scorching weather. Flashing light effects can be created if a controller is used. The Mini Round Instant Flexilight is suitable for making complicated patterns and designs with acute angles and dense lines. Its flexibility also makes it perfect for making smaller designs, such as portable signs and small home decorations.



Number of wire	2
Number of bulb/foot	12
Diameter	3/8"
Shape	Round
Colors available (PVC)	Clear:
	Clear, Red
	Green, Orange, Purple
	Fluorescent Colors:
	Green, Orange and Pink
	Pearl Colors:
	Red, Yellow, Blue & Green

Specifications of Mini Round Instant Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	12V	30'	4"	3.0V 0.07A 0.21W	12	2.52W/foot
	24V	60'	8"	3.0V 0.07A 0.21W	12	2.52W/foot
	110-120V	150'	24"	6.5V 0.07A 0.46W	12	5.5W/foot

Packages Available

Item Number	Length	Package	ERMF - 120 - 150 - COLOR
ERMF-120-150	150'	/Roll	Item No. Voltage Length Specify color
ERMF-24-150*	150'	/Roll	(Available in 150' Rolls only, no custom cut)
ERMF-12-150**	150'	/Roll	

NOTE: EACH ROLL INCLUDES; 3pcs ERM1XXX Power Cords, 3pcs M3 Splice Connectors, 3pcs M4 End Caps

Mini Round Instant Flexilight Accessories:

ERM1-120V	Mini Round Flexilight 6ft. Power Cord w/ Power Connector
ERM1-24V*	Mini Round Flexilight 6ft. Power Cord w/ Power Connector
ERM1-12V**	Mini Round Flexilight 6ft. Power Cord w/ Power Connector
M3	Mini Round Flexilight Splice Connector
M4	Mini Round Flexilight End Caps
M5	Mini Round Flexilight Tie Strap
M6	Mini Round Flexilight Mounting Clips
M7	Mini Round Flexilight Suction Cup
M8	Mini Round Flexilight 6ft. Channel
M9	Mini Round Flexilight Easy Splice Connector
M10	Mini Round Flexilight Y-cord
M11	Mini Round Flexilight T-connector
M14	Housing Clamp for Splice Connector
M103	Mini Round Flexilight PVC Connector
M22	Mini Round Flexilight PVC T-Connector
M23	Mini Round Flexilight PVC X-Connector

ERM1



M3



M4



M5



M6



M8



M9



M10



M11



M7



M14



M22



M23



M103



Standard Controller

MODEL	VOLTAGE AVAILABLE	MAX. LENGTH	FUNCTIONS
ERWL-2C-M-110	120V	150 FT.	Static/Flashing
ERWL-2C-M-24A*	24V	60 FT.	Static/Flashing
(*Requires 24V AC power source)			
ERWL-2C-M-12A**	12V	30 FT.	Static/Flashing
(**Requires 12V AC power source)			

