

MT-4LD2 - 2 Light

4" LED Precision Multiples

WAC



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- ELV and 0-10V dimming options
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Fully retractable from housing
- 365° horizontal rotation and 180° vertical aiming
- Accepts 1 replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Universal (120V - 277V) or 120V input only

Light Source: High output LED (included with housing)

Dimming: 0-10V or ELV (see list of housings below)

Mounting: Supplied with hanger bars, adjustable from 9 1/4" - 24 1/2" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 9 3/4" x 5 1/8" cutout with trim, 9 3/4" x 5 1/8" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed. Airtight.

TRIMS

		MT-4LD216T Trim	WT White BK Black
		MT-4LD216TL Invisible Trim™	WT White



Example: **MT-4LD216T-BK**

HOUSINGS

	Power	Beam	Color Temp	CRI	Interior
	MT-4LD216N 0-10V dimming Non-IC, 120V-277V input 15W x 2	S 20° F 40°	27 2700K 85	BK Black	
	MT4LD216NE ELV dimming Non-IC, 120V input 15W x 2		927 2700K 90		
	MT4LD211NE ELV dimming IC-Rated, 120V input 11W x 2		30 3000K 85		
			930 3000K 90		
			35 3500K 85		
			40 4000K 85		



Example: **MT-4LD216NE-S927-BK**

REPLACEMENT LENS

Amber	LENS-16-AMB	UV Filter	LENS-16-UVF
Blue	LENS-16-BLU	Frosted	LENS-16-FR
Green	LENS-16-GRN	Spread	LENS-16-SPR
Red	LENS-16-RED	Beam Elongator	LENS-16-BEL

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility









1750 S Archibald Ave

Ontario, CA 91761

MT-4LD2 - 2 Light

4" LED Precision Multiples

WAC

LUMINAIRE PERFORMANCE	Power Per Light	Beam	Photometry	Color Temp	CRI	Lumen	CBCP
MT-4LD216N 0-10V dimming Non-IC, 120V-277V input	15W	S 20°		27 2700K 85 2600 6990 x 2			
				927 2700K 90 2160 5800 x 2			
				30 3000K 85 2700 7270 x 2			
				930 3000K 90 2240 6010 x 2			
		F 40°		35 3500K 85 2780 7480 x 2			
				40 4000K 85 2810 7550 x 2			
				27 2700K 85 2530 3060 x 2			
				927 2700K 90 2100 2540 x 2			
		S 20°		30 3000K 85 2700 7270 x 2			
				930 3000K 90 2240 6010 x 2			
				35 3500K 85 2780 7480 x 2			
				40 4000K 85 2810 7550 x 2			
MT4LD216NE ELV dimming Non-IC, 120V input	15W	F 40°		27 2700K 85 2530 3060 x 2			
				927 2700K 90 2100 2540 x 2			
				30 3000K 85 2630 3185 x 2			
				930 3000K 90 2180 2635 x 2			
		S 20°		35 3500K 85 2710 3275 x 2			
				40 4000K 85 2730 3310 x 2			
				27 2700K 85 2060 5570 x 2			
				927 2700K 90 1710 4620 x 2			
MT4LD211NE ELV dimming IC-Rated, 120V input	11W	F 40°		30 3000K 85 2140 5790 x 2			
				930 3000K 90 1770 4790 x 2			
				35 3500K 85 2200 5960 x 2			
				40 4000K 85 2220 6015 x 2			
		S 20°		27 2700K 85 2000 2395 x 2			
				927 2700K 90 1650 1980 x 2			
				30 3000K 85 2080 2490 x 2			
				930 3000K 90 1720 2065 x 2			
		F 40°		35 3500K 85 2140 2560 x 2			
				40 4000K 85 2160 2585 x 2			
				27 2700K 85 2000 2395 x 2			
				927 2700K 90 1650 1980 x 2			

REPLACEMENT HEADS (INCLUDES: ONE HEAD, LED, AND DRIVER)

Housing Model	Module
MT-4LD216N	4MT4LD16N-S27-BK
	4MT4LD16N-S30-BK
	4MT4LD16N-S35-BK
	4MT4LD16N-S40-BK
	4MT4LD16N-S927-BK
	4MT4LD16N-S930-BK
	4MT4LD16N-F27-BK
	4MT4LD16N-F30-BK
	4MT4LD16N-F35-BK
	4MT4LD16N-F40-BK
	4MT4LD16N-F927-BK
	4MT4LD16N-F930-BK
MT4LD216NE	4MT4LD16NE-S27-BK
	4MT4LD16NE-S30-BK
	4MT4LD16NE-S35-BK
	4MT4LD16NE-S40-BK
	4MT4LD16NE-S927-BK
	4MT4LD16NE-S930-BK
	4MT4LD16NE-F27-BK
	4MT4LD16NE-F30-BK
	4MT4LD16NE-F35-BK
	4MT4LD16NE-F40-BK
	4MT4LD16NE-F927-BK
	4MT4LD16NE-F930-BK
MT4LD211NE	4MT4LD11NE-S27-BK
	4MT4LD11NE-S30-BK
	4MT4LD11NE-S35-BK
	4MT4LD11NE-S40-BK
	4MT4LD11NE-S927-BK
	4MT4LD11NE-S930-BK
	4MT4LD11NE-F27-BK
	4MT4LD11NE-F30-BK
	4MT4LD11NE-F35-BK
	4MT4LD11NE-F40-BK
	4MT4LD11NE-F927-BK
	4MT4LD11NE-F930-BK