FLEXIBLE ROPELIGHT

Specifications of LED Instant Flexilight:

Struc	ture	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
#9 <u>+</u> Y	*	110-120V	600' (WW, CW, B, G)	40" (WW, CW, B, G)	LED	36	0.8W/foot
			900′ (R, Y)	54" (R, Y)	LED	54	0.53W/foot
*9)	24V	100' (WW, CW, B, G)	6" (WW, CW, B, G)	LED	6	0.88W/foot .
			200' (R, Y)	4" (R, Y)	LED	12	0.44W/foot
*9 -\C	<u> </u>	12V	50' (WW, CW, B, G)	3" (WW, CW, B, G)	LED	6	0.88W/foot
			100' (R, Y)	6" (R, Y)	LED	12	0.44W/foot

Packages Available

Item Number	Length	Package
ER-LED-120-150	150′	/Roll
ER-LED-24-150	150′	/Roll
ER-LED-12-150	150′	/Roll

No Driver Required/ Rectifier Included

Item No. Voltage - 150 - COLOR Specify color

(Available in 150' Rolls only, no custom cut)


NOTE: Each Roll Includes; 3pcs ERIFL-XXX Power Cords, 3pcs F4 End Caps

NOTE:	Cat#		LED Lenght	Max. Wattage
LED Magnetic Transformer	M100L-12-DC	12V	50′	75w
	M100L-24-DC	24V	100′	100w

LED Instant Flexilight Accessories:

ERIFL-F106 -120V LED Flexilight 6ft. Power Cord w/ Power Connector
ERIFL-F107 -24V LED Flexilight 6ft. Power Cord w/ Power Connector
ERIFL-F107 -12V LED Flexilight 6ft. Power Cord w/ Power Connector













F6



F7





FI0



FI4



F22



F23



F103

