

# Data-2-Dynamics: a modeling environment tailored to parameter estimation in dynamical systems

A. Raue<sup>1,2,\*</sup> and J. Timmer<sup>1,3,4</sup>

<sup>1</sup>University of Freiburg, Institute for Physics, 79104 Freiburg, Germany

<sup>2</sup>Merrimack Pharmaceuticals Inc., 02139 Cambridge, MA, USA

<sup>3</sup>BIOSS Centre for Biological Signalling Studies, University of Freiburg, 79104 Freiburg, Germany

<sup>4</sup>Zentrum für Biosystemanalyse (ZBSA), University of Freiburg, 79104 Freiburg, Germany

Received on XXXXX; revised on XXXXX; accepted on XXXXX

Associate Editor: XXXXXXXX

## ABSTRACT

**Summary:** Modeling of dynamical systems using ordinary differential equations is a popular approach in the field of Systems Biology. One of the most critical steps in this approach is to conveniently construct dynamical models of biochemical reaction networks for large data sets and complex experimental conditions and to perform efficient and reliable parameter estimation for model fitting. We present a MATLAB based modeling environment that pioneers these challenges. The numerically expensive parts of the required calculations such as the solving of the differential equations and of the associated sensitivity system are parallelized and automatically compiled into efficient C code. A variety of parameter estimation algorithms as well as both frequentist and Bayesian methods for uncertainty analysis have been implemented and used on a range of applications that lead to publications.

**Availability and Implementation:** The Data-2-Dynamics modeling environment is a collaborative open source project and freely available. The code and full documentation are hosted and developed on the BitBucket website <https://bitbucket.org/d2d-development/d2d-software>. Participation in the further development is highly welcome!

**Contact:** andreas.raue@fdm.uni-freiburg.de

**Supplementary information:** Supplementary text and figures are available.

**Model Construction** The dynamics of cellular processes such as signal transduction pathways or models of cell growth and death can be described by models consisting of ordinary differential equations (ODE). Mathematically, such dynamical systems can be characterised by  $\dot{\mathbf{x}}(t, \boldsymbol{\theta}) = \mathbf{f}(\mathbf{x}(t, \boldsymbol{\theta}), \mathbf{u}(t, \boldsymbol{\theta}), \boldsymbol{\theta})$  with  $\mathbf{x}(0, \boldsymbol{\theta}) = \mathbf{g}(\boldsymbol{\theta})$ . In this case the vector of state variables  $\mathbf{x}(t, \boldsymbol{\theta})$  describes the dynamics of molecular components. The function  $\mathbf{u}(t, \boldsymbol{\theta})$  represents experimental treatments that are time-varying inputs to the ODE systems. A variety of predefined function such as step functions, pulses, splines or custom defined functions are available that can depend on unknown parameters (Schelker *et al.*, 2012). The initial concentrations  $\mathbf{x}(0, \boldsymbol{\theta})$  can be a function  $\mathbf{g}(\boldsymbol{\theta})$  of unknown parameters as well. For a specific cell type or biological context, the set of parameters  $\boldsymbol{\theta}$  are often not available from literature and

have to be estimated from experimental data. Similar to previous software, e.g. Maiwald and Timmer (2008), our current software allows to consider multiple different models that can share common parameters and fit them simultaneously to all available data. Our software allows both to 1) directly specify the right hand side of the ODE manually, or to 2) automatically generate it by providing a reaction scheme such as  $A + B \rightarrow C$ . In the latter case, for specifying the reaction rate equations one can either choose to apply default Mass Action kinetics, either reversible  $\leftrightarrow$  or non-reversible  $\rightarrow$ , or a custom rate law such as Michaelis-Menten or Hill kinetics. The resulting right hand side of the ODE system as well as its Jacobian matrix that is calculated automatically by symbolic differentiation are translated to C code and compiled together with the ODE solver CVODES (Hindmarsh *et al.*, 2005). In case of 2), the code makes efficient use of pre-calculated reaction fluxes throughout the code as described in the Supplementary Information.

**Dataset and Experimental Conditions** Experimental data provides information to estimate unknown model parameter by fitting the model. Each possible measurement is mathematically represented by a functional mapping  $\mathbf{y}(t, \boldsymbol{\theta}) = \mathbf{h}(\mathbf{x}(t, \boldsymbol{\theta}), \mathbf{u}(t, \boldsymbol{\theta}), \boldsymbol{\theta})$ , that might include additional parameters such as scaling or offset parameters and thus increase the dimension of  $\boldsymbol{\theta}$ . For each model, multiple datasets can and should be considered simultaneously. One key feature of the Data-2-Dynamics software that is its ability of the conveniently and automatically create model variants that represent different experimental conditions that were used in different experiments. These conditions can directly be defined in the data sheets that contain the experimental data and is conveniently parsed and grouped. For instance, a time course experiment could have been performed with all combinations of two treatment options. The corresponding four experimental setting will be extracted and respective variants of the ODE system are generated and linked to the data. The model simulation will be plotted in the same grouping as well. Another frequently occurring case are dose response experiments at a fixed time points. In this case the software will again automatically generate all required model variants and display the simulation results in a dose response plot. For computational efficiency experimental conditions, and thus model variants, that are share between different experiments are calculated only once. Since all variants of the original ODE system have to be solved independently, the C code automatically

\*to whom correspondence should be addressed

parallelized the execution of the ODE solver, see Supplementary Information for a performance comparison.

**Experimental Noise** Another unique feature of the Data-2-Dynamics software is its ability to consider and estimate uncertainty in experimental data. By implementing a full Maximum Likelihood Estimation framework, we demonstrated that this approach provides a more robust and reliable determination of experimental noise (Raue et al., 2013b). The software is able to estimate the amount of experimental noise simultaneously with the unknown parameter that define the dynamics in a statistically more efficient way. A determination of measurement noise by manual inspection or by a preprocessing procedure is not required any more. Therefore, the results that are obtained by our software are independent of the degree of the experimenter's believe in the quality of the experimental data.

**Sensitivity Equations** The software implements a sophisticated method to calculate model sensitivities, the derivatives of the dynamics with respect to model parameters (Leis and Kramer, 1988). The sensitivity equations are derived automatically by symbolic differentiation, are translated to C code and compiled together with the original ODE systems and the solver. The solver CVODES (Hindmarsh et al., 2005) allows for an efficient numerical solution of both the original ODE systems and of the sensitivity equations. We showed previously (Raue et al., 2013b) that this approach is not only about ten fold faster but also more precise than the default approach. A reliable calculation of these derivatives is key to successful parameter estimation.

**Parameter Estimation** A critical task in modeling of dynamical systems is the efficient and reliable estimation of model parameters, also called model fitting. We implemented a variety of different parameter estimation algorithms, see Supplementary Information. The most efficient and reliable algorithm for parameter estimation in our hands is a deterministic trust region approach (Coleman and Li, 1996) combined with multi-start strategy (Raue et al., 2013b) to avoid local minima. Parameters can and should be estimated on a log scale. For experimental data, the software allows to compare model to data on a log scale as well. A very general objective function including all model variant, dataset and experimental conditions is generated based on the Maximum Likelihood Estimation framework. If a steady state assumption  $\dot{\mathbf{x}}(t) = 0$  for the model dynamics is required, and its solution  $\mathbf{g}(\boldsymbol{\theta})$  is not known, a steady state constraint can be added to the objective function, including the respective derivatives. Prior assumption can be added to the objective function as well. A quality control, as proposed in Raue et al. (2013b) can be performed to validate robustness of the estimation results.

**Uncertainty Analysis and Experimental Design** In addition to finding the best model fit to the collection of experimental data using parameter estimation, the Data-2-Dynamics software implements a variety of algorithms that determined uncertainty in the estimated parameter as well as in the predicted model dynamics or derived quantities. In particular, the frequentist profile likelihood approach for identifiability analysis (Raue et al., 2009), the predictions profile likelihood approach for observability analysis (Kreutz et al., 2012) as well as a variety of Bayesian approaches (Raue et al., 2013a; Hug et al., 2013) that calculate posterior probability distributions

are available. Based on the results of the uncertainty analysis, the software allows to design additional experiments (Steiert et al., 2012) that can resolve non-identifiability and non-observability (Raue et al., 2010; Kreutz et al., 2013) and improve prediction accuracy.

**Visualization and Reports** A variety of automatically generated plots and visualizations of all simulated quantities as well as experimental data, model structure and parameter estimation and uncertainty analysis results are available. All information about the model equations, the data set and estimation results as well as generated figure can be automatically compiled into a Latex based PDF report.

**Summary** We present the Data-2-Dynamics software, a modeling environment that is especially tailored to parameter estimation and model fitting in dynamical systems. The code is open source and is developed in a community effort using a web-based hosting service and a revision control systems. A variety of published applications, e.g. Becker et al. (2010); Raia et al. (2011); Bachmann et al. (2011), that made use of the software are provided as benchmark examples for further methods development and as guide for novel applications. For these examples not only the models but also all datasets and their link to the models as well as all original information used in the parameter estimation and uncertainty analysis are provided. The software was awarded twice as best performer in the Dialogue for Reverse Engineering Assessments and Methods (DREAM, 2011 and 2012).

## ACKNOWLEDGEMENT

We thank all academic and industrial collaborators that helped to evolve this modeling environment, in particular the Timmer group at the University of Freiburg, the Klingmüller group and the Höfer group at DKFZ Heidelberg, the Theis group at the German Research Center for Environmental Health, the Bode group at the University Hospital of Düsseldorf, the Klipp group at the Humboldt-University Berlin as well as Merrimack Pharmaceuticals in Cambridge.

**Funding:** This work was supported by XXX

**Conflict of interest:** None declared.

## REFERENCES

- Bachmann, J., Raue, A., Schilling, M., Böhm, M., Kreutz, C., Kaschek, D., Busch, H., Gretz, N., Lehmann, W., Timmer, J., and Klingmüller, U. (2011). Division of labor by dual feedback regulators controls JAK2/STAT5 signaling over broad ligand range. *Molecular Systems Biology*, **7**, 516.
- Becker, V., Schilling, M., Bachmann, J., Baumann, U., Raue, A., Maiwald, T., Timmer, J., and Klingmüller, U. (2010). Covering a broad dynamic range: information processing at the erythropoietin receptor. *Science*, **328**(5984), 1404–1408.
- Coleman, T. and Li, Y. (1996). An interior, trust region approach for nonlinear minimization subject to bounds. *SIAM Journal on Optimization*, **6**(2), 418–445.
- Hindmarsh, A., Brown, P., Grant, K., Lee, S., Serban, R., Shumaker, D., and Woodward, C. (2005). SUNDIALS: Suite of nonlinear and differential/algebraic equation solvers. *ACM T Math Software*, **31**(3), 363–396.
- Hug, S., Raue, A., Hasenauer, J., Bachmann, J., Klingmüller, U., Timmer, J., and Theis, F. (2013). High-dimensional Bayesian parameter estimation: Case study for a model of JAK2/STAT5 signaling. *Mathematical Biosciences*, **246**(2), 293–304.
- Kreutz, C., Raue, A., and Timmer, J. (2012). Likelihood based observability analysis and confidence intervals for predictions of dynamic models. *BMC Systems Biology*, **6**, 120.

- Kreutz, C., Raue, A., Kaschek, D., and Timmer, J. (2013). Profile likelihood in systems biology. *FEBS Journal*, **280**(11), 2564–2571.
- Leis, J. and Kramer, M. (1988). The simultaneous solution and sensitivity analysis of systems described by ordinary differential equations. *ACM T Math Software*, **14**(1), 45–60.
- Maiwald, T. and Timmer, J. (2008). Dynamical modeling and multi-experiment fitting with potterswheel. *Bioinformatics*, **24**(18), 2037–2043.
- Raia, V., Schilling, M., Böhm, M., Hahn, B., Kowarsch, A., Raue, A., Sticht, C., Bohl, S., Saile, M., Möller, P., Gretz, N., Timmer, J., Theis, F., Lehmann, W., Lichter, P., and Klingmüller, U. (2011). Dynamic mathematical modeling of IL13-induced signaling in Hodgkin and primary mediastinal B-cell lymphoma allows prediction of therapeutic targets. *Cancer Research*, **71**, 693–704.
- Raue, A., Kreutz, C., Maiwald, T., Bachmann, J., Schilling, M., Klingmüller, U., and Timmer, J. (2009). Structural and practical identifiability analysis of partially observed dynamical models by exploiting the profile likelihood. *Bioinformatics*, **25**(15), 1923–1929.
- Raue, A., Becker, V., Klingmüller, U., and Timmer, J. (2010). Identifiability and observability analysis for experimental design in non-linear dynamical models. *Chaos*, **20**(4), 045105.
- Raue, A., Kreutz, C., Theis, F., and Timmer, J. (2013a). Joining forces of Bayesian and frequentist methodology: A study for inference in the presence of non-identifiability. *Phil. Trans. Roy. Soc. A*, **371**, 20110544.
- Raue, A., Schilling, M., Bachmann, J., Matteson, A., Schelker, M., Kaschek, D., Hug, S., Kreutz, C., Harms, B., Theis, F., Klingmüller, U., and Timmer, J. (2013b). Lessons learned from quantitative dynamical modeling in systems biology. *PLOS ONE*, **8**(9), e74335.
- Schelker, M., Raue, A., Timmer, J., and Kreutz, C. (2012). Comprehensive estimation of input signals and dynamical parameters in biochemical reaction networks. *Bioinformatics*, **28**(18), i522–i528.
- Steiert, B., Raue, A., Timmer, J., and Kreutz, C. (2012). Experimental design for parameter estimation of gene regulatory networks. *PLOS ONE*, **7**(7), e40052.