

Contents

<i>List of Figures</i>	x
<i>List of Tables</i>	xii
1 Introduction	1
1.1 Motivation	1
1.2 Molecular Dynamics	2
1.2.1 Newton's Laws of Motion	2
1.2.2 Lennard-Jones Potential	3
1.2.3 Störmer-Verlet Algorithm	3
2 AutoPas	5
2.1 Background	5
2.2 Configuration Parameters	5
2.2.1 Containers	5
2.2.2 Traversals	5
2.2.3 Additional Parameters	5
2.3 Tuning Strategies	6
3 Implementation	7
3.1 Considerations	7
3.1.1 Computational Overhead	7
3.1.2 Available Simulation Statistics	7
3.1.3 Interaction with Tuning Strategies	7
3.2 Time-based Triggers	8
3.2.1 Simple Trigger	8
3.2.2 Single-iteration averaging Trigger	8
3.2.3 Interval averaging Trigger	9
3.2.4 Linear Regression Trigger	9
3.3 Hybrid Triggers	10
4 Evaluation	11
4.1 Benchmarking Scenarios	11
4.1.1 Equilibrium	11
4.1.2 Exploding Liquid	11
4.1.3 Heating Sphere	12
4.1.4 Falling Drop	13
4.1.5 Spinodial Decomposition	13
4.2 Evaluation Metrics	13

5	Results	14
5.1	Trigger Parameters	14
5.1.1	Equilibrium	14
5.1.2	Exploding Liquid	16
5.1.3	Heating Sphere	16
5.2	Trigger Behavior	16
5.2.1	Simple Trigger	16
5.2.2	Single-iteration averaging Trigger	16
5.2.3	Interval averaging Trigger	16
5.2.4	Linear Regression Trigger	16
5.3	Optimality	16
5.4	Runtime	16
5.5	Share of Tuning Iterations	16
6	Conclusion	17
6.1	Dynamic Initiation of Tuning Intervals	17
6.2	Future Work	17
	<i>Bibliography</i>	19

This page is intentionally left blank.

List of Figures

1.1	An illustration of the potential well of the 12-6 LJ potential, with the minimum of $-\varepsilon$ at $r_{\min} = \sigma \sqrt[6]{2}$ and zero-crossing at σ . The figure is based on Lenhard et al. [Lenhard2024]	4
2.1	Comparison between the Array of Structures (AoS) and Structure of Arrays (SoA) memory layouts. The $r^{(i)}$'s correspond to the position vector of the i th particle.	6
3.1	Average Speedup between unoptimized and optimized runs for the TimeBasedAverage, TimeBasedSplit and TimeBasedRegression strategies. . . .	8
3.2	Comparison between the TimeBasedSimpleTrigger (left) and TimeBasedAverageTrigger (right) strategies for $\lambda = 1.5$ and $n = 5$. A new tuning phase is initiated in both cases, however the TimeBasedAverageTrigger results in a higher threshold.	9
3.3	Comparison between the TimeBasedSplitTrigger and TimeBasedRegressionTrigger strategies for $\lambda = 1.5$ and $n = 11$	9
4.1	Evolution of the simulation state in the equilibrium scenario.	12
4.2	Evolution of the simulation state in the exploding liquid scenario.	12
4.3	Evolution of the simulation state in the heating sphere scenario.	13
5.1	Trigger behavior in the equilibrium scenario, the numbers in the legends refer to the number of samples n considered. Note the logarithmic scale in the plots for the tuning iterations.	15

This page is intentionally left blank.

List of Tables

5.1	Suggested default parameters for the equilibrium scenario.	15
-----	--------------------------------------------------------------------	----

This page is intentionally left blank.

4

Evaluation

This chapter presents the scenarios and criteria employed in the evaluation of our implementation. Section 4.1 introduces a series of benchmarking scenarios, which have been chosen to reflect distinct simulation characteristics appearing in real-world applications.

Subsequently, Section 4.2 defines the evaluation metrics applied to these benchmarks. The metrics are intended to provide comparability between simulation runs with dynamic tuning intervals and to the baseline runs with static tuning intervals.

Together, the benchmarking scenarios and evaluation metrics provide a framework for assessing the performance and reliability of the proposed strategies.

4.1 Benchmarking Scenarios

As to not limit our analysis to one specific simulation setting, we use a selection of benchmarking scenarios. These represent different structures as they may be used in real-world applications. The heating-sphere and exploding-liquid scenarios are identical to the ones given by Newcome et al., the configuration files have been adapted and parametrized for use in this thesis [2]. The other scenarios are taken from the AutoPas `md-flexible` example.

4.1.1 Equilibrium

In the equilibrium scenario, particles with initial velocity 0 are packed tightly into a cube with periodic boundary conditions. The particles interact with each other and the grid structure loosens up, but ultimately an equilibrium is reached in which no rapid changes in velocity occur anymore. After some initial relaxation of the grid structure, there is no further scenario change expected. Therefore, no additional tuning phases should be needed, as the optimal configuration is not expected to change.

4.1.2 Exploding Liquid

Similarly to the equilibrium scenario, the exploding liquid scenario starts with the particles packed into a cuboid with periodic boundaries. The cuboid explodes in y -




Figure 4.1: Evolution of the simulation state in the equilibrium scenario.

direction, collides with the boundary and finally settles into an equilibrium state spread out over the whole simulation space. If a single AutoTuner instance is used for the whole domain, the rapid changes in particle positions and heterogeneous particle distribution make finding an optimal configuration very hard. However, if the domain is split up into multiple independent AutoPas instances on different MPI nodes, each AutoTuning instance can independently find an optimal configuration for its part of the domain. By this, the simulation domain can be split up into regions that have been affected by the “explosion” and regions that no particles have entered yet.




Figure 4.2: Evolution of the simulation state in the exploding liquid scenario.

4.1.3 Heating Sphere

The heating sphere scenario consists of a dense, small sphere of particles. Reflective boundary conditions apply as in the previous scenarios. In the course of the simulation, the temperature rises from 0.1 to 100 with a $\Delta T^* = 0.1$ every 100 iterations. Additionally, brownian motion, i.e. random fluctuations in particle positions are applied [1]. The sphere expands with the increase in temperature and particles are radiating out from the sphere center.




Figure 4.3: Evolution of the simulation state in the heating sphere scenario.

4.1.4 Falling Drop

4.1.5 Spinodial Decomposition

4.2 Evaluation Metrics

To compare results between dynamic and static tuning intervals, different metrics can be used. Firstly, the primary goal is to reduce the total simulation runtime for a range of typical scenarios. As tuning phases spend time in quite suboptimal configurations, a reduction in total runtime is the expected result if our approach reduces the number of tuning phases without spending too many iterations using a suboptimal configuration outside tuning phases.

The metric of total runtime is not particularly fine-grained however, as it only takes into account entire simulation runs. To achieve a more detailed benchmark, we also consider the number of iterations that were running on an optimal configuration. As an approximation to the optimal configuration per iteration we use simulation run with static tuning, a high number of tuning samples and a short tuning interval. Based on this static data we can then rank the configuration our dynamic run chose in terms of “optimality”.

This page is intentionally left blank.

Bibliography

- [1] Peter Mörters and Yuval Peres. *Brownian motion*. Vol. 30. Cambridge University Press, 2010.
- [2] Samuel James Newcome et al. “Algorithm Selection in Short-Range Molecular Dynamics Simulations”. In: (May 2025). doi: 10.48550/ARXIV.2505.03438. arXiv: 2505.03438 [cs.CE].

This page is intentionally left blank.

