LEXICAL MULTI-DIMENSIONAL ANALYSIS SOLUTION

High-Level Design

Tony Berber Sardinha

Rogério Yamada

2025

Abstract

work in progress (Biber, 1988)

Keywords: work in progress

Contents

1	Project Overview					
	1.1	Purpose	2			
	1.2	Scope	2			
	1.3	Stakeholders	2			
2	Functional Requirements					
	2.1	Corpus Ingestion	3			
	2.2	Preprocessing	4			
	2.3	Feature Extraction	4			
	2.4	Dimensional Analysis	4			
	2.5	Visualisation and GUI	4			
	2.6	Export and Reporting	4			
	2.7	Automation and Scripting	4			
3	Non-Functional Requirements 5					
	3.1	Performance	5			
	3.2	Usability	5			
	3.3	Reliability and Robustness	5			
	3.4	Portability and Compatibility	5			
	3.5	Security	5			
4	System Architecture					
	4.1	Overview	5			
	4.2	Components	5			
	4.3	Data Flow	6			
5	Tecl	hnology Stack	6			

6	Interfaces and APIs					
	6.1	Python Module Interfaces	7			
	6.2	Plug-in Interface	7			
	6.3	CLI	7			
	6.4	Optional REST API (FastAPI)	7			
7	Seci	urity and Privacy Considerations	7			
	7.1	Data Protection	7			
	7.2	Access Control (Server Mode)	8			
	7.3	Supply Chain	8			
8	Risks and Mitigations					
9	Timeline and Milestones					
Α	Арр	endices	10			
	A.1	work in progress	10			

1 Project Overview

1.1 Purpose

This document describes the high-level design of a Python-based application for Lexical Multi-Dimensional Analysis (LMDA) with an interactive graphical user interface (GUI). The system ingests text corpora, performs linguistic preprocessing, extracts lexical features, projects texts into a multi-dimensional factor space (e.g., via PCA/FA/MD analysis), and presents results through interactive visualisations and reports.

1.2 Scope

The application supports:

- Corpus ingestion from files, folders, and CSV/TSV columns;
- Language-aware preprocessing (tokenisation, lemmatisation, POS tagging);
- Feature extraction (lexical richness, frequency profiles, function/content word ratios, POS ngrams, domain lexicons);
- Dimensionality reduction and factor analysis (e.g., PCA, Exploratory Factor Analysis) to derive interpretable dimensions;
- Interactive exploration (scatter plots, loadings, factor scores), filtering, and labeling;
- Exportable reports (PDF/HTML) and machine-readable outputs (CSV/JSON).

1.3 Stakeholders

• Linguists and corpus analysts;




Figure 1: Lexical Multi-Dimensional Analysis (Berber Sardinha & Fitzsimmons-Doolan, 2025)




Figure 2: Lexical Multi-Dimensional Analysis Procedures

- Data scientists working on stylistic and register analysis;
- Educators and applied researchers;
- Software maintainers and operations personnel (if deployed as a desktop or server app).

2 Functional Requirements

2.1 Corpus Ingestion

- FR-1: Import plain text files, folders, and CSV/TSV with a designated text column;
- FR-2: Detect/allow selection of text encoding (UTF-8 default), handle BOM, and report decoding errors;
- FR-3: Optional metadata import (e.g., author, source, label) to support grouping and filtering.

2.2 Preprocessing

- FR-4: Tokenise, normalise (case, punctuation policies), and sentence-segment texts;
- FR-5: Lemmatise and POS-tag (spaCy models; fallback to NLTK if unavailable);
- FR-6: Language selection and multi-language support; warn if models are missing;
- FR-7: Stopword management (built-in lists and user-defined additions).

2.3 Feature Extraction

- FR-8: Compute lexical richness metrics (TTR, MTLD, Maas, HDD);
- FR-9: Frequency features: word and lemma frequency profiles; function word distributions;
- FR-10: POS and POS n-grams; content/function word ratios; lexical sophistication bands;
- FR-11: Custom feature plug-ins via a documented Python interface.

2.4 Dimensional Analysis

- FR-12: Build a document-feature matrix (DFM) with configurable weighting (raw, tf-idf, z-scores);
- FR-13: Perform dimensionality reduction (PCA) and optional factor analysis (EFA/Varimax);
- FR-14: Compute factor loadings, factor scores, and explained variance;
- FR-15: Save and load trained models/pipelines for reproducibility.

2.5 Visualisation and GUI

- FR-16: Interactive scatter/biplots of documents in 2D/3D factor space with tooltips and labels;
- FR-17: Loading plots, scree plots, and feature contribution charts;
- FR-18: Brushing/filtering by metadata, search, and selection for detailed inspection;
- FR-19: Theming, layout persistence, and session autosave.

2.6 Export and Reporting

- FR-20: Export factor scores, loadings, and projections to CSV/JSON;
- FR-21: Generate PDF/HTML reports with key plots and tables;
- FR-22: Export model artifacts (preprocessing config, feature schema, PCA/FA components).

2.7 Automation and Scripting

- FR-23: Batch processing via CLI and/or headless mode;
- FR-24: Optional REST API for programmatic access (server mode).

3 Non-Functional Requirements

3.1 Performance

- NFR-1: Handle corpora up to 1M tokens on a standard laptop with reasonable latency (<10s for PCA on 10k documents x 1k features, assuming sparse ops);
- NFR-2: Incremental processing and caching to avoid recomputation.

3.2 Usability

- NFR-3: Intuitive GUI with sensible defaults; accessible color schemes;
- NFR-4: Contextual help and onboarding tips; undo/redo for key actions.

3.3 Reliability and Robustness

- NFR-5: Deterministic pipelines when seeds are fixed; versioned model artifacts;
- NFR-6: Error handling with clear diagnostics and recovery suggestions.

3.4 Portability and Compatibility

- NFR-7: Cross-platform support (Windows, macOS, Linux);
- NFR-8: Python 3.10+; packaged with virtualenv/Poetry; optional standalone (PyInstaller).

3.5 Security

- NFR-9: Local-only data processing by default; no data leaves the machine;
- NFR-10: If server mode enabled, enforce TLS and authentication.

4 System Architecture

4.1 Overview

The system follows a modular, pipeline-oriented architecture separating ingestion, preprocessing, feature extraction, modeling, and presentation layers. A central configuration orchestrates reproducible runs; artifacts are persisted for reuse.

4.2 Components

GUI Layer Desktop GUI (PySide6/PyQt) for user workflows: project management, corpus loading, configuration, visualisation, and export.

Controller / **Orchestration** Coordinates pipeline stages, manages state, triggers incremental recomputation when inputs change, and logs provenance.

Preprocessing Service Language detection, sentence segmentation, tokenisation, lemmatisation, POS tagging, stopword filtering; caches normalised representations.

Feature Service Computes metrics and vectorises documents into a DFM with configurable normalisation and weighting; supports plug-ins.

Modeling Service Performs PCA/EFA, computes loadings and scores, applies rotations (e.g., Varimax/Promax), and persists models.

Visualisation Service Generates interactive plots (2D/3D scatter, biplots, scree, loadings) and data tables; supports selections and linked views.

Persistence Layer Stores corpora metadata, preprocessed artifacts, features, and models (e.g., SQLite for metadata, parquet/npz for matrices, joblib for models).

API Layer (Optional) FastAPI-based REST endpoints for batch/remote processing in server mode.

4.3 Data Flow

- 1. Import corpus \rightarrow normalise text \rightarrow linguistic annotation.
- 2. Extract features \rightarrow construct DFM \rightarrow apply weighting/normalisation.
- 3. Fit PCA/EFA \rightarrow compute scores/loadings \rightarrow store artifacts.
- 4. Visualise and interact \rightarrow export results and reports.

5 Technology Stack

- Language: Python 3.11 (or 3.10+);
- GUI: PySide6 or PyQt6; alternative: Qt for Python widgets + matplotlib/plotly;
- NLP: spaCy (core models: en_core_web_sm/md/lg), NLTK (fallback, resources), langdetect/fastText for language ID;
- Data: pandas, numpy, scipy (sparse matrices), scikit-learn for PCA, factor analyzers (factor_analyzer)
 for EFA/rotations;
- Visualisation: matplotlib, seaborn, plotly; pyqtgraph for fast interactive plots;
- Persistence: SQLite (metadata), parquet/CSV (tables), npz (sparse matrices), joblib/pickle (models), YAML/TOML (config);
- Packaging: Poetry or pip-tools; PyInstaller for desktop bundle; Docker for server mode;
- Testing: pytest, hypothesis for property-based testing, tox/nox for matrix runs;
- CI/CD: GitHub Actions or GitLab CI for tests, linting (ruff, black), and packaging.

6 Interfaces and APIs

6.1 Python Module Interfaces

- ullet Preprocessor: process(corpus, config) o annotations;
- FeatureExtractor: fit_transform(annotations) → DFM; transform(...);
- Modeler: fit(DFM) \rightarrow model; transform(DFM) \rightarrow scores;
- Visualiser: plots(scores, loadings, metadata);
- Persistence: save_artifact(obj, kind) and load_artifact(kind).

6.2 Plug-in Interface

Third-party feature extractors implement IFeaturePlugin:

- schema() returns feature names and dtypes;
- compute(doc) yields a sparse/compact feature vector;
- Registration via entry points or a plugins folder.

6.3 CLI

```
lmda run --config config.yaml --input corpus/ --output artifacts/
lmda visualise --project my_project.lmda
```

6.4 Optional REST API (FastAPI)

- POST /v1/projects: create project
- POST /v1/projects/id/ingest: upload texts/metadata
- POST /v1/projects/id/run: execute pipeline
- GET /v1/projects/id/scores: factor scores
- GET /v1/projects/id/loadings: factor loadings
- GET /v1/projects/id/report: PDF/HTML report

7 Security and Privacy Considerations

7.1 Data Protection

- Local-first processing; no external calls by default;
- Optional at-rest encryption for project files; secure temp directories;
- Configurable redaction of personally identifiable information (PII) in exports.

7.2 Access Control (Server Mode)

- Authentication (OAuth2/JWT) and role-based access control (RBAC);
- TLS enforcement; secure headers and CSRF protections for Web GUI (if used).

7.3 Supply Chain

- Pin dependencies; verify wheels; use vulnerability scanning (pip-audit, Safety);
- Sandboxed plug-ins with permission checks.

8 Risks and Mitigations

- R1: Model interpretability Factors may be hard to interpret.
 Mitigation: Offer rotations, feature contribution charts, and glossary tooltips.
- R2: Performance on large corpora High memory/CPU usage.

 Mitigation: Sparse structures, incremental processing, caching, chunked I/O.
- R3: NLP model availability spaCy models not installed.
 Mitigation: Guided download, fallback tokenisers, graceful degradation.
- R4: Data privacy Sensitive texts accidentally exported.
 Mitigation: Local-first defaults, explicit consent prompts, export redaction.
- R5: Cross-platform GUI quirks Rendering differences.

 Mitigation: UI testing matrix, use of Qt styles, theming validation.
- **R6:** Reproducibility drift Version changes affect outputs. *Mitigation*: Lockfiles, artifact versioning, seeds, environment capture.

9 Timeline and Milestones

1. Week 1-2: Foundations

Project scaffolding, env setup, CI/CD, basic data model, configuration schema;

2. Week 3-4: Preprocessing

Language detection, tokenisation, lemmatisation, POS tagging; caching;

3. Week 5-6: Features

Core lexical metrics, function word profiles, POS n-grams; plug-in API;

4. Week 7-8: Modeling

PCA/EFA pipeline, rotations, persistence; basic CLI;

5. Week 9-10: GUI v1

Data loading, configuration panels, 2D scatter, scree and loadings plots;

6. Week 11-12: Reporting & Export

CSV/JSON exports, PDF/HTML reports; theming and preferences;

7. Week 13-14: Hardening

Performance tuning, testing, error handling, documentation;

8. Week 15+: Optional Server Mode

FastAPI endpoints, auth/TLS, Docker packaging.

References

Berber Sardinha, T., & Fitzsimmons-Doolan, S. (2025). *Lexical Multi-Dimensional Analysis: Identifying Discourses and Ideologies*. Cambridge: Cambridge University Press.

Biber, D. (1988). Variation across speech and writing (1st ed.). Cambridge: Cambridge University Press.

A Appendices

A.1 work in progress