"Pay As You Park" Smart Parking Solution

2021-198

SLIIT
FACULTY OF COMPUTING

Student Information

Student ID	Student Name	Presentation Slides
IT18012552	M.D.S.M. Antany	Validate the parking yards standard and suggest the solution for parking yards
IT18154672	Priyankara A.D.D	Introduction and Find the availability of free spaces inside parking yard
IT18013092	Aadil M.R.M	Suggest and direct to most suitable parking yard for user
IT18013924	Ferreira L.V	Internal navigation in parking yards

Introduction

WHAT IS SMART PARKING ?

DOES CURRENT SOCIETY NEED A SMART PARKING SOLUTION?

Research Problem

- Existing payment process in parking systems

- Hardness to find a parking yard to park
- Difficulty of navigation inside parking yards



- Difficulty of measuring parking yards standard without human interaction

Objectives

- Introduce "pay as you park" concept to the parking system.
- Support users to find the most suitable parking yard
- Provide the best experience in parking using smart technology

Research Components

- Find the availability of free spaces inside parking yard
- Suggest and direct to most suitable parking yard for user
- Internal navigation in parking yards
- Measuring parking yards standard and validate suitability before the yard registration

System Diagram



IT18154672 | PRIYANKARA A. D. D.

Software Engineering

INTRODUCTION

- Research Problem
- Research Gap
- Objectives

RESEARCH QUESTION

- What is the cost-friendly and accurate alternative to identify car parking spaces in a parking slot?



OBJECTIVES

- Identifying vacant parking slots in a parking lot.

SUB OBJECTIVES

- Save time of the user by pre-identifying vacant spaces.

- Send the processed data for the further process.



RESEARCH METHODOLOGY

- System Diagram
- Technologies used

SYSTEM DIAGRAM



TECHNOLOGIES USED

- Identifying vacant/available parking spaces
- Number of vehicles detection
  - RestNet 50 CNN - (Convolutional Neural Networks) with
- REST APIs
  - Express JS with MongoDB

EVIDENCE OF COMPLETION

```
% train the cubic SVM classifier with 5-fold cross validation, should take
% 6 seconds to train the classifier

tic
% using 5 fold cross validation in the model
[trainedClassifier, validationAccuracy, validationPredictions] =...
    trainClassifier(training_matrix);
toc
```

```
Elapsed time is 4.712597 seconds.
```

```
disp('Training finished for the SVM classifier')
```

```
Training finished for the SVM classifier
```

```
% display the cross-validation accuracy of the trained classifier for the training data
fprintf('The validation accuracy of the classifier %f %%.\n',validationAccuracy*100);
```

```
The validation accuracy of the classifier 99.833333 %.
```

EVIDENCE OF COMPLETION

EVIDENCE OF COMPLETION

REFERENCES

[1] Sukumar, M. B., Sireesha, G., Ashok, A., Mounish, G., & Prathap, D. Real Time Image Processing Based Vacant Car Parking Occupancy Information System.

[2] Nwave, (2021), Advantages and Disadvantages of Smart Parking Sensors | Nwave [Online] Available: https://www.nwave.io/news/pros-and-cons-of-smart-parking-systems/ [Accessed 20 Feb 2021]

[3] Paidi, V., Fleyeh, H., Håkansson, J., & Nyberg, R. G. (2018). Smart parking sensors, technologies and applications for open parking lots: a review. *IET Intelligent Transport Systems*, *12*(8), 735-741.

[4] PcMag, (2021), Definition of smart parking | PCMag [Online] Available: https://www.pcmag.com/encyclopedia/term/smart-parking#:~:text=A%20vehicle%20parking%20system%20that,incoming%20drivers%20to%20available%20locations.&text=With%20the%20Smart%20Park%20system,car%2C%20smart%20home%20and%20smart [Accessed 20 Feb 2021]

[5] Gunasekara, G. G. Y. U., Gunasekara, A. D. A. I., & Kathriarachchi, R. P. S. (2015). A Smart Vehicle Parking Management Solution.

[6] Karunarathne, M. S., & Nanayakkara, L. D. J. F. (2014). A Prototype to Identify Availability of a Car in a Smart Car Park with Aid of Programmable Chip and Infrared Sensors. *Journal of Emerging Trends in Computing and Information Sciences*, *5*(2).

[7] Nandyal, S., Sultana, S., & Anjum, S. (2017). Smart car parking system using arduino uno. *International Journal of Computer Applications*, *975*(169), 1.

[8] Bachani, M., Qureshi, U. M., & Shaikh, F. K. (2016). Performance analysis of proximity and light sensors for smart parking. Procedia Computer Science, 83, 385-392.

[9] Britannica, (2021), Image processing | computer science | Britannica [Online] Available: https://www.britannica.com/technology/image-processing [Accessed 21 Feb 2021]

[10] True, N. (2007). Vacant parking space detection in static images. University of California, San Diego, 17, 659-662.

[11] Ichihashi, H., Notsu, A., Honda, K., Katada, T., & Fujiyoshi, M. (2009, August). Vacant parking space detector for outdoor parking lot by using surveillance camera and FCM classifier. In 2009 IEEE International Conference on Fuzzy Systems (pp. 127-134). IEEE.

IT18013092 | AADIL M.R.M

Software Engineering

INTRODUCTION

- Research Question
- Specific and Sub Objectives

RESEARCH PROBLEM

- Problems faced by the drivers when finding a parking yard.
- How does it affect the society ?
- How does it affect the environment ?

Objectives

- Identify the nearest parking yard around user/user destination.
- Suggest optimal parking yard to park the vehicle based on key factors.
- Provide a cross platform mobile app to perform the task

RESEARCH METHODOLOGY

SYSTEM DAIGARM

TECHNOLOGY AND TECHNIQUES USED

SYSTEM DIAGRAM



TECHNOLOGY AND TECHNIQUES USED

- Retrieving the current location of user
  - GPS related technology
  - Google Map API – visualize the location
- Suggest optimal parking yard to park the vehicle based on key factors
  - Machine learning algorithms : SARIMA
  - Haversine Algorithm
  - Google Map API – visualize the locations and directions

EVIDENCE FOR THE COMPLETION

Haversine Imp

suggest_nearest_yard.ipynb

File Edit View Insert Runtime Tools Help Last saved at 5 July

+ Code + Text

```
parkin_yards = parkin_yards.rename(columns={'X':'lat','Y':'lon'})

parkin_yards.head()
```

	ID	lat	lon	Name	address	no of slots
0	P1	79.882664	6.914951	LOLC Car Park	21, 25 Chandraleka Mawatha, Colombo 00800	120
1	P2	79.876301	6.883533	Best Western Elyon Colombo	Baseline Road, 102A Kirulapone Ave, Colombo 00500	75
2	P3	79.850030	6.933701	Fort	Fort, Colombo	100
3	P4	79.864816	6.928458	Maradana Railway Station	Jayantha Weerasekara Mawatha, Colombo 01000	225
4	P5	79.870644	6.879944	Tenaga Carparks (Pvt)Ltd	Level 4, 124 Maya Ave, Colombo 00500	300

Haversine Formula

```
from math import radians, cos, sin, asin, sqrt
def dist(lat1, long1, lat2, long2):
    # convert decimal degrees to radians
    lat1, long1, lat2, long2 = map(radians, [lat1, long1, lat2, long2])
    # haversine formula
    dlon = long2 - long1
    dlat = lat2 - lat1
    a = sin(dlat/2)**2 + cos(lat1) * cos(lat2) * sin(dlon/2)**2
    c = 2 * asin(sqrt(a))
    # Radius of earth in kilometers is 6371
    km = 6371* c
    return km

def find_nearest(lat, long):
    distances = parkin_yards.apply(
        lambda row: dist(lat, long, row['lat'], row['lon']),
        axis=1)
    return parkin_yards.loc[distances.idxmin(), 'ID']

find_nearest(79.876301,6.883533)
```

'P2'

Double-click (or enter) to edit

Dataset Pattern Overview

jupyter DataSetPatternOverview Last Checkpoint: Last Saturday at 22:20 (autosaved)

File Edit View Insert Cell Kernel Widgets Help

Run Code

In [1]:
```
# Import libraries and custom functions defined in Workbook_Init.py
from initial import *

df_raw = pd.read_csv('./dataset.csv')
df_raw.head(10)
```

Out[1]:

	parking_yard_id	capacity	occcupancy	last_update
0	BHMBCCMKT01	577	61	10/4/2016 7:59
1	BHMBCCMKT01	577	64	10/4/2016 8:25
2	BHMBCCMKT01	577	80	10/4/2016 8:59
3	BHMBCCMKT01	577	107	10/4/2016 9:32
4	BHMBCCMKT01	577	150	10/4/2016 9:59
5	BHMBCCMKT01	577	177	10/4/2016 10:26
6	BHMBCCMKT01	577	219	10/4/2016 10:59
7	BHMBCCMKT01	577	247	10/4/2016 11:25
8	BHMBCCMKT01	577	259	10/4/2016 11:59
9	BHMBCCMKT01	577	266	10/4/2016 12:29

In [2]:
```
df_clean = df_raw.copy()
df_clean.last_update = df_clean.last_update.astype('datetime64')
df_clean['PercentOccupied'] = df_clean.occcupancy / df_clean.capacity
df_clean['date'] = df_clean.last_update.dt.date
df_clean['dayofweek'] = df_clean.last_update.dt.dayofweek
df_clean['date_time_halfhour'] = df_clean.last_update.dt.round('30min')
df_clean['time'] = df_clean.date_time_halfhour.dt.time
```

EVIDENCE FOR THE COMPLETION

SARIMA Model

jupyter parking_availability Last Checkpoint: a day ago (autosaved)

Logout

File Edit View Insert Cell Kernel Widgets Help

Trusted Python 3

Run Code

```
# print('-'*77)
# print('ARIMA Model Metrics on Test Data')
# print('='*77)
# report_metrics(test.squeeze(), y_pred_AR.squeeze())
```

In [27]:
```
%%time
# Define and fit SARIMA model
my_seasonal_order = (1, 1, 1, 48)
sarima_model = SARIMAX(train, order=(1, 0, 1), seasonal_order=my_seasonal_order)
results_SAR = sarima_model.fit(disp=-1)
```

```
C:\Users\moham\anaconda3\lib\site-packages\statsmodels\tsa\base\tsa_model.py:524: ValueWarning: No frequency information was pr
ovided, so inferred frequency 30T will be used.
  warnings.warn('No frequency information was'
C:\Users\moham\anaconda3\lib\site-packages\statsmodels\tsa\base\tsa_model.py:524: ValueWarning: No frequency information was pr
ovided, so inferred frequency 30T will be used.
  warnings.warn('No frequency information was'
```

```
Wall time: 1min 52s
```

In [28]:
```
plt.figure(figsize=(16,6))
plt.title('SARIMA Model on Aggregate Data')
plt.plot(train, label='Training Actual Occupancy Rate')
plt.xlabel('Date')
plt.ylabel('Percent Occupied')
y_pred_sar = pd.Series(results_SAR.forecast(steps=len(test)).values, index=test.index)
plt.plot(test, label='Testing Actual Occupancy Rate')
plt.plot(y_pred_sar, color='red', label='SARIMA Predicted Occupancy Rate')
plt.legend()

plt.show()
```

EVIDENCE FOR THE COMPLETION

SARIMA Forecasting

jupyter parking_availability Last Checkpoint: a day ago (autosaved)

Logout

File Edit View Insert Cell Kernel Widgets Help

Trusted Python 3

Run Code

```
print('SARIMA Model Metrics on Test Data')
print('='*77)
report_metrics(test.squeeze(), y_pred_sar.squeeze())
```




```
--------------------------------------------------------------------------------
SARIMA Model Metrics on Test Data
================================================================================
Explained Variance:
        0.9965519017195572
MAE:
        0.007079906357941675
```

IT18013924 | FERREIRA L.V.

Software Engineering

INTERNAL PARKING NAVIGATION INSIDE A PARKING AREA

INTRODUCTION

- What is a parking and an Internal Navigation inside a parking area?
- Indoor/outdoor parking areas.
- Why use Beacon technology and its advantages.

OBJECTIVES

- Identify the user's position
- View user's position in a map
- Show users path to free parking slots

METHODOLOGY

- Models Created (NN Model)
- Accuracy of these Models
- How to show predicted location in a map

SYSTEM DIAGRAM AND COMPONENT FLOW



System Diagram



Component Flow

TECHNOLOGY AND TECHNIQUES TO BE USED

- Identify the User's Position
  - ➢ Beacons
  - ➢ Calculate Distance of the Beacons(by getting RSSI values)
  - ➢ Machine learning algorithms : Nural Network(Sequential)
  - ➢ Pass image of the map and show user's position
  - ➢ Show path to the destination(free slot)

COMPLETION OF THE COMPONENT

- Trained the Model
- Dummy Map which can show User Position
- Method Implemented to get position of a user
  when give three beacon distances to user as input
  Parameters
- Implement a Code to calculate the distance by using Beacon Bluetooth RSSI Values
- Used Kalman Filter to get more Accurate RSSI value
- Implement a way to show the path from user to the destination
- Design All the UIs and Databases (API used with dio to retrieve data from mongo db)

FUTURE WORK

- Identify the stories of a building by using Beacons.
- Integrate the Application

EVIDENCE FOR THE COMPLETION

Model Predicts Position Y



jupyter creating the model for Y Last Checkpoint: 4 hours ago (autosaved)

```
In [1]: import pandas as pd
        dataset=pd.read_csv('beacon_readings.csv').values

In [2]: data=dataset[:,0:3]

In [3]: #to predictt Y
        target=dataset[:,4]
        from keras.utils import np_utils

        categorized_target=np_utils.to_categorical(target)
```

```
C:\Users\Administrator\anaconda3\envs\newenv1\lib\site-packages\h5py\__init__.py:36: FutureWarning: Conversion of the second argument of issubdtype from `float` to `np.floating` is deprecated. In future, it will be treated as `np.float64 == np.dtype(float).type`.
  from ._conv import register_converters as _register_converters
Using TensorFlow backend.
```

```
In [4]: from sklearn.model_selection import train_test_split

        train_data,test_data,train_target,test_target=train_test_split(data,categorized_target,test_size=0.1)

In [5]: from keras.models import Sequential
        from keras.layers import Dense

        model=Sequential()
        model.add(Dense(64,input_dim=3,activation='relu'))
        model.add(Dense(32,activation='relu'))
        model.add(Dense(224,activation='softmax'))

        model.compile(loss='categorical_crossentropy',optimizer='adadrad',metrics=['accuracy'])

In [6]: model.fit(train_data,train_target,epochs=200,validation_split=0.1)
```

```
Train on 202 samples, validate on 23 samples
Epoch 1/200
202/202 [==============================] - 0s 2ms/step - loss: 4.6882 - acc: 0.2970 - val_loss: 3.3484 - val_acc: 0.4348
Epoch 2/200
```




```
202/202 [==============================] - 0s 79us/step - loss: 0.9524 - acc: 0.5941 - val_loss: 0.7917 - val_acc: 0.7391
Epoch 8/200
202/202 [==============================] - 0s 89us/step - loss: 0.9447 - acc: 0.5941 - val_loss: 0.8248 - val_acc: 0.7391
Epoch 9/200
202/202 [==============================] - 0s 89us/step - loss: 0.9397 - acc: 0.5941 - val_loss: 0.7696 - val_acc: 0.7391
Epoch 10/200
202/202 [==============================] - 0s 89us/step - loss: 0.9290 - acc: 0.5941 - val_loss: 0.7544 - val_acc: 0.7391
Epoch 11/200
202/202 [==============================] - 0s 74us/step - loss: 0.9261 - acc: 0.5941 - val_loss: 0.7423 - val_acc: 0.7391
Epoch 12/200
202/202 [==============================] - 0s 74us/step - loss: 0.9210 - acc: 0.5941 - val_loss: 0.8027 - val_acc: 0.7391
Epoch 13/200
202/202 [==============================] - 0s 74us/step - loss: 0.9176 - acc: 0.5941 - val_loss: 0.7401 - val_acc: 0.7391
Epoch 14/200
202/202 [==============================] - 0s 74us/step - loss: 0.9127 - acc: 0.5941 - val_loss: 0.7564 - val_acc: 0.7391
```

```
In [7]: import numpy as np
        predicted_target=model.predict(test_data)
        print(np.argmax(predicted_target,axis=1))
```

```
[180 180 137 223 223 180 223 180 180 180 180 223 180 137 137 137 180 180
 223 180 180 223 180 137 137]
```

```
In [8]: print(np.argmax(test_target,axis=1))
```

```
[180 180 137 223 223 180 223 223 180 223 180 223 180 137 137 137 223 180
 223 180 180 223 180 137 137]
```

```
In [9]: from sklearn.metrics import accuracy_score

        accuracy=accuracy_score(np.argmax(test_target,axis=1),np.argmax(predicted_target,axis=1))
        print(accuracy)
```

```
0.88
```

```
In [10]: model.save_weights('y_weights.h5')  #to save only weights
         model.save('y.model')  #to save the whole model
```

EVIDENCE FOR THE COMPLETION

Model Predicts Position X



```
In [1]:
import pandas as pd

dataset=pd.read_csv('beacon_readings.csv').values

In [2]:
data=dataset[:,0:3]

In [3]:
#to predictt X
target=dataset[:,3]
from keras.utils import np_utils

categorized_target=np_utils.to_categorical(target)

C:\Users\Administrator\anaconda3\envs\newenvt\lib\site-packages\h5py\__init__.py:36: FutureWarning: Conversion of the second argument of issubdtype from `float` to `np.floating` is deprecated. In future, it will be treated as `np.float64 == np.dtype(float).type`.
  from ._conv import register_converters as _register_converters
Using TensorFlow backend.

In [4]:
from sklearn.model_selection import train_test_split

train_data,test_data,train_target,test_target=train_test_split(data,categorized_target,test_size=0.1)

In [5]:
from keras.models import Sequential
from keras.layers import Dense

model=Sequential()
model.add(Dense(64,input_dim=3,activation='relu'))
model.add(Dense(32,activation='relu'))
model.add(Dense(166,activation='softmax'))

model.compile(loss='categorical_crossentropy',optimizer='adadrad',metrics=['accuracy'])

In [6]:
model.fit(train_data,train_target,epochs=200,validation_split=0.1)

Train on 202 samples, validate on 23 samples
Epoch 1/200
202/202 [==============================] - 0s 718us/step - loss: 4.0376 - acc: 0.4752 - val_loss: 2.6483 - val_acc: 0.4348
```



```
Epoch 54/200
202/202 [==============================] - 0s 74us/step - loss: 0.5823 - acc: 0.6337 - val_loss: 0.6688 - val_acc: 0.7391
Epoch 55/200
202/202 [==============================] - 0s 64us/step - loss: 0.5758 - acc: 0.7475 - val_loss: 0.6697 - val_acc: 0.7391
Epoch 56/200
202/202 [==============================] - 0s 79us/step - loss: 0.5717 - acc: 0.6782 - val_loss: 0.6696 - val_acc: 0.6957
Epoch 57/200
202/202 [==============================] - 0s 74us/step - loss: 0.5651 - acc: 0.6832 - val_loss: 0.6775 - val_acc: 0.6957
Epoch 58/200
202/202 [==============================] - 0s 64us/step - loss: 0.5601 - acc: 0.6733 - val_loss: 0.6594 - val_acc: 0.8261
Epoch 59/200
```

```
In [8]:
import numpy as np
predicted_target=model.predict(test_data)
print(np.argmax(predicted_target,axis=1))

[137 180 180 137 180 180 223 180 137 137 180 180 137 137 223 223 223 137
 223 180 180 180 180 180 223]

In [9]:
print(np.argmax(test_target,axis=1))

[137 180 180 137 180 180 223 180 137 137 180 180 137 137 223 223 223 137
 223 180 180 180 180 180 223]

In [10]:
from sklearn.metrics import accuracy_score

accuracy=accuracy_score(np.argmax(test_target,axis=1),np.argmax(predicted_target,axis=1))
print(accuracy)

1.0

In [11]:
model.save_weights('y_weights.h5')  #to save only weights
model.save('y.model')  #to save the whole model

In [12]:
model.save('modelY.pkl')

In [ ]:
```

EVIDENCE FOR THE COMPLETION

Implemented method to get position



EVIDENCE FOR THE COMPLETION

Main User Interface



Main User Interface – Toast Message



User Guide

Image of the parking Area

Dropdown to Select the Parking Slot

Toast message will be shown if the user does not select the parking slot

EVIDENCE FOR THE COMPLETION

Navigation UI





User Guide

User's position is shown on the map with the slots

Red Color Slots – Unavailable Parking Slots

Green Color Slots – Available Parking Slots

EVIDENCE FOR THE COMPLETION

Implemented Model API using Flask



```
import numpy as np
from keras.models import load_model
from flask import Flask, request, jsonify

app = Flask(__name__)
model_x = load_model('x.model')
model_y = load_model('y.model')


def give_predictions(input_array):
    prediction = {}
    # get x value
    predicted_x = np.argmax(model_x.predict(np.array(input_array).reshape(1, 3, )))

    # get y value
    predicted_y = np.argmax(model_y.predict(np.array(input_array).reshape(1, 3, )))

    prediction['x'] = predicted_x
    prediction['y'] = predicted_y

    return prediction

    # print(give_predictions([0.877462, 0.768608, 1.457214]))


@app.route('/api', methods=['GET'])
def position():
    dict = {}
    user_input_a = str(request.args['beacon_a'])
    user_input_b = str(request.args['beacon_b'])
```



```
    dict = {}
    user_input_a = str(request.args['beacon_a'])
    user_input_b = str(request.args['beacon_b'])
    user_input_c = str(request.args['beacon_c'])

    print("inputs: " + user_input_a, user_input_b, user_input_c)

    value_float_a = float(user_input_a)
    value_float_b = float(user_input_b)
    value_float_c = float(user_input_c)

    beacon_array = [value_float_a, value_float_b, value_float_c]
    print(beacon_array)
    print("################################################")
    prediction = give_predictions(beacon_array)

    print(prediction)
    print("************************************************")
    dict['output'] = prediction
    print(dict)
    return [dict]


if __name__ == '__main__':
    app.run(debug=False, threaded=False)
```

EVIDENCE FOR THE COMPLETION

Implemented MongoDB access API

Slots Retrieve API Implementation



Indoor Location API Implementation





IT18012552 | M.D.S.M. ANTANY

Software Engineering

MEASURING PARKING YARDS STANDARD AND VALIDATE SUITAB BEFORE THE YARD REGISTRATION

RESEARCH QUESTION

How to identify a standard parking yard without time wasting and a without human interaction before registration?

- Reviewing thousands of parking registration forms by a human is time consuming
- Registration process is too complicated
- Inability to audit the parking yard condition without man power (monthly or annually)

MAIN OBJECTIVE

Identify the parking yard surface type and Quality of the surface before registering to the system as a valid parking yard

SUB OBJECTIVES

- Identify the parking yard surface type
- Identify the quality of the parking yard surface under the surface type

Research Methodology

- SYSTEM DAIGARM
- TECHNOLOGY AND TECHNIQUES USED

SYSTEM OVERVIEW DIAGRAM



SYSTEM FLOWCHART DIAGRAM



TECHNOLOGY AND TECHNIQUES USED

- Used Road Traversing Knowledge (RTK) Dataset
- Region of Interest (ROI) is defined as a pre-processing step for each input frame
- The data augmentation consists of increasing and decreasing the brightness in each frame
- Input images are passed to the CNN structure containing three convolution layers and two fully connected layers.
- The flatten layer is used to transform the convolution multi-dimensional tensor into a one-dimensional tensor.
- Model training divided to two parts
    - Parking surface type model
    - Parking surface quality model

MODEL ARCHITECTURE



EVIDENCE FOR COMPLETION



Parking surface quality classification Model training

EVIDENCE FOR COMPLETION



Surface and quality measurement image output

EVIDENCE FOR COMPLETION



Model deployed on Heroku

EVIDENCE FOR COMPLETION



Parking owner login to pay as you park web application

EVIDENCE FOR COMPLETION



CNN Parking Surface Classification model integrated new parking places registration view and the Owner's dashboard

REFERENCES

[1]. M. M. Forrest, Z. Chen, S. Hassan, I. O. Raymond and K. Alinani, "Cost Effective Surface Disruption Detection System for Paved and Unpaved Roads," in IEEE Access, vol. 6, pp. 48634-48644, 2018, doi: 10.1109/ACCESS.2018.2867207.

[2]. Nienaber, S & Booysen, M.J. (Thinus) & Kroon, Rs. (2015). Detecting Potholes Using Simple Image Processing Techniques and Real-World Footage. 10.13140/RG.2.1.3121.8408.

[3]. Taluja, Chandan & Thakur, Ritula. (2018). An Intelligent Model for Indian Soil Classification using various Machine Learning Techniques. 2250-3005.

[4]. Mahmoodi-Eshkaftaki, M., Haghighi, A., & Houshyar, E. (2019). Land Suitability Evaluation using Image Processing based on Determination of Soil Texture-Structure and Soil Features. Soil Use and Management. doi:10.1111/sum.12572

[5]. Bennett, Jordan. (2019). Smart (Ai) Pothole Detector (Powered by "Tensorflow/TensorRT" on "Google Colab" and or "Jetson Nano" via a Convolutional Artificial Neural Network).

Thank You !

Q & A