



Settings

Public Settings file `settings.json` will let you setup some info like team name, webhook url, server listen address, and more

This config controls how your Parking Simulator server runs and communicates:

- `ListenAddress` : Address and port where the simulator server listens. `0.0.0.0` means accept connections from any network interface on port `9898`.
- `WebhookUrl` : URL where the simulator sends parking events, such as car entry, payment, exit, failures, etc.
- `GameSpeedMultiplier` : Simulation speed multiplier. `1` = normal speed, it affect whole game speed. used to increase simulator testing speed, it will affect the `ParkingSpeedMultiplier` also since it is the main speed multiplier.
- `ParkingSpeedMultiplier` : Parking time speed multiplier. it only affect the time measured for car at entry/park/exit. so you don't need to wait much if doing tests.
- `TeamName` : Name identifying the participating team.
- `MinParkingTime` : Minimum randomly assigned parking duration (minutes).
- `MaxParkingTime` : Maximum randomly assigned parking duration (minutes).
- `Name` : Username used to login to the Parking Simulator server.
- `Password` : Password used together with `Name` to login to the Parking Simulator server.

```
{ "ListenAddress": "http://0.0.0.0:9898", "WebhookUrl":  
"http://www.carparking.local/webhook.php", "ParkingSpeedMultiplier": 1,  
"GameSpeedMultiplier":1, "TeamName": "NewTeam X", "MinParkingTime": 1,  
"MaxParkingTime": 5, "Name": "admin", "Password": "admin" }
```