



QuikStor Management System Integration API

October 16, 2024

Non-disclosure warning

By reading this integration specification, you agree to only share the following information with direct employees of their company and to make all reasonable effort to prevent release to unauthorized persons without QuikStor's written consent.

Contents

Non-disclosure warning	1
1 General usage	3
1.1 Introduction	3
1.2 Sending requests	3
1.3 Responses	4
1.4 Pagination	5
2 Authentication	7
2.1 Retrieving Access Token using Client Credentials	8
2.2 Retrieving Access Token using Refresh Token	8
3 API Endpoints	9
3.1 List Company Facilities	9
3.1.1 Model Details (List Company Facilities)	10
3.1.2 Examples (List Company Facilities)	11
3.2 Read Facility Details	12
3.2.1 Model Details (Read Facility Details)	13
3.2.2 Examples (Read Facility Details)	14
3.3 List Facility Lead Sources	15
3.3.1 Model Details (List Facility Lead Sources)	15
3.3.2 Examples (List Facility Lead Sources)	16
3.4 List Available Unit Groups	17
3.4.1 Model Details (List Available Unit Groups)	18
3.4.2 Examples (List Available Unit Groups)	19
3.5 Read Unit Groups Unit Reservation Settings	20
3.5.1 Model Details (Unit Groups Unit Reservation Settings)	20
3.5.2 Examples (Read Unit Groups Unit Reservation Settings)	20
3.6 Reserve a Unit from Unit Group Listing	21
3.6.1 Model Details (Reserve a Unit from Unit Group Listing)	21
3.6.2 Examples (Reserve a Unit from Unit Group Listing)	23
Appendix	23
A Facility Amenities	24
B Unit Group Features	26

Chapter 1

General usage

1.1 Introduction

The QuikStor Management System Integration API allows the integrating party to interface with the QuikStor Property Management System in order to retrieve data and trigger actions. It is a collection of REST API Endpoints.

Every endpoint is executed in the context of a specific single property (later called facility) identified by a pair of: Company Code and Facility Code, provided in the request URL. A single set of integration partner credentials may allow access to a number of specific endpoints for one or several specific facilities, and not necessarily the same endpoints for each of accessible facilities. The exact scope of access is defined by the profile of the integration and access required to fulfill the role of the integration.

For example, your set of credentials may allow you to access one endpoint in facility A and also several endpoints in facility B.

As an integration partner you will be provided with a list of endpoints and facilities to which your credentials grant access to.

1.2 Sending requests

Requests are sent to specific endpoints via the HTTP protocol. Encryption (via HTTPS) is mandatory for all requests.

Each endpoint has a designated URL and a HTTP method, a combination of those two uniquely identifying a single endpoint. All endpoints require a resource target to be provided in the URL in the form of Company Code and Facility Code. These are always specific sections of the URL following an expected format.

Every request must be authorized. In order for a request to pass authorization, an access token should be provided in the request Authorization header. For more details, please see section 2. Authentication.

An example URL, that can be found in this documentation:

```
/api/v1/companies/{companyCode}/facilities/{facilityCode}/[...]
```

In order to be used, needs {companyCode} and {facilityCode} substituted with appropriate Company and Facility Codes. If we use an example Company Code "test" and Facility Code "west", we end up with the following URL:

```
/api/v1/companies/test/facilities/west/[...]
```

The above URL points at an endpoint to be executed in context of the facility with Facility Code "west" belonging to a company with Company Code "test".

Some endpoints require additional request data to be provided as: a) query parameters, or b) in the body of the request. These two ways of request data provision are not interchangeable: endpoint-specific query parameters may only be provided as query parameters, and request body data may only be provided in the body of the request. Endpoint request data provision details are specified in this document, individually for each endpoint (see: section 3. API Endpoints). Request Data provided in the body of the request must be provided in the JSON document format.

Request property	Is it required?	Notes
Encryption via HTTPS	Required	—
Endpoint HTTP Method	Required	Required together with Endpoint URL to uniquely identify the endpoint.
Endpoint URL	Required	Required together with Endpoint HTTP Method to uniquely identify the endpoint.
Company Code and Facility Code	Required	Required to be present in the URL.
Authorization Header	Required	See section 2. Authentication.
Content-Type Header	Required if data in request body is present	The header value must be application/json
Query parameters	Varies by endpoint	Must be URL-encoded
Request body	Varies by endpoint	JSON document format

Table 1.1: Table summarizing required request protocol and format.

1.3 Responses

All endpoint responses are standard HTTP responses containing the appropriate HTTP Status Code and response body. Some endpoints may result in HTTP Status Code 204 — No Content, in which case the response body will not be present. In all other success or failure cases, the request body will be present in JSON document format and contain response information in case of success, or extended failure details in case of failure.

Important: Unless otherwise specified all elements in all response models should be considered optional — they may be not present in the response. Which elements are available depends on the individual resource being accessed (i.e. Facility or Unit Group).

HTTP Status Code	Success?	Notes
200 — OK	Yes	Response body contains the expected results for the given request in JSON document format.
204 — No Content	Yes	No response body will be present for responses of this kind.
400 — Bad Request	No	Request invalid. Body may be malformed or missing required model properties. Response body may contain specific details.
401 — Unauthorized	No	Authentication problem. Please make sure you are following the steps in section 2. Authentication.
403 — Forbidden	No	Authorization problem. You may be trying to access an endpoint to which you do not have permissions to.
404 — Not Found	No	The resource you are trying to access could not be found. Please make sure the URL you are specifying is correct. Response body may contain more details.
409 — Conflict	No	A response of this type indicates that the request could not have been fulfilled as fulfilling it would have violated some business rule. Refer to the response body for details.

Table 1.2: Possible response HTTP status codes.

1.4 Pagination

Some endpoints which respond with a list result support pagination — that is, querying only a fraction of result models. The queried values are ordered (sortBy parameter), split into ordered pages, each containing a specified number of models in order (size parameter) and only one of the pages is retrieved (page parameter, 0-indexed).

Pagination extends each endpoint that supports it and all requests to such endpoints accept three additional query parameters as visible in table 1.3. Paginated endpoint query parameters.

Responses of endpoints supporting pagination also follow a standard format, documented in table 1.4. Standard response format for endpoints supporting pagination.

Example request with pagination query parameters present:

```
/facilities/west/lead-sources?sortBy=id%3AASC%3Bname%3ADESC&Page=0&Size=10
```

Example response:

```
1 {
2   "totalCount": 3,
3   "results": [
4     {
5       "id": "798e06d1-9683-4c47-b848-207d825ad795",
6       "name": "Walk-in",
7     },
8     {
9       "id": "7d2bf977-ea58-4777-b038-739cf6bdad46",
10      "name": "Call center",
11    },
12    {
13      "id": "146fd2f1-b2e9-4ecf-97ff-504837b7f61a",
14      "name": "Ad campaign"
15    }
16  ],
17  "size": 10,
18  "page": 0
19 }
```

Name	Type	Example value
SortBy	string of semicolon-separated sort properties. Each consisting of property name, a colon and order: ASC for ascending or DESC for descending	Id:ASC;Name:DESC
Page	integer, 0-indexed	0
Size	integer	10

Table 1.3: Paginated endpoint query parameters.

Element name	Type	Example value
TotalCount	integer	14
Results	list of items	["First", "Second", "Third"]
Size	integer	10
Page	integer, 0-indexed	0

Table 1.4: Standard response format for endpoints supporting pagination.

Chapter 2

Authentication

In order to gain access to the endpoints provided by the QuikStor Management System Integration API, each of your requests must be authorized. Requests are authorized by providing a valid Access Token in the Authorization header of each API request (see section 1.2. Sending requests).

Access Tokens are initially procured by validating your Client Credentials in the QuikStor Management System Integration API. Access Tokens remain valid for a limited time but may be renewed using Refresh Tokens. Refresh Tokens will also eventually expire, in which case credentials will have to be provided again in order to receive a new Access Token.

If the provided credentials are deemed valid, the response will indicate success (Http Status 200) and the resulting response body will be in Response Body format (see: Response body).

In case of a failure your credentials may be invalid, request format may be malformed, or a different problem may be occurring. Please see the 1.3. Responses section for basic troubleshooting.

2.1 Retrieving Access Token using Client Credentials

This method should be used to log in for the first time or when the Refresh Token has expired. If the Refresh Token has not yet expired, please use the 2.2. Retrieving Access Token using Refresh Token instead.

The following request should be sent:

Endpoint: `POST /api/login`

Request Header: `Content-Type: application/json`

Request Body:

```
1 {  
2   "grantType": "Client_Credentials",  
3   "clientId": specific string - your Integration Partner Credentials,  
4   "clientSecret": specific string - your Integration Partner Credentials  
5 }
```

Response Body:

```
1 {  
2   "token": string,  
3   "tokenType": "Access",  
4   "expiresIn": integer - seconds to expire,  
5   "refreshToken": string  
6 }
```

2.2 Retrieving Access Token using Refresh Token

This method should be used whenever a non-expired Refresh Token is available. If the Refresh Token has expired, please use the 2.1. Retrieving Access Token using Client Credentials method instead.

The following request should be sent:

Endpoint: `POST /api/login`

Request Header: `Content-Type: application/json`

Request Body:

```
1 {  
2   "grantType": "Refresh_Token",  
3   "refreshToken": specific string - the Refresh Token  
4 }
```

Response Body:

```
1 {  
2   "token": string,  
3   "tokenType": "Access",  
4   "expiresIn": integer - seconds to expire,  
5   "refreshToken": string  
6 }
```

Chapter 3

API Endpoints

3.1 List Company Facilities

This endpoint can be used to list all facilities belonging to a company. Please note that the facilities listed here are limited to what you, as an integration partner, are allowed to view, and will not include facilities that fall outside the scope of your integration.

The following request should be sent:

Endpoint: `GET /api/v1/companies/{companyCode}/facilities`

Request Body: None

Response Body:

```
1 [
2   {
3     "id": uuid,
4     "name": string,
5     "code": string,
6     "email": string,
7     "address": Address,
8     "phoneNumber": PhoneNumber
9   }
10 ]
```

3.1.1 Model Details (List Company Facilities)

Element name	Type	Notes
CountryCode	string	Including preceding plus symbol (i.e. "+1")
Number	string	Only digits. No spaces or special characters.
Type	specific string	Possible values: "Cell", "Office", "Home".

Table 3.1: [PhoneNumber](#) Model for 3.1. List Company Facilities.

Element name	Type	Notes
Id	uuid	—
Name	string	—
Code	string	—
Email	string, email	—
Address	Address model	See: Address model.
PhoneNumber	PhoneNumber model	See: PhoneNumber model.

Table 3.2: Response Model for 3.1. List Company Facilities

Name	Type	Notes
Street1	string	—
Street2	string	Additional address like a P.O. box.
City	string	—
PostalCode	string	—
State	string	—
Country	string	—
Latitude	double precision	In degrees; positive values are on Northern hemisphere.
Longitude	double precision	In degrees; positive values are on Eastern hemisphere.
TimeZone	specific string	Windows format i.e. "Pacific Standard Time".

Table 3.3: [Address](#) Model for 3.1. List Company Facilities.

3.1.2 Examples (List Company Facilities)

Example URL:

```
/api/v1/companies/test/facilities
```

Example Response Body:

```
1 {
2   "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
3   "name": "West API Facility",
4   "code": "west",
5   "email": "example@email.com",
6   "address": {
7     "street1": "123 Example Street",
8     "street2": "P.O. Box 12345",
9     "city": "Example City",
10    "postalCode": "12345",
11    "state": "Washington",
12    "country": "United States"
13  },
14  "phoneNumber": {
15    "countryCode": "+1",
16    "number": "1231231234",
17    "type": "Cell"
18  }
19 }
```

3.2 Read Facility Details

This endpoint can be used to retrieve detailed information about the facility, including exact address, phone number, tenant portal URL and amenities.

The following request should be sent:

Endpoint: `GET /api/v1/companies/{companyCode}/facilities/{facilityCode}`

Request Body: None

Response Body:

```
1 {  
2   "id": uuid,  
3   "name": string,  
4   "code": string,  
5   "email": string,  
6   "tenantPortalUrl": string,  
7   "address": Address,  
8   "phoneNumber": PhoneNumber,  
9   "amenities": Amenities  
10 }
```

3.2.1 Model Details (Read Facility Details)

Element name	Type	Notes
Id	uuid	—
Name	string	—
Code	string	—
Email	string, email	—
TenantPortalUrl	string, url	The Url to the facility's Tenant Portal.
Address	Address model	See: Address model.
PhoneNumber	PhoneNumber model	See: PhoneNumber model.
Amenities	list of Amenities items	See: Appendix A. Facility Amenities.

Table 3.4: Response Model for 3.2. Read Facility Details

Element name	Type	Notes
CountryCode	string	Including preceding plus symbol (i.e. "+1")
Number	string	Only digits. No spaces or special characters.
Type	specific string	Possible values: "Cell", "Office", "Home".

Table 3.5: [PhoneNumber](#) Model for 3.2. Read Facility Details.

Element name	Type	Notes
Street1	string	—
Street2	string	Additional address like a P.O. box.
City	string	—
PostalCode	string	—
State	string	—
Country	string	—
Latitude	double precision	Degrees with fractions. Positive values are on the Northern hemisphere.
Longitude	double precision	Degrees with fractions. Positive values are on the Eastern hemisphere.
TimeZone	specific string	Windows format i.e. "Pacific Standard Time".

Table 3.6: [Address](#) Model for 3.2. Read Facility Details.

3.2.2 Examples (Read Facility Details)

Example URL:

```
/api/v1/companies/test/facilities/west
```

Example Response Body:

```
1 {
2   "id": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
3   "name": "West API Facility",
4   "code": "west",
5   "email": "example@email.com",
6   "tenantPortalUrl": "https://portal.quikstor.com/en/test/west",
7   "address": {
8     "street1": "123 Example Street",
9     "street2": "P.O. Box 12345",
10    "city": "Example City",
11    "postalCode": "12345",
12    "state": "Washington",
13    "country": "United States"
14  },
15  "amenities": {
16    "availableHandcartsOrDollies": true,
17    "hasElevator": true,
18    "movingSuppliesForSale": true,
19    "videoCamerasOnSite": true,
20    "electronicGateAccess": true,
21    "fencedAndLighted": true,
22    "managerLanguages": [
23      "English",
24      "French",
25    ]
26  }
27 }
```

3.3 List Facility Lead Sources

Some endpoints (3.4. List Available Unit Groups or 3.6. Reserve a Unit from Unit Group Listing) may require an existing Lead Source to be provided in the request. This endpoint allows for reading all possible Lead Sources that may be used for these purposes. Note that Lead Sources available may vary per facility.

The following request should be sent:

Endpoint: `GET /api/v1/companies/{companyCode}/facilities/{facilityCode}`
(Continued) `/lead-sources`

Query Parameters: Pagination query parameters, see section 1.4. Pagination for details.

Request Body: None

Response Body:

```
1 {  
2   "totalCount": integer,  
3   "results": list of LeadSource,  
4   "size": integer - items per page,  
5   "page": integer, 0-indexed - number of the page to retrieve  
6 }
```

3.3.1 Model Details (List Facility Lead Sources)

Element name	Type
Id	uuid
Name	string

Table 3.7: [LeadSource](#) Model for 3.3. List Facility Lead Sources.

3.3.2 Examples (List Facility Lead Sources)

Example URL:

```
/api/v1/companies/test/facilities/west/lead-sources?Page=0&Size=10
```

Example Response Body:

```
1 {  
2   "totalCount": 3,  
3   "results": [  
4     {  
5       "id": "798e06d1-9683-4c47-b848-207d825ad795",  
6       "name": "Walk-in"  
7     },  
8     {  
9       "id": "7d2bf977-ea58-4777-b038-739cf6bdad46",  
10      "name": "Call center"  
11    },  
12    {  
13      "id": "146fd2f1-b2e9-4ecf-97ff-504837b7f61a",  
14      "name": "Ad campaign"  
15    }  
16  ],  
17  "size": 10,  
18  "page": 0  
19 }
```

3.4 List Available Unit Groups

This endpoint retrieves a list of available unit types with details on each of them including counts. If a special is available within the group, then the unit with lowest price including special will be selected as the unit with lowest price. In case of an available special both regular and discounted prices will be listed together with the name of the special.

Note: The URL supplied in response as "onlineMoveInUrl" can be appended with an optional query parameter "leadSourceId", with uuid value matching the id of a valid lead source id (See: 3.3.List Facility Lead Sources). Attaching a lead source to the request is optional and not required, but allows to override the otherwise default lead source with a specific one for move-ins initiated via this URL.

The following request should be sent:

Endpoint: `GET /api/v1/companies/{companyCode}/facilities/{facilityCode}`
(Continued) `/unit-groups`

Request Body: None

Response Body:

```
1 [
2   {
3     "unitGroupId": uuid,
4     "name": string,
5     "featuredFeatures": list of strings,
6     "features": list of Features,
7     "regularPrice": double precision,
8     "availableSpecial": AvailableSpecial,
9     "availableTotal": integer - count of units available,
10    "availableAtThisPrice": integer - count available at this price,
11    "totalInGroup": integer - count of ALL units in this group,
12    "reservedTotal": integer - count of reserved units in this group,
13    "areaInSquareFeet": double precision,
14    "onlineMoveInUrl": string, url
15  },
16  {
17    ...more list items...
18  }
19 ]
```

3.4.1 Model Details (List Available Unit Groups)

Element name	Type	Notes
SpecialId	uuid	Provided when reserving a unit. See: 3.6. Reserve a Unit from Unit Group Listing.
SpecialPrice	double precision	This is the promotional price for the first month. The price may apply for a longer duration. The value may be identical to regular price for specials that do not affect first month's pricing.
SpecialLabel	string	The special name to be presented to customers.

Table 3.8: [AvailableSpecial](#) Model for 3.4. List Available Unit Groups.

Element name	Type	Notes
UnitGroupId	uuid	—
Name	string	—
FeaturedFeatures	list of strings	Values listed may be unrelated to those present in the Features element.
Features	list of Features items	See: Appendix B. Unit Group Features.
RegularPrice	double precision	Non-promotional price.
AvailableSpecial	AvailableSpecial model	See: AvailableSpecial model.
AvailableTotal	integer	Count of units of this type available for rental.
AvailableAtThis-PriceTotal	integer	Count of units of this type available for rental at this price. If a special is available this is the count of units available at the promotional price.
TotalInGroup	integer	Count of all units in this group, including unavailable ones.
ReservedTotal	integer	Count of reserved units in this group. Reserved units are considered not available.
AreaInSquareFeet	double precision	Can be used to categorize units by size.
OnlineMoveInUrl	string, url	This is an URL that will redirect customers to the Tenant Portal with a unit of this kind pre-selected. See Note in endpoint description.

Table 3.9: Response Model for 3.4. List Available Unit Groups

3.4.2 Examples (List Available Unit Groups)

Example URL:

```
/api/v1/companies/test/facilities/west/unit-groups
```

Example Response Body:

```
1  [
2    {
3      "unitGroupId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
4      "name": "Covered Parking",
5      "featuredFeatures": [ "Covered Parking", "Pull-thru" ],
6      "features": {
7        "UnitType": "Parking",
8        "Width": "8",
9        "Depth": "20" },
10     "regularPrice": 80.00,
11     "availableSpecial": {
12       "specialId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
13       "specialPrice": 60.00,
14       "specialLabel": "25% OFF for 3 months" },
15     "availableTotal": 7,
16     "availableAtThisPrice": 3,
17     "totalInGroup": 10,
18     "reservedTotal": 1,
19     "areaInSquareFeet": 160,
20     "onlineMoveInUrl": "https://portal.quikstor.com/en/move-in/test/west?
      unitGroupId=3fa85f64-5717-4562-b3fc-2c963f66afa6&price=80.00" },
21   {
22     "unitGroupId": "abc12345-5717-4562-b3fc-2c963f66afa6",
23     "name": "5' x 5'",
24     "featuredFeatures": [ "Drive-up" ],
25     "features": {
26       "UnitType": "Storage",
27       "Width": "5",
28       "Depth": "5",
29       "Floor": "1" },
30     "regularPrice": 50.00,
31     "availableTotal": 5,
32     "availableAtThisPrice": 5,
33     "areaInSquareFeet": 25,
34     "onlineMoveInUrl": "https://portal.quikstor.com/en/move-in/test/west?
      unitGroupId=abc12345-5717-4562-b3fc-2c963f66afa6&price=50.00" }
35 ]
```

3.5 Read Unit Groups Unit Reservation Settings

This endpoint retrieves the maximum number of days a reservation can be made for. Reservation attempts not adhering to this setting will fail. The endpoint is provided as a way to allow pre-validation of user input, in particular whether the day the reservation should be made until falls within the allowed period. Note that some response elements are optional and may be not present in the response body.

The following request should be sent:

Endpoint: `GET /api/v1/companies/{companyCode}/facilities/{facilityCode}/unit-groups/reservations/settings`
(Continued)

Request Body: None

Response Body:

```
1 {  
2   "reservationMaximumDaysAhead": integer  
3 }
```

3.5.1 Model Details (Unit Groups Unit Reservation Settings)

Element name	Type	Notes
ReservationMaximumDaysAhead	integer	This specifies the maximum length of a reservation in days. Value of 0 means until today at midnight.

Table 3.10: Response Model for 3.5. Read Unit Groups Unit Reservation Settings

3.5.2 Examples (Read Unit Groups Unit Reservation Settings)

Example URL:

`/api/v1/companies/test/facilities/west/unit-groups/reservations/settings`

Example Response Body:

```
1 {  
2   "reservationMaximumDaysAhead": 3  
3 }
```

3.6 Reserve a Unit from Unit Group Listing

This endpoint allows reserving a unit present in the Unit Group Listing (see: 3.4. List Available Unit Groups). If multiple units are available in the same Unit Group, the reserved unit will be randomly picked from the pool that matches the provided specification: Unit Group must match, Regular Price must match and the Special Available (if provided) must match.

Note: It is possible for a unit selected for reservation to become unavailable during processing of the request. In such an event, a response with Status Code 409 will be provided. If the unit group has other units available at this price with this special, you can retry the request and a different unit from the pool will be selected for reservation.

The following request should be sent:

Endpoint: **POST /api/v1/companies/{companyCode}/facilities/{facilityCode}**

(Continued) **/unit-groups/reservations**

Request Body:

```
1 {
2   "unitGroupId": uuid, required,
3   "matchRegularPrice": double precision, required,
4   "matchSpecialAvailable": uuid, optional,
5   "firstName": string, required,
6   "lastName": string, required,
7   "email": string, required,
8   "phoneNumbers": list of PhoneNumber, at least 1 item required,
9   "accountType": specific string, required,
10  "companyName": string, conditionally required,
11  "leadSourceId": uuid, conditionally required,
12  "reservedUntil": date string in YYYY-MM-DD format
13 }
```

Response Body:

```
1 {
2   "reservationId": uuid,
3   "reservedUnitNumber": string,
4   "tenantId": uuid
5 }
```

3.6.1 Model Details (Reserve a Unit from Unit Group Listing)

Element name	Type	Notes
CountryCode	string	Including preceding plus symbol (i.e. "+1")
Number	string	Only digits. No spaces or special characters
Type	specific string	Values allowed: "Cell", "Office", "Home"

Table 3.11: [PhoneNumber](#) Model for 3.6. Reserve a Unit from Unit Group Listing.

Element name	Type	Notes
UnitGroupId	uuid	Required. This is the group from which a unit to reserve will be selected.
MatchRegularPrice	double precision	Required. This is the regular price of the unit to be reserved. This is necessary because there may be several units with different prices in the same unit group.
MatchSpecialAvailable	uuid	Not required. If provided, only units that have the provided special available will be considered for reservation. Not all units within the same unit group have the same specials available.
FirstName	string	Required. Reservee's details.
LastName	string	Required. Reservee's details.
Email	string, email	Required. Reservee's details.
PhoneNumbers	List of PhoneNumber models	Required with at least 1 entry. Reservee's details. See: PhoneNumber Model.
AccountType	specific string	Required. Reservee's details. Values allowed: "Individual" and "Company"
CompanyName	string	Required if AccountType is Company. Reservee's details.
LeadSourceId	uuid	The id of the Lead Source to be used for reservation. May be required depending on facility settings. Must match an existing Lead Source. See: 3.3. List Facility Lead Sources.
ReservedUntil	date string: yyyy-mm-dd	Required. Reservation will be valid until the end of the date specified.

Table 3.12: Request Body Model for 3.6. Reserve a Unit from Unit Group Listing.

Element name	Type	Notes
ReservationId	uuid	—
ReservedUnitNumber	string	May be presented to customers.
TenantId	uuid	Unique internal identifier of the reservee. May be an identifier of a pre-existing tenant.

Table 3.13: Response Model for 3.6. Reserve a Unit from Unit Group Listing

3.6.2 Examples (Reserve a Unit from Unit Group Listing)

Example URL:

```
/api/v1/companies/test/facilities/west/unit-groups/reservations
```

Example Request Body:

```
1 {
2   "unitGroupId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
3   "matchRegularPrice": 100.00,
4   "matchSpecialAvailable": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
5   "firstName": "Example",
6   "lastName": "Reservee",
7   "email": "example@email.com",
8   "phoneNumbers": [
9     {
10      "countryCode": "+1",
11      "number": "1231231234",
12      "type": "Cell"
13    }
14  ],
15   "accountType": "Individual",
16   "reservedUntil": "2024-02-17"
17 }
```

Example Response Body:

```
1 {
2   "reservationId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
3   "reservedUnitNumber": "T-313",
4   "tenantId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
5 }
```


Appendix A

Facility Amenities

Table A.1: Amenities List for 3.2. Read Facility Details.

Property name	Property type
AvailableTruckRental	boolean
AvailableFreeTruckRental	boolean
FreeTruckRentalMaxDistanceInMiles	integer
FreeTruckRentalInsuranceRequired	boolean
FreeTruckRentalInsuranceFee	double precision
HasLoadingDock	boolean
LoadingDockSizeInFeet	double precision
AvailableHandcartsOrDollies	boolean
HasElevator	boolean
MovingSuppliesForSale	boolean
VideoCamerasOnSite	boolean
ElectronicGateAccess	boolean
FencedAndLighted	boolean
ManagerLanguages	List of strings
Is24HourKioskAvailable	boolean
Is24HourManagerAvailable	boolean
Is24HourAccessAvailable	boolean
MailOrPackagesAcceptedForTenants	boolean
CashAccepted	boolean
CheckAccepted	boolean
CreditCardsAccepted	boolean

Continued on next page

Table A.1: Amenities List for 3.2. Read Facility Details. (Continued)

Property name	Property type
CreditCardTypesAccepted	List of strings
EmailInvoicingAvailable	boolean
AutomaticPaymentsAvailable	boolean
InvoicingScheme	string
SecurityDepositRequired	boolean
MilitaryDiscountsOffered	boolean
SeniorDiscountOffered	boolean
StudentDiscountOffered	boolean
InsuranceRequired	boolean
InsuranceAvailable	boolean
ProtectionPlanRequired	boolean
ProtectionPlanAvailable	boolean
InsuranceCertificateHonored	boolean
BandPracticeAllowed	boolean
PaperworkCanBeDoneRemotely	boolean
RequiresTitle	boolean
RequiresRegistration	boolean
RequiresInsurance	boolean
MustBeDrivable	boolean
MaintenanceAllowedOnProperty	boolean
WashStationAvailable	boolean
DumpStationAvailable	boolean
GeneralMaintenance	boolean
Propane	boolean
DieselAndGas	boolean
DoesStateInspections	boolean
AutoCleaningOrDetailing	boolean
HasAirPump	boolean
HasVacuumStation	boolean
HasIceMachine	boolean
HoseOrSpigotAvailable	boolean

Appendix B

Unit Group Features

Table B.1: Features List for 3.4. List Available Unit Groups.

Property name	Property type
Width	double precision
Depth	double precision
Height	double precision
UnitType	string
ClimateControlled	string
DoorType	string
HumidityControlled	boolean
Floor	boolean
HasElevatorAccess	boolean
HasStairAccess	boolean
HasLiftAccess	boolean
HasDriveUpAccess	boolean
IsSkybox	boolean
IsAdaAccessible	boolean
Has24HourAccess	boolean
HasLighting	boolean
HasElectricOutlets	boolean
HasAlarm	boolean
HasShelves	boolean
IsPremiumUnit	boolean