

ECE780_Assignment_2_Q1_python_code

June 12, 2024

```
[ ]: import numpy as np
import matplotlib.pyplot as plt
from progress.bar import Bar

class manipulator_control:
    def __init__(self, L, ML, IL, D, qd, qd_dot, q, q_dot, q_dot_dot, x, x_dot,
    ↪xd, xd_dot):
        # RR manipulator situation
        self.L = L # length of each link
        self.ML = ML # mass of each link
        self.D = D # distance between link center of mass and its origin
        self.IL = IL # inertia of each link
        self.qd = qd # desired joint anlge
        self.qd_dot = qd_dot # desired joint velocity
        self.q = q # initial joint anlge
        self.q_dot = q_dot # initial joint velocity
        self.q_dot_dot = q_dot_dot # initial joint acceleration

        self.x = x # end-effector position
        self.x_dot = x_dot # end-effector velocity
        self.xd = xd # desired end-effector position
        self.xd_dot = xd_dot # desired end-effector velocity
        self.g = 9.81 # gravity
        self.dt = 0.01 # delta time
        self.T = 3.0 # simulation time
        self.max_length = self.L[0][0] + self.L[1][0] # maximum length
        self.text = "assignment_2_Q1"

    def get_dynamics(self, q, q_dot):
        """
        Calculate the dynamic of the manipulator based on the joint anlge and
        ↪joint velocity

        :param np.ndarray q: joint angle
        :param np.ndarray q_dot: joint velocity
        :returns:
        - D (np.ndarray) - Inertia matrix
```

```

- C (np.ndarray) - Centrifugal and Coriolis matrix
- G (np.ndarray) - Gravity compensation
"""
ML1, ML2 = self.ML[0][0], self.ML[1][0] # mass of each link
D1, D2 = self.D[0][0], self.D[1][0] # distance between link center of
↳ mass and its origin
L1, L2 = self.L[0][0], self.L[1][0] # length of each link
IL1, IL2 = self.IL[0][0], self.IL[1][0] # inertia of each link
q1, q2 = q[0][0], q[1][0] # joint angle
q1_dot, q2_dot = q_dot[0][0], q_dot[1][0] # joint velocity

# Jvc1 = np.array([[ -D1*np.sin(q1), 0],
#                  [ D1*np.cos(q1), 0],
#                  [ 0, 0]])
# vc1 = Jvc1 @ q_dot
# Jvc2 = np.array([[ -D1*np.sin(q1)-D2*np.sin(q1+q2), -D2*np.sin(q1+q2)],
#                  [ D1*np.cos(q1)+D2*np.cos(q1+q2), D2*np.cos(q1+q2)],
#                  [ 0, 0]])
# vc2 = Jvc2 @ q_dot

# Jw1 = np.array([[ 0, 0],
#                  [ 0, 0],
#                  [ 1, 0]])
# w1 = Jw1 @ q_dot
# Jw2 = np.array([[ 0, 0],
#                  [ 0, 0],
#                  [ 1, 1]])
# w2 = Jw2 @ q_dot

# Inertia Matrix
# K1 (linear) = 0.5*ML1*vc1.T@vc1 + 0.5*ML2*vc2.T@vc2
# K1 (linear) = 0.5*ML1*Jvc1.T@q_dot.T@Jvc1@q_dot + 0.5*ML2*Jvc2.
↳ T@q_dot.T@Jvc2@q_dot
# K1 (linear) = 0.5*q_dot.T@(ML1*Jvc1.T@Jvc1 + ML2*Jvc2.T@Jvc2)@q_dot
# K2 (rotation) = 0.5*IL1*w1.T@w1 + 0.5*IL2*w2.T@w2
# K2 (rotation) = 0.5*IL1*Jw1.T@q_dot.T@Jw1@q_dot + 0.5*IL2*Jw2.T@q_dot.
↳ T@Jw2@q_dot
# K2 (rotation) = 0.5*q_dot.T@(IL1*Jw1.T@Jw1 + IL2*Jw2.T@Jw2)@q_dot
# K2 (rotation) = 0.5*q_dot.T@(np.array([[I1, 0],[0, 0]]) + np.
↳ array([[I2, I2],[I2, I2]]))@q_dot
# K2 (rotation) = 0.5*q_dot.T@(np.array([[I1+I2, I2],[I2, I2]]))@q_dot
# K (total) = K1 + K2
# K (total) = 0.5*q_dot.T@(ML1*Jvc1.T@Jvc1 + ML2*Jvc2.T@Jvc2)@q_dot + 0.
↳ 5*q_dot.T@(np.array([[I1+I2, I2],[I2, I2]]))@q_dot
# D = ML1*Jvc1.T@Jvc1 + ML2*Jvc2.T@Jvc2 + np.array([[I1+I2, I2],[I2,
↳ I2]])

```

```

# K (total) = 0.5*q_dot.T@D@q_dot
d11 = ML1*pow(D1,2)+ML2*(pow(L1,2)+pow(D2,2)+2*L1*D2*np.cos(q2))+IL1+IL2
d12 = ML2*(pow(D2,2)+L1*D2*np.cos(q2))+IL2
d21 = ML2*(pow(D2,2)+L1*D2*np.cos(q2))+IL2
d22 = ML2*(pow(D2,2))+IL2
D = np.array([[d11, d12],[d21, d22]])

# Centrifugal and Coriolis matrix
# cij = 0.5*(partial(dkj/qi)+partial(dki/qj)-partial(dij/qk))
# c111 = 0.5*(partial(d11/q1)+partial(d11/q1)-partial(d11/q1)) = 0.
↪ 5*(0+0-0) = 0
# c112 = 0.5*(partial(d21/q1)+partial(d21/q1)-partial(d11/q2)) = 0.
↪ 5*(0+0-(-2*ML2*L1*D2*np.sin(q2))) = ML2*L1*D2*np.sin(q2) = -h
# c121 = 0.5*(partial(d12/q1)+partial(d11/q2)-partial(d12/q1)) = 0.
↪ 5*(0+(-2*ML2*L1*D2*np.sin(q2))-0) = -ML2*L1*D2*np.sin(q2) = h
# c122 = 0.5*(partial(d22/q1)+partial(d21/q2)-partial(d12/q2)) = 0.
↪ 5*(0+(-ML2*L1*D2*np.sin(q2))-(-ML2*L1*D2*np.sin(q2))) = 0
# c211 = 0.5*(partial(d11/q2)+partial(d12/q1)-partial(d21/q1)) = 0.
↪ 5*((-2*ML2*L1*D2*np.sin(q2))+0-0) = -ML2*L1*D2*np.sin(q2) = h
# c212 = 0.5*(partial(d21/q2)+partial(d22/q1)-partial(d21/q2)) = 0.
↪ 5*((-ML2*L1*D2*np.sin(q2))+0-(-ML2*L1*D2*np.sin(q2))) = 0
# c221 = 0.5*(partial(d12/q2)+partial(d12/q2)-partial(d22/q1)) = 0.
↪ 5*((-ML2*L1*D2*np.sin(q2))+(-ML2*L1*D2*np.sin(q2))-0) = -ML2*L1*D2*np.
↪ sin(q2) = h
# c222 = 0.5*(partial(d11/q1)+partial(d11/q1)-partial(d11/q1)) = 0.
↪ 5*(0+0-0) = 0
h = -ML2*L1*D2*np.sin(q2)
# c111 = 0
# c112 = -h
# c121 = h
# c122 = 0
# c211 = h
# c212 = 0
# c221 = h
# c222 = 0

# ckj = summation(cijk(q)qi_dot)
# c11 = c111*q1_dot + c211*q2_dot = 0*q1_dot + h*q2_dot = h*q2_dot
# c12 = c112*q1_dot + c212*q2_dot = h*q1_dot + h*q2_dot = h*q1_dot +
↪ h*q2_dot
# c21 = c121*q1_dot + c221*q2_dot = -h*q1_dot + 0*q2_dot = -h*q1_dot
# c22 = c122*q1_dot + c222*q2_dot = 0*q1_dot + 0*q2_dot = 0
C = np.array([[h*q2_dot, h*q1_dot + h*q2_dot],
               [-h*q1_dot, 0]])

# Gravity component

```

```

    # P1 = ML1*g*D1*np.sin(q1)
    # P2 = ML2*g*(L1*np.sin(q1)+D2*np.sin(q1+q2))
    # P = P1 + P2
    g1 = (ML1*D1+ML2*L1)*self.g*np.cos(q1) + ML2*D2*self.g*np.cos(q1+q2) #
    ↪ partial derviative of (G/q1)
    g2 = ML2*D2*self.g*np.cos(q1 + q2) # partial derviative of (G/q2)
    G = np.array([[g1], [g2]])

    return D, C, G

def forward_kinematic(self, q):
    """
    Calculate the forward kinematic of the manipulator to find end-effector
    ↪ position based on the joint anlge

    :param np.ndarray q: joint angle
    :returns:
        - pos (np.ndarray) - end-effector of position
    """
    L1, L2 = self.L[0][0], self.L[1][0] # length of each link
    q1, q2 = q[0][0], q[1][0] # joint angle
    x = L1*np.cos(q1) + L2*np.cos(q1+q2)
    y = L1*np.sin(q1) + L2*np.sin(q1+q2)
    pos = np.array([[x], [y]])
    return pos

def jacobian(self, q):
    """
    Calculate the jacobian matrix of the manipulator based on the joint
    ↪ anlge

    :param np.ndarray q: joint angle
    :returns:
        - J (np.ndarray) - jacobian matrix
    """
    L1, L2 = self.L[0][0], self.L[1][0] # length of each link
    q1, q2 = q[0][0], q[1][0] # joint angle
    j11 = -L1*np.sin(q1)-L2*np.sin(q1+q2)
    j12 = -L2*np.sin(q1+q2)
    j21 = L1*np.cos(q1)+L2*np.cos(q1+q2)
    j22 = L2*np.cos(q1+q2)
    J = np.array([[j11, j12], [j21, j22]])
    return J

def main(self, Kp, Ki, Kd):
    """

```

*Implement joint space controller of type PD with gravity compensation
 ↪ in here and regulate the joint angle to desired angle*

```

:param float Kp: proportional joint angle error gain
:param float Ki: integral joint angle error gain
:param float Kd: derivative joint velocity error gain
"""

self.Kp = np.diag(np.array([Kp, Kp])) # pow(omega,2)
self.Ki = np.diag(np.array([Ki, Ki]))
self.Kd = np.diag(np.array([Kd, Kd])) # 2*zeta*omega
error = np.array([[0], [0]])
pos_x_list = []
pos_y_list = []
q1_list = []
q2_list = []
tau1_list = []
tau2_list = []
iteration_list = []
self.xd = self.forward_kinematic(self.qd)
with Bar('Processing... ', max=int(self.T/self.dt)) as bar:
    for i in range (int(self.T/self.dt)):
        # Get dynamic by current joint angle and joint velocity
        D, C, G = self.get_dynamics(self.q, self.q_dot)

        # Accumated error
        error = error + ((self.qd-self.q)*self.dt)

        # PID controller on control input torque
        tau = self.Kp @ (self.qd-self.q) + self.Kd @ (self.qd_dot-self.
↪q_dot) + self.Ki @ error + G

        # Calculate the joint acceleration by solving dynamic equation
        self.q_dot_dot = np.linalg.inv(D) @ (tau - C @ self.q_dot - G)

        # Update the joint angle and velocity
        self.q_dot = self.q_dot + self.q_dot_dot * self.dt
        self.q = self.q + self.q_dot * self.dt

        self.x = self.forward_kinematic(self.q)
        x = self.x[0][0]
        y = self.x[1][0]
        q1 = self.q[0][0]
        q2 = self.q[1][0]
        tau1 = tau[0][0]
        tau2 = tau[1][0]
        q1_list.append(q1)
        q2_list.append(q2)

```

```

        tau1_list.append(tau1)
        tau2_list.append(tau2)
        iteration_list.append(i)
        pos_x_list.append(x)
        pos_y_list.append(y)

        # Plot the movement
        self.plot_robot()
        bar.next()

print("Target joint angle: ", self.qd[0][0], self.qd[1][0])
print("Final joint angle: ", self.q[0][0], self.q[1][0])
print("Target position: ", self.xd[0][0], self.xd[1][0])
print("Final position: ", self.x[0][0], self.x[1][0])
self.plot_angle(q1_list, q2_list, iteration_list)
self.plot_tau(tau1_list, tau2_list, iteration_list)
self.plot_position(pos_x_list, pos_y_list, iteration_list)

def plot_robot(self):
    # Plot robotic arm movement
    x0, y0 = 0, 0
    x1 = self.L[0][0] * np.cos(self.q[0][0])
    y1 = self.L[0][0] * np.sin(self.q[0][0])
    x2 = x1 + self.L[1][0] * np.cos(self.q[0][0] + self.q[1][0])
    y2 = y1 + self.L[1][0] * np.sin(self.q[0][0] + self.q[1][0])

    plt.plot([x0, x1], [y0, y1], 'b-', label='Link 1')
    plt.plot([x1, x2], [y1, y2], 'g-', label='Link 2')
    plt.plot([x0, x1, x2], [y0, y1, y2], 'ro', label='Joint')

    plt.xlim(-self.max_length, self.max_length)
    plt.ylim(-self.max_length, self.max_length)
    plt.plot(self.xd[0][0], self.xd[1][0], 'yo', label='Desired Position')

    plt.legend()
    plt.savefig('script\\assignment\\assignment_2_picture\\{}_robotic_arm.
    ↪png'.format(self.text))
    plt.draw()
    plt.pause(0.01)
    plt.clf()

def plot_angle(self, q1_list, q2_list, iteration_list):
    fig, axs = plt.subplots(1, 1, figsize=(12, 6))
    # plot trajectory
    axs.plot(iteration_list, q1_list, label='q1') # joint angle 1
    axs.plot(iteration_list, q2_list, label='q2') # joint angle 2

```

```

        axs.axhline(y=qd[0], color='r', linestyle='--', label='qd1') # joint_
↪velocity 1
        axs.axhline(y=qd[1], color='g', linestyle='--', label='qd2') # joint_
↪velocity 2
        axs.set_xlabel('Time [{}s]'.format(self.dt))
        axs.set_ylabel('Joint Angles [rad]')
        axs.legend()
        plt.tight_layout()
        plt.savefig('script\\assignment\\assignment_2_picture\\{}_joint_angle.
↪png'.format(self.text))
        plt.show()

    def plot_tau(self, tau1_list, tau2_list, iteration_list):
        # plot torque
        fig, axs = plt.subplots(1, 1, figsize=(12, 6))
        axs.plot(iteration_list, tau1_list, label='tau1') # joint torque 1
        axs.plot(iteration_list, tau2_list, label='tau2') # joint torque 2
        axs.set_xlabel('Time [{}s]'.format(self.dt))
        axs.set_ylabel('Joint Torques [Nm]')
        axs.legend()
        plt.tight_layout()
        plt.savefig('script\\assignment\\assignment_2_picture\\{}_joint_torque.
↪png'.format(self.text))
        plt.show()

    def plot_position(self, pos_x_list, pos_y_list, iteration_list):
        # plot position
        fig, axs = plt.subplots(1, 1, figsize=(12, 6))
        axs.plot(iteration_list, pos_x_list, label='current x') # current_
↪position x
        axs.plot(iteration_list, pos_y_list, label='current y') # current_
↪position y
        axs.axhline(y=self.xd[0], color='r', linestyle='--', label='desired x')_
↪# desired position x
        axs.axhline(y=self.xd[1], color='g', linestyle='--', label='desired y')_
↪# desired position y
        axs.set_xlabel('Time [{}s]'.format(self.dt))
        axs.set_ylabel('Position [m]')
        axs.legend()

        plt.tight_layout()
        plt.
↪savefig('script\\assignment\\assignment_2_picture\\{}_joint_position.png'.
↪format(self.text))
        plt.show()

```

```

L = np.array([[1.0], [0.5]], dtype=float) # length of each link
ML = np.array([[0.1], [0.05]], dtype=float) # mass of each link
D = np.array([[0.5], [0.25]], dtype=float) # distance between link center of
↳mass and its origin
IL = np.array([[0.1], [0.05]], dtype=float) # inertia of each link
q = np.array([[0.5], [1]], dtype=float) # initial joint angle
qd = np.array([[-2*np.pi/3], [2*np.pi/3]], dtype=float) # desired joint angle
q_dot = np.array([[0], [0]], dtype=float) # initial joint velocity
qd_dot = np.array([[0], [0]], dtype=float) # desired joint velocity
q_dot_dot = np.array([[0], [0]], dtype=float) # initial joint acceleration
x = np.array([[0], [0]], dtype=float) # initial end-effector position
x_dot = np.array([[0], [0]], dtype=float) # initial end-effector velocity
xd = np.array([[0], [0]], dtype=float) # desired end-effector position
xd_dot = np.array([[0], [0]], dtype=float) # desired end-effector velocity
sim = manipulator_control(L, ML, IL, D, qd, qd_dot, q, q_dot, q_dot_dot, x,
↳x_dot, xd, xd_dot)
Kp = 6.0
Ki = 0.0
Kd = 2.0
sim.main(Kp, Ki, Kd)

```