

OneLink Remote Administration

Foreman

OneLink remote deployment, database & service management

User Guide

A complete guide to installing, connecting, and operating the Foreman administration tool for OneLink Linux servers over SSH.

Version 1.0.0 · Updated September 17, 2026

Contents

- | | |
|----------------------------------|---|
| 1. Overview & concepts | 7. Database tab |
| 2. Installing & launching | 8. Certificates tab |
| 3. The main window | 9. Package tab |
| 4. Managing servers | 10. SSH Console |
| The Servers grid & row actions | 11. Edit File |
| Per-server right-click menu | 12. Configuration: Template, Export, Import |
| Connecting & disconnecting | 13. Efficiency Recorder |
| 5. Server resources & health | 14. Troubleshooting |
| 6. Target servers (multi-select) | 15. Reference tables |

1. Overview & concepts

Foreman is a single, self-contained Windows application for administering OneLink Linux servers remotely over SSH. From one screen you can connect to several servers at once and perform database, certificate, package and service operations without opening a terminal.

Key ideas

Server	One Linux host (an IP / hostname) you connect to over SSH. You can add many.
Role (mark)	A label you attach to a server telling Foreman what it is for: AppServer, Concentrator, ReportServer, nConnect, Database master, Database slave, or Auxiliary Service. Roles drive which packages and services apply.
Target server	The server(s) an operation runs against. Each Operations tab has a multi-select target picker.
Server operations	The OneLink server tasks (database export/import, service start/stop, SSL config, etc.). Foreman performs these directly over SSH -- it does not depend on the server-side nmenu menu being present.

Everything is judged by outcome, not exit code. OneLink's server scripts often exit non-zero for cosmetic reasons, so Foreman verifies success by the actual result (file present, service active, package in the database) rather than trusting the exit code.

2. Installing & launching

2.1 Standalone EXE & requirements

- Foreman ships as a single .exe. There is nothing to install -- copy it anywhere and run it.
- No external dependencies. The SSH engine (Posh-SSH) is embedded inside the EXE and is unpacked automatically on first run to %LOCALAPPDATA%\OneLinkAdminTool\Modules.
- Requires Windows with the .NET Framework (4.5+), which is present on all supported Windows versions.
- The only files Foreman writes are its log files and any backups / config files you export.

2.2 First launch

Double-click the EXE. The main window opens with an empty Servers grid. If a dependency needed unpacking you may briefly see a one-time "dependency ready" message.

2.3 Passwordless sudo (automatic)

Most operations (package install, service control, SSL, MySQL) need passwordless sudo. When you connect, if the account doesn't already have it, Foreman enables it once using the same login password -- it writes /etc/sudoers.d/one-link-admin-tool (the same drop-in a properly-built OneLink image ships). After that, every operation runs without prompting.

If sudo can't be enabled (wrong password, or the account isn't a sudoer), the server's Status shows "sudo unavailable" and package/service/MySQL operations will fail until sudo is granted on the server.

3. The main window

3.1 Header, footer & version

- Header (blue-violet band): the Foreman logo and title, and a "OneLink Remote Administration" badge.
- Footer (dark bar): the product name, the Efficiency Recorder button, the Change Log Folder button, the version, the last-update date, and a live status word (Ready).

3.2 Activity Log

The dark Activity Log panel at the bottom records every action with a timestamp and level (INFO / SUCCESS / WARNING / ERROR). Passwords are automatically masked. Use Clear Log to empty the on-screen view and Open Log to open the log file on disk.

3.3 Log folder location

Click Change Log Folder (footer) to choose where Foreman saves its logs. Your choice is remembered across restarts (stored in %LOCALAPPDATA%\OneLinkAdminTool\preferences.json). Until you set one, logs go to a Logs folder beside the EXE. Three logs are written per session: the activity log, an efficiency log, and a metrics log.

4. Managing servers

4.1 The Servers grid & row actions

Each row is one server. Columns:

Column	Purpose
Server IP / Host	The IP or hostname. Type directly in the cell.
Port	SSH port (default 22).
Username	SSH login user.
Password	Click the cell to set the SSH password (masked).
Roles (mark)	Click to tick one or more roles for this server.
OneLink Services	The OneLink services discovered on the server; the ■ button re-scans.
Resources	A coloured health pill; click to see disk / memory / CPU details.
Status	Connection state, plus the health summary.

Column	Purpose
Actions	Console and Edit File buttons that open those tools for that server directly (see sections 10 and 11).

Columns are resizable -- drag a column border. A horizontal scrollbar appears automatically if the content is wider than the window.

4.2 Adding & clearing rows

- Add Row -- adds a blank server row.
- Clear All -- removes every server row (asks you to confirm first, and disconnects any open sessions).
- To remove a single server, right-click its row (section 4.4).

4.3 Passwords & shared login

Click a row's Password cell to open the password dialog. Tick Show password to verify what you typed; the password is held only in memory for the session. When many servers share the same credentials, click Same login for all, enter a username and/or password once, and apply it to every row (or only the selected rows). Leave a field blank to keep the existing value.

Click a Roles (mark) cell and tick the purposes that apply. A server can carry several roles (e.g. AppServer + Database master). Roles determine which packages match in the plan and which services appear for control.

4.4 Per-server right-click menu

Right-click any server row for quick actions that target that exact server (no picker). The menu shows the server's IP at the top, and only the actions that apply are enabled:

Item	What it does
Command Console	Opens the SSH console on that server (section 10).
Connect / Disconnect	Connects or disconnects just that one server.
Reconnect	Disconnects and reconnects (handy after a reboot).
View Resources	Opens the disk / memory / CPU popup for that server.
Copy IP	Copies the server's IP to the clipboard.
Remove from list	Removes that single row (disconnecting it first).

4.5 Connecting & disconnecting

- Fill in IP, Port, Username; set the Password; mark Roles.
- Click Connect All (or Connect on a single row's right-click). Foreman opens SSH sessions, detects the OS, enables sudo, and discovers services.
- The Status shows "Connected" and the connection summary shows "N of M servers connected."

- Click Disconnect All to close every session.

[NEW] If a server was rebuilt and its SSH identity changed, Foreman recognises this and reconnects automatically instead of failing with a confusing error.

5. Server resources & health

5.1 The health pill

After a server connects, the Resources column becomes a coloured pill reflecting disk and memory usage:

Pill	Meaning
OK	All partitions below 85% used and memory below 85% used.
CAUTION	Any partition $\geq 85\%$ used, or memory $\geq 85\%$ used.
CRITICAL	Any partition $\geq 95\%$ used, or memory $\geq 95\%$ used.

The same state is shown in the Status column (e.g. "Connected • Health: OK"). Health is refreshed on connect, on a services refresh, and whenever you open the Resources popup.

5.2 Resources popup

Click the pill (or use View Resources in the right-click menu) to open a popup listing disk partitions (size / used / available per mount), memory, and CPU / uptime.

6. Target servers (multi-select)

Each Operations tab (Database, Certificates, Package) has a Target server picker -- a button that opens a checkbox list of connected servers.

- Tick All servers to act on every eligible connected server (the default).
- Or tick specific servers (e.g. 4 of 10). Ticking individual servers clears "All", and vice-versa.
- The button shows the current selection (All servers / N servers / a single host).
- The Database picker only lists servers marked Database master or Database slave.

7. Database tab

7.1 MySQL service control

Pick the target, then use Restart, Stop, or Get Status of Database. On RHEL, a first-time Restart performs the full MySQL enable sequence (create data/log dirs, SELinux labels, start, remove strict password policy, open port 3306, enable service). On Debian it does a plain restart. Success is judged by `systemctl is-active`.

7.2 Create Database

Enter a Database Name and click Create Database. Runs against the selected Database target(s).

7.3 Create Database User

Enter a username and password (with confirm). Optionally tick Allowed IP to restrict the user to a host (% = any, localhost, or a specific IP populated from the selected target). Click Create DB User.

7.4 InnoDB Buffer Pool Size [NEW]

Tune the MySQL `innodb_buffer_pool_size` setting for the selected target, the same way nmenu's "Configure InnoDB buffer pool size" option did -- but without depending on nmenu being present.

- Click Check Current / Recommended to load the current buffer pool size, Total RAM, Available RAM, and the recommended maximum (75% of Total RAM) for the target server.
- Enter a new size in the New Size box. Accepted formats: 1.5G, 500M, 2GB, 1.5g, 500mb -- upper or lower case, with or without the trailing "B".
- A caution box updates live as you type: it turns green and says "OK" when the value is within the recommended maximum, or red with "CAUTION" if it exceeds it.
- Click Apply (Restarts MySQL). Foreman rounds the value to the nearest 128 MB (the size MySQL actually allocates in), confirms with you, backs up the configuration file, writes the new value, and restarts MySQL. If the restart fails, the previous configuration is restored automatically and MySQL is started again.

A buffer pool size change only takes effect after a MySQL restart, because it lives in the configuration file, not a live setting -- Apply always restarts the service for you.

Applying a value above the recommended maximum is blocked, not just warned -- re-enter a smaller size to continue.

7.5 Run SQL Script [NEW]

Run an existing .sql file that is already on the target server against its database -- the equivalent of nmenu's "Run a .sql script" option, with a whole-server search added.

- Type part of the file name in Search (name contains) -- e.g. "test" -- and click Search. Foreman searches the entire target server (skipping virtual filesystems like /proc and /sys) for matching .sql files, case-insensitively, so `test.sql`, `TEST.sql` and `Test_v2.sql` are all found.
- Pick a result under Found scripts.
- Click Run Script. You are asked to confirm, because the script can change or delete data.
- A progress window opens immediately and shows status while the script runs (large scripts can take a while); it cannot be closed until the run finishes.
- When it finishes, the window shows either a success confirmation, or a plain-language explanation of what went wrong (unknown table, SQL syntax error, duplicate entry, foreign key violation, permission denied, MySQL not running, etc.) followed by the full output from MySQL.

Only one SQL script runs at a time; run another once the current one finishes.

7.6 Grant Admin Privileges

Pick a User and Database (use Refresh users / databases to load the lists), optionally set a password, and click Grant Privileges. System/root users are intentionally excluded from the list.

7.7 Export Database (backup)

- Choose the Database to back up.
- Choose a Destination: Server (path on the VM), Local Windows (this PC), or a Network path.
- Set the Backup file path (Browse for a local/network destination).
- Click Export DB. The job runs in the background; watch the status line. Use Stop to cancel.

If the export says a file was not created: the database name you selected probably has nothing to export (wrong/empty DB). Foreman reports the underlying reason so you can see what happened.

7.8 Import Database (restore)

Choose the target Database, the Source (Server path, Local Windows, or Another VM), and the Backup file, then click Import DB. Runs in the background with a Stop button. A restore overwrites data -- be sure of the target.

Only one backup/restore runs at a time. If one is in progress the other export/import buttons are blocked until it finishes (or you Stop it).

8. Certificates tab

8.1 Deploy a certificate / license

Foreman deploys certificates and licenses (.pem .crt .cer .der .cert .ca .p7b .csr .ks .jks .p12 .pfx .lic .key and more).

- Pick the target server(s).
- Choose the Cert / License file (local or a network path) via Browse.
- Set the Destination (server path) where the file should be installed.
- Click Deploy.

8.2 Network login

If the file lives on a network share that needs credentials, tick Network login and enter the User and Password (the fields are disabled until you tick it). Use Test login to confirm access -- it first checks whether the path is already reachable with your current Windows sign-in (often it is, and no separate login is needed).

8.3 List & check status

Type a Folder / file on server, click List files to find certs / keystores / licenses there, pick one under Found files, then Check Status.

[IMPROVED] List files now finds all matching files in a folder -- including root-owned files and names with spaces or brackets (e.g. "license (3).lic") -- across every certificate, keystore and license format. If a folder can't be read, you get a clear "permission denied" message instead of an empty result.

Foreman identifies each file by content and reports what it actually is:

File type	What you see
X.509 certificate	Subject, Issuer, Expiry, a health line (days left), SHA-256 fingerprint.
Certificate request (CSR)	Subject.
Private / public key	Identified as a key (with size) -- keys have no expiry.
Java keystore (.ks/.jks/.p12/.pfx)	Alias, owner, issuer, validity.
License / other	File type, size, and a short preview.

9. Package tab

The Package tab shows the Service Installer (left) and Package Source (right) side by side, with the deployment plan below.

9.1 Service Installer & actions

- Pick the target server(s).
- Optionally type in Find to filter the service list; use Select all / Deselect all on the shown services.
- Tick the services you want.
- Use Check Service Status (read-only), Check Details (version), or pick an Action (Restart / Stop) and click Start / Restart / Stop Service.

Filter + selection: actions apply only to services that are ticked and currently visible. If you filter to "one" and tick onelink-appserver, only that service is acted on -- services hidden by the filter are not affected even if they were ticked before.

9.2 Auxiliary (non-OneLink) services

Mark a server with the Auxiliary Service role to manage non-OneLink apps (nginx, postgresql, a custom package...). Foreman auto-discovers the server's non-OneLink service units so they appear in the Service Installer, and controls them with plain systemctl. There is no SSL step for auxiliary apps.

9.3 Package Source

Folder	A local folder or a network path holding the .rpm / .deb packages (tick Network login if the share needs credentials; Test login to verify).
---------------	--

Remote Directory	The Linux directory packages are uploaded to (default /tmp/onelink-admin-tool).
Installation Mode	Install or Upgrade.
Install Reason	The compliance reason recorded on the server.

9.4 Build / Refresh plan

Click Build / Refresh Plan. Foreman lists one row per role-marked connected server, auto-matches the best package by role and OS, and shows the Size of each selected package. You can change the package per row (or set it to (skip)), remove rows, or clear the plan.

9.5 Upload & Install

Upload Only copies the packages to the remote directory. Upload and Install also installs and verifies each against the package database (a genuine downgrade is warned about and must be explicitly accepted). Optionally tick Enable & start service after install.

9.6 SSL after install

The SSL after install option (No change / Enable / Disable) applies to Concentrator and Report Server (Foreman edits activemq.xml directly) and the OneLink Appserver (via app.properties) after a successful install. Restart the affected service to apply. Auxiliary apps are unaffected.

Enabling SSL on the Concentrator requires a keystore (client.ks) -- deploy one on the Certificates tab first.

10. SSH Console

[NEW] Run commands directly on a server from inside Foreman -- no PuTTY or separate SSH client needed for routine work.

Open it from a server row's Console button, or right-click the row → Command Console. With more than one server connected you'll be asked which one; with a single server it opens straight away.

- Type a command and press Enter (or click Run). Output appears in the terminal-style panel.
- It runs on a persistent session, so cd, environment and passwordless sudo carry over between commands.
- The window is non-modal -- keep it open while you use the rest of Foreman, and open more than one (e.g. a console per server).
- Clear empties the output; Close ends the session.

The console is for commands and their output -- it is not a full terminal emulator. Full-screen programs (nano, vim, top, less, man...) are politely refused with a message instead of freezing the console; use PuTTY for those. Pagers are disabled automatically so commands like "git log" or "systemctl status" don't hang.

11. Edit File

[NEW] Open, edit and save any text file on a server without logging in manually -- the file's owner and permissions are preserved and a backup is made automatically.

Open it from a server row's Edit File button, or right-click the row. Then:

- Enter the file path (e.g. /opt/onelink-concentrator/conf/activemq.xml) and click Load.
- Edit the content in the editor.
- Click Save. A backup is written and the original owner/permissions are kept unchanged.

Works with any text file regardless of extension (.xml .properties .conf .java .py .sh .html .json .yaml ...). Binary files are safely declined. You can optionally have a service restarted right after saving.

11.1 Find a file by name

Don't know the path? Type just the file name (or a wildcard like *.properties) and click Find. Foreman searches the server and lists every matching location -- pick one to load it. The search is tolerant of spacing, brackets and case, so typing "license 3.lic" also finds "license (3).lic" or "license(3).lic". Press Enter in the path box to Load (full path) or Find (a name).

12. Configuration: Template, Export, Import

Foreman saves and loads its configuration as a colour Excel workbook (.xlsx) with a separate tab per section.

Template	Saves a blank fill-in .xlsx with example rows/values and every option, across tabs: Servers, Database, Package, Certificate, Service.
Export Config	Saves the current configuration as a colour .xlsx (re-importable). The Password column is left blank by design.
Import Config	Loads a .xlsx (or an older .csv) back into the tool -- server rows and all form settings.

Edit the workbook in Excel, add each server's password in the Servers tab, then use Import Config. Servers can be replaced or appended.

13. Efficiency Recorder

The Efficiency Recorder (footer) is an internal productivity tool. It opens a small panel where you can start/stop capturing, open the Metrics tab, and export a report. When capturing is on, Foreman records, per completed activity, the number of clicks, the distinct fields you edited, and the active (non-idle) time. The Metrics tab lists each activity; the footer shows a live "Recording" readout. Capturing is off until you enable it.

14. Troubleshooting

Symptom	Cause & fix
"sudo unavailable" in Status	The login password was rejected by sudo, or the account isn't a sudoer. Grant sudo/NOPASSWD on the server.
Connection fails with a message like "wrong username or password" / "can't reach server" / "server identity changed"	Foreman now shows a plain-language reason. Fix the credential, network/VPN, or (for a rebuilt server) simply reconnect -- the changed SSH identity is handled automatically.
Test login "Login FAILED" on a domain/DFS path	You likely already have access with your current Windows sign-in -- untick Network login. The real Windows error is shown to guide you.
Export says a file wasn't created	The selected database has nothing to export (wrong/empty name). Pick the correct database; Foreman shows the underlying message.
"A backup/restore is already running"	Only one runs at a time. Wait for it, or click Stop.
"A SQL script is already running"	Only one SQL script (section 7.5) runs at a time. Wait for the progress window to finish, or note that the Run Script button re-enables automatically once it does.
A command doesn't work in the SSH Console	Full-screen programs (nano/vim/top/less) aren't supported there -- use the Edit File tool for files, or PuTTY for full-screen apps.
Log files aren't where you expect	Check the Change Log Folder button's tooltip for the current path; set a new one if needed.

15. Reference tables

Roles & services

Role	Service (systemd)	Notes
AppServer	onelink-appserver	Base onelink package.
Concentrator	onelink-concentrator	SSL via activemq.xml.
ReportServer	onelink-report-server	SSL via ssl.properties.
nConnect	onelink-nconnect	
Database master / slave	-- (MySQL)	Only these appear in the Database target picker.
Auxiliary Service	auto-discovered	Non-OneLink apps; plain systemctl; no SSL.

Files & locations

Item	Location
Embedded SSH module	%LOCALAPPDATA%\OneLinkAdminTool\Modules
Saved preferences (log folder)	%LOCALAPPDATA%\OneLinkAdminTool\preferences.json
Default logs	Logs folder beside the EXE (or your chosen Log Folder)
Server-side temp (uploads/backups)	/tmp/onelink-admin-tool (created automatically)
Sudo drop-in	/etc/sudoers.d/onelink-admin-tool
InnoDB config file (section 7.4)	/etc/mysql/mysql.conf.d/zz-aristocrat.cnf

Health thresholds

State	Disk (any partition)	Memory
OK	< 85% used	< 85% used
CAUTION	≥ 85% used	≥ 85% used
CRITICAL	≥ 95% used	≥ 95% used

InnoDB buffer pool sizing (section 7.4)

Item	Rule
Accepted size formats	1.5G, 500M, 2GB, 1.5g, 500mb (case-insensitive; G/GB or M/MB)
Recommended maximum	75% of the target server's Total RAM
Applied value	Rounded to the nearest 128 MB
Takes effect	After MySQL restarts (done automatically by Apply)
If MySQL fails to restart	The previous configuration is restored and MySQL is started again