```
Checkresult (s[i]) ;
    if (s[i].marks >= highest)
    {
        highest = s[i].marks ;
    }
}

cout << "highest marks : " << highest << endl;
return 0;
}.
```

Ans

```
# include <iostream>
using namespace std;
class student {
  public:
    int id;
    int marks;
    void setdata (void) {
      cout << "Enter id : ";
      cin >> id;
      cout << "Enter marks: ";
      cin >> marks ;
    }

    void show data (void)
    {
      cout << "id : " << id << endl << "marks : " << marks
        << endl ;
    }
};

void check result (student O) {
    if (O.marks >= 40 )
      { cout << "pass " << endl;
    }
    Else {
      cout << "fail! " << endl;
    }
}

int main () {

  student s[5] ;
  int highest = 0 ;
  for (int i=0 ; i<5 ; i++ ) {
      s[i]. setdata ();
  }
  for (int i=0 ; i<5 ; i++)
  {  cout << " ----------------------" << endl
```

② Pass By reference

void modify(student &s)

- No copy is made.
- function work on original object

Example

```
class Student {
    public:
        int marks;
};
void update (student &s) {// reference
    s.marks = 100;
}
int main () {
    Student s1;
    s1.marks = 50;
    update( s1);
    cout << " updated Marks:" << s1.marks;
    return 0;
}
```

100

③ ~~Pass By Pointers~~

~~void update (student *s)~~

Problem Statement: Student Management System.

- Creat Class student
- data member id, marks
- Input data and print it
- use Array to input and print
- Creat function out side Class Marks > 90 (Pass)
- call function in loop chude Pass Fail

Passing object as functional argument

There are three ways to pass an object

① Pass By value

void display(student s)

- here a copy of object is created
- Orignal object will not change.

Example

```
#include <iostream>
using namespace std;
class student {
  public:
    int marks;
    void setMarks (int m) {
        marks = m;
    }
};

void show( student s) {
    cout << " Marks: " << s.marks << endl;
}

int main () {
    student s1;
    s1. setMarks (80);
    show (s1);
    return 0;
}.
```

- slower (Because copy is made)
- safer (Orignal data unchanged)

Day-17 (Array of objects & passing object as function)

Arrays of object in cpp.

int arr[5]; Just like this we can store 5 object like - $\boxed{\text{classname obj[5];}}$

Problem take details (ID) of 5 employee and print them all :

```
#include <iostream>
using namespace std;
class Employee {
    int id;

    public:
    static int count;
    void setid (void){
        cout << " Enter id of Employee : " ;
        cin >> id ;
        count++ ;
    }
    void getid (void){
        cout << " id of Employee " << count << " is " << id <<
    }
};
int Employee :: count=0;
int main (){
    Employee e[5] ;
    for (int i= 0; i<5; i++ ){
        e[i]. setid() ;
        e[i] . getid() ;
    }
    return 0 ;
}
```