Problem Statement: Shop item list

- add items
- store them as object
- display all items.

s1 → gets memory for id and age
s → gets separate memory for its id and age.

Member function are shared

- functions are stored only ones
- All object use the same functions

```
Class Test {
  Public:
      int a;
  void show () {
      Cout << a;
  }
};
```

- a → separate for each other
- show() → shared by all objects.

Object size

object size = sum of all data members

```
Class Demo {
    int a;
    float b;
    char c;
};
```

size = int(4 bytes) + float(4 bytes) + Char(1 bytes) = 9 bytes.

we can check by using

```
Cout << sizeof(Demo);
```

Multiple object memory

Student arr[3]

memory
[id age] [id age] [id age]

```
void show() {
        secret(); // allowed (nesting)
};
int main() {
    Example obj;
    obj.show();  //works
}
```

but
obj.secret(); X

Problem statement: Binary Checker Program (C++)

101011 102011 12A1 A1_12

Binary these are not
contains only 1 and 0;

Day-15 (Objects Memory Allocation & Using Arrays) in classes

When you create a object of a class, memory is allocated to store
- its data member (variable)
- (functions are not stored inside each object)
- Each object get separate memory

Ex.
```
Class student {
    public :
        int id;
        int age;
    };
int main() {
        student s1, s2 ;
}
```